

# HP71

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				
<b>Black Sidewall</b>																	
<b>22"</b>	* 285/45 R22 114H	9.5	9.0 - 10.5	3.5	51	1060	2337	285	11.2	815	32.1	*	*	379	2486	* * *	*
<b>20"</b>	* 275/55 R20 113H	8.5	7.5 - 9.5	3.5	51	1150	2535	284	11.2	810	31.9	*	*	372	2471	* * *	*
	* 265/50 R20 XL 111V	8.5	7.5 - 9.5	3.4	50	1090	2403	277	10.9	774	30.5	8.8	11.1	358	2361	* * *	O
	* 255/50 R20 XL 109V	8.0	7.0 - 9.0	3.4	50	1030	2271	265	10.4	764	30.1	8.8	11.1	354	2330	* * *	O
	* 255/55 R20 110H	8.0	7.0 - 9.0	3.5	51	975	2149	265	10.4	788	31.0	*	*	363	2403	* * *	*
	* 245/50 R20 102V	7.5	7.0 - 8.5	3.5	51	850	1874	253	10.0	754	29.7	*	*	350	2300	* * *	*
	* 235/55 R20 102H	7.5	6.5 - 8.5	3.5	51	850	1874	245	9.6	766	30.2	*	*	355	2336	* * *	*
<b>19"</b>	* 265/50 R19 XL 110V	8.5	7.5 - 9.5	3.4	50	1090	2403	277	10.9	774	30.5	8.8	11.1	355	2361	* * *	O
	* 255/50 R19 XL 107V	8.0	7.0 - 9.0	3.4	50	975	2149	265	10.4	739	29.1	8.8	11.1	341	2254	* * *	O
	* 255/60 R19 109H	7.5	7.0 - 9.0	3.5	51	1030	2271	260	10.2	789	31.1	*	*	361	2406	* * *	*
	* 245/50 R19 XL 105V	7.5	7.0 - 8.5	3.4	50	925	2039	253	10.0	729	28.7	8.8	11.1	337	2223	* * *	O
	* 235/45 R19 95H	8.0	7.5 - 9.0	3.5	51	690	1521	236	9.3	695	27.4	*	*	324	2120	* * *	*
	* 235/50 R19 XL 103V	7.5	6.5 - 8.5	3.4	50	875	1929	245	9.6	719	28.3	8.8	11.1	333	2193	* * *	O
<b>18"</b>	* 235/55 R19 101H	7.5	6.5 - 8.5	3.5	51	825	1819	245	9.6	741	29.2	8.8	11.1	342	2260	* * *	O
	* 265/60 R18 110V	8.0	7.5 - 9.5	3.5	51	1060	2337	272	10.7	775	30.5	8.8	11.1	353	2364	* * *	O
	* 255/55 R18 XL 109V	8.0	7.0 - 9.0	3.4	50	1030	2271	265	10.4	737	29.0	8.8	11.1	338	2248	* * *	O
	* 255/60 R18 108V	7.5	7.0 - 9.0	3.5	51	1000	2205	260	10.2	763	30.0	8.8	11.1	348	2327	* * *	O
	* 245/55 R18 103V	7.5	7.0 - 8.5	3.5	51	875	1929	253	10.0	727	28.6	8.8	11.1	334	2217	* * *	O
	* 245/60 R18 105V	7.0	7.0 - 8.5	3.5	51	925	2039	248	9.8	751	29.6	8.8	11.1	343	2291	* * *	O
	* 235/50 R18 97V	7.5	6.5 - 8.5	3.5	51	730	1609	245	9.6	693	27.3	8.8	11.1	321	2114	* * *	O
	* 235/55 R18 XL 104V	7.5	6.5 - 8.5	3.4	50	900	1984	245	9.6	715	28.1	8.8	11.1	329	2181	* * *	O
	* 235/60 R18 XL 107V	7.0	6.5 - 8.5	3.4	50	975	2149	240	9.4	739	29.1	8.8	11.1	339	2254	* * *	O
	* 225/55 R18 98V	7.0	6.0 - 8.0	3.5	51	750	1653	233	9.2	705	27.8	8.8	11.1	325	2150	* * *	O
<b>17"</b>	* 225/60 R18 XL 104V	6.5	6.0 - 8.0	3.4	50	900	1984	228	9.0	727	28.6	8.8	11.1	334	2217	* * *	O
	* 215/55 R18 95V	7.0	6.0 - 7.5	3.5	51	690	1521	226	8.9	693	27.3	8.8	11.1	321	2114	* * *	O
	* 245/55 R17 XL 106V	7.5	7.0 - 8.5	3.4	50	950	2094	253	10.0	702	27.6	8.8	11.1	321	2141	* * *	O
	* 245/65 R17 107V	7.0	7.0 - 8.5	3.5	51	975	2149	248	9.8	750	29.5	8.8	11.1	340	2288	* * *	-
	* 235/55 R17 XL 103V	7.5	6.5 - 8.5	3.4	50	875	1929	245	9.6	690	27.2	8.8	11.1	317	2105	* * *	O
	* 235/60 R17 102V	7.0	6.5 - 8.5	3.5	51	850	1874	240	9.4	714	28.1	8.8	11.1	326	2178	* * *	O
	* 235/65 R17 104V	7.0	6.5 - 8.5	3.5	51	900	1984	240	9.4	738	29.1	8.8	11.1	335	2251	* * *	-
	* 225/60 R17 99V	6.5	6.0 - 8.0	3.5	51	775	1709	228	9.0	702	27.6	8.8	11.1	321	2141	* * *	O
<b>16"</b>	* 225/65 R17 102V	6.5	6.0 - 8.0	3.5	51	850	1874	228	9.0	724	28.5	8.8	11.1	330	2208	* * *	-
	* 255/65 R16 109V	7.5	7.0 - 9.0	3.5	51	1030	2271	260	10.2	738	29.1	8.8	11.1	333	2251	* * *	-
	* 235/60 R16 100V	7.0	6.5 - 8.5	3.5	51	800	1764	240	9.4	688	27.1	8.8	11.1	313	2098	* * *	O
	* 235/70 R16 XL 109H	7.0	6.0 - 8.0	3.4	50	1030	2271	240	9.4	736	29.0	8.8	11.1	332	2245	* * *	-
	* 215/70 R16 100H	6.5	5.5 - 7.0	3.5	51	800	1764	221	8.7	708	27.9	*	*	321	2159	* * *	*

**XL : Extra Load**

\* Available at the 1st Quarter of 2017

\* Available at the 4th Quarter of 2017