

# HP91

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG		Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"					
<b>Black Sidewall</b>																		
22"	275/40 ZR22 XL 108Y	9.5	9.0 - 11.0	3.4	50	975	2149	278	10.9	779	30.7	8.0	10.1	365	2376	420	A A	O
	275/45 ZR22 XL 112W	9.0	8.5 - 10.5	3.4	50	1120	2469	273	10.7	807	31.8	8.3	10.5	376	2461	420	A A	O
	265/35 ZR22 98W	9.5	9.0 - 10.5	3.5	51	750	1653	271	10.7	745	29.3	8.0	10.1	352	2272	420	A A	O
21"	295/35 ZR21 XL 107Y	10.5	10.0 - 11.5	3.4	50	975	2149	301	11.9	739	29.1	8.0	10.1	347	2254	420	A A	O
	275/45 ZR21 XL 110Y	9.0	8.5 - 10.5	3.4	50	1060	2337	273	10.7	781	30.7	8.0	10.1	363	2382	420	A A	O
	255/40 ZR21 XL 102Y	9.0	8.5 - 10.0	3.4	50	850	1874	260	10.2	737	29.0	8.0	10.1	346	2248	420	A A	O
20"	315/35 ZR20 XL 110Y	11.0	10.5 - 12.0	3.4	50	1060	2337	320	12.6	728	28.7	8.0	10.1	340	2220	420	A A	O
	295/40 ZR20 XL 110Y	10.5	10.0 - 11.5	3.4	50	1060	2337	301	11.9	744	29.3	8.0	10.1	346	2269	420	A A	O
	285/50 R20 112V	9.0	8.0 - 10.0	3.5	51	1120	2469	297	11.7	794	31.3	8.3	10.5	366	2422	420	A A	O
	275/40 ZR20 XL 106Y	9.5	9.0 - 11.0	3.4	50	950	2094	278	10.9	728	28.7	8.0	10.1	340	2220	420	A A	O
	275/45 ZR20 XL 110Y	9.0	8.5 - 10.5	3.4	50	1060	2337	273	10.7	756	29.8	8.0	10.1	351	2306	420	A A	O
	275/50 ZR20 109W	8.5	7.5 - 9.5	3.5	51	1030	2271	284	11.2	784	30.9	8.3	10.5	362	2391	420	A A	O
	265/45 ZR20 XL 108Y	9.0	8.5 - 10.0	3.4	50	1000	2205	266	10.5	746	29.4	8.0	10.1	347	2275	420	A A	O
	265/50 R20 XL 111V	8.5	7.5 - 9.5	3.4	50	1090	2403	277	10.9	784	30.9	8.0	10.1	362	2391	420	A A	O
	255/45 ZR20 XL 105W	8.5	8.0 - 9.5	3.4	50	925	2039	255	10.0	738	29.1	8.2	10.3	344	2251	420	A A	O
	255/55 ZR20 XL 110Y	8.0	7.0 - 9.0	3.4	50	1060	2337	265	10.4	788	31.0	8.0	10.1	363	2403	420	A A	O
	245/45 R20 XL 103V	8.0	7.5 - 9.0	3.4	50	875	1929	243	9.6	728	28.7	8.0	10.1	340	2220	420	A A	O
19"	285/45 ZR19 107W	9.5	9.0 - 10.5	3.5	51	975	2149	285	11.2	739	29.1	8.2	10.3	341	2254	420	A A	O
	275/45 ZR19 XL 108Y	9.0	8.5 - 10.5	3.4	50	1000	2205	273	10.7	731	28.8	8.0	10.1	338	2230	420	A A	O
	265/50 ZR19 XL 110Y	8.5	7.5 - 9.5	3.4	50	1060	2337	277	10.9	749	29.5	8.0	10.1	345	2284	420	A A	O
	255/50 ZR19 103W	8.0	7.0 - 9.0	3.5	51	875	1929	265	10.4	739	29.1	8.2	10.3	341	2254	420	A A	O
	255/55 R19 XL 111V	8.0	7.0 - 9.0	3.4	50	1090	2403	265	10.4	763	30.0	8.2	10.3	351	2327	420	A A	O
	235/45 ZR19 95W	8.0	7.5 - 9.0	3.5	51	690	1521	236	9.3	695	27.4	8.0	10.1	324	2120	420	A A	O
	* 235/50 R19 99V	7.5	6.5 - 8.5	3.5	51	775	1709	245	9.6	719	28.3	8.3	10.5	333	2193	*	* * *	O
	235/55 R19 101V	7.5	6.5 - 8.5	3.4	50	825	1819	245	9.6	741	29.2	8.3	10.5	342	2260	420	A A	O
	235/55 ZR19 XL 105W	7.5	6.5 - 8.5	3.4	50	925	2039	245	9.6	741	29.2	8.3	10.5	342	2260	420	A A	O
18"	285/55 R18 113V	9.0	8.0 - 10.0	3.5	51	1150	2535	297	11.7	771	30.4	8.3	10.5	351	2352	420	A A	O
	285/60 R18 116V	8.5	8.0 - 10.0	3.5	51	1250	2756	292	11.5	799	31.5	8.2	10.3	362	2437	420	A A	O
	265/60 R18 110V	8.0	7.5 - 9.5	3.5	51	1060	2337	272	10.7	775	30.5	8.2	10.3	353	2364	420	A A	O
	255/55 ZR18 XL 109W	8.0	7.0 - 9.0	3.4	50	1030	2271	265	10.4	737	29.0	8.2	10.3	338	2248	420	A A	O
	* 255/60 R18 XL 112V	7.5	7.0 - 9.0	3.4	50	1120	2469	260	10.2	763	30.0	8.3	10.5	348	2327	*	* * *	O
	235/50 ZR18 97W	7.5	6.5 - 8.5	3.5	51	730	1609	245	9.6	693	27.3	8.3	10.5	321	2114	420	A A	O
	* 235/55 R18 100V	7.5	6.5 - 8.5	3.5	51	800	1764	245	9.6	715	28.1	8.3	10.5	329	2181	*	* * *	O
	235/60 R18 XL 107V	7.0	6.5 - 8.5	3.4	50	975	2149	240	9.4	739	29.1	8.2	10.3	339	2254	420	A A	O
	225/55 R18 98V	7.0	6.0 - 8.0	3.5	51	750	1653	233	9.2	705	27.8	8.2	10.3	325	2150	420	A A	O
225/60 R18 100H	7.0	6.0 - 8.0	3.0	44	800	1764	234	9.2	727	28.6	8.0	10.1	328	344	420	A A	O	
17"	285/65 R17 116H	8.5	8.0 - 10.0	3.5	51	1250	2756	292	11.5	802	31.6	8.2	10.3	360	2446	420	A A	O
	265/65 R17 112V	8.0	7.5 - 9.5	3.5	51	1120	2469	272	10.7	776	30.6	8.3	10.5	350	2367	420	A A	O
	255/60 R17 106V	7.5	7.0 - 9.0	3.5	51	950	2094	260	10.2	738	29.1	8.3	10.5	335	2251	420	A A	O
	255/65 R17 110V	7.5	7.0 - 9.0	3.5	51	1060	2337	260	10.2	764	30.1	8.3	10.5	345	2330	420	A A	O
	235/55 R17 99V	7.5	6.5 - 8.5	3.5	51	775	1709	245	9.6	690	27.2	8.2	10.3	317	2105	420	A A	O
	235/65 R17 104V	7.0	6.5 - 8.5	3.5	51	900	1984	240	9.4	738	29.1	8.3	10.5	335	2251	420	A A	O
	225/55 ZR17 97W	7.0	6.0 - 8.0	3.5	51	730	1609	233	9.2	680	26.8	8.2	10.3	313	2074	420	A A	O
16"	265/70 R16 112V	8.0	7.0 - 9.0	3.5	51	1120	2469	272	10.7	778	30.6	8.3	10.5	348	2373	420	A A	O
	* 235/60 R16 100H	7.0	6.5 - 8.5	3.5	51	875	1929	240	9.4	739	29.1	8.3	10.5	333	2254	*	* * *	O
	* 215/65 R16 98V	6.0	6.0 - 7.5	3.5	51	750	1653	221	8.7	686	27.0	8.3	10.5	312	2092	*	* * *	O

XL : Extra Load

\* Available at the 2nd Quarter of 2017