

# KL33

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				
<b>Black Sidewall</b>																	
<b>22"</b>	<b>P285/45 R22 110H</b>	9.5	9.0 - 10.5	3.5	51	1060	2337	285	11.2	815	32.1	9.0	11.3	379	2486	440	A A O
<b>20"</b>	<b>275/60 R20 XL 119H</b>	8.0	7.5 - 9.5	3.4	50	1215	2679	279	11.0	838	33.0	9.3	11.7	383	2556	440	A A O
	<b>265/50 R20 XL 111T</b>	8.5	7.5 - 9.5	3.4	50	1090	2403	277	10.9	774	30.5	8.7	11.0	358	2361	440	A A O
	<b>265/50 R20 XL 111V</b>	8.5	7.5 - 9.5	3.4	50	1090	2403	277	10.9	774	30.5	9.0	11.3	358	2361	440	A A O
	<b>255/45 R20 XL 105V</b>	8.5	8.0 - 9.5	3.4	50	925	2039	255	10.0	738	29.1	9.0	11.3	344	2251	440	A A O
	<b>255/50 R20 XL 109V</b>	8.0	7.0 - 9.0	3.4	50	1030	2271	265	10.4	764	30.1	9.0	11.3	354	2330	440	A A O
	<b>P255/55 R20 107H</b>	8.0	7.0 - 9.0	3.5	51	975	2149	265	10.4	788	31.0	9.0	11.3	363	2403	440	A A O
	<b>P245/50 R20 102V</b>	7.5	7.0 - 8.5	3.5	51	850	1874	253	10.0	754	29.7	9.0	11.3	350	2300	440	A A O
	<b>235/55 R20 XL 105V</b>	7.5	6.5 - 8.5	3.4	50	925	2039	245	9.6	766	30.2	8.8	11.1	355	2336	440	A A O
<b>19"</b>	<b>275/55 R19 111V</b>	8.5	7.5 - 9.5	3.5	51	1090	2403	284	11.2	785	30.9	9.0	11.3	359	2394	440	A A O
	<b>265/50 R19 XL 110V</b>	8.5	7.5 - 9.5	3.4	50	1060	2337	283	11.1	747	29.4	9.0	11.3	344	2278	440	A A O
	<b>255/40 R19 XL 100V</b>	9.0	8.5 - 10.0	3.4	50	800	1754	268	10.6	685	27.0	9.0	11.3	320	2089	440	A A O
	<b>255/45 R19 XL 104V</b>	8.5	8.0 - 9.5	3.4	50	900	1984	263	10.4	711	28.0	9.0	11.3	330	2169	440	A A O
	<b>255/50 R19 XL 107V</b>	8.0	7.0 - 9.0	3.4	50	975	2149	265	10.4	739	29.1	9.0	11.3	341	2254	440	A A O
	<b>255/55 R19 XL 111V</b>	8.0	7.0 - 9.0	3.4	50	1090	2403	265	10.4	763	30.0	9.0	11.3	351	2327	440	A A O
	<b>P255/60 R19 108H</b>	7.5	7.0 - 8.5	3.5	51	1000	2205	260	10.2	789	31.1	9.0	11.3	361	2406	440	A A O
	<b>245/45 R19 98H</b>	8.0	7.5 - 9.0	3.5	51	750	1653	254	10.0	700	27.6	8.5	10.7	326	2135	440	A A O
	<b>245/55 R19 103H</b>	7.5	7.0 - 8.5	3.5	51	875	1929	261	10.3	751	29.6	9.0	11.3	346	2291	440	A A O
	<b>235/45 R19 XL 99H</b>	8.0	7.5 - 9.0	3.4	50	775	1709	236	9.3	695	27.4	8.8	11.1	324	2120	440	A A O
	<b>235/50 R19 XL 103V</b>	7.5	6.5 - 8.5	3.4	50	875	1929	251	9.9	717	28.2	9.0	11.3	333	2187	440	A A O
	<b>P235/55 R19 101H</b>	7.5	6.5 - 8.5	3.5	51	825	1819	255	10.0	739	29.1	8.8	11.1	341	2254	440	A A O
	<b>235/55 R19 101H</b>	7.5	6.5 - 8.5	3.0	44	825	1819	245	9.6	741	29.2	8.8	11.1	348	2249	440	A A O
	<b>225/45 R19 95V</b>	7.5	7.0 - 8.5	3.5	51	630	1389	225	8.9	685	27.0	8.8	11.1	320	2089	440	A A O
<b>225/55 R19 99V</b>	7.0	6.0 - 8.0	3.0	44	775	1709	233	9.2	730	28.7	8.2	10.3	331	2174	440	A A -	
<b>18"</b>	<b>P275/65 R18 114T</b>	8.0	7.5 - 9.5	3.5	51	1180	2601	283	11.1	813	32.0	9.0	11.3	367	2480	440	A A O
	<b>P265/60 R18 109H</b>	8.0	7.5 - 9.5	3.5	51	1030	2271	267	10.5	772	27.6	7.9	10.0	348	2356	440	A A -
	<b>265/60 R18 110V</b>	8.0	7.5 - 9.5	3.5	51	1060	2337	272	10.7	775	30.5	9.5	12.0	353	2364	440	A A O
	<b>255/55 R18 XL 109V</b>	8.0	7.0 - 9.0	3.4	50	975	2149	265	10.4	737	29.0	9.5	12.0	338	2248	440	A A O
	<b>P255/65 R18 109T</b>	7.5	7.0 - 9.0	3.5	51	1030	2271	265	10.4	787	31.0	9.0	11.3	357	2400	440	A A O
	<b>245/60 R18 105V</b>	7.0	7.0 - 8.5	3.5	51	925	2039	248	9.8	751	29.6	9.5	12.0	343	2291	440	A A O
	<b>235/55 R18 XL 104V</b>	7.5	6.5 - 8.5	3.4	50	900	1984	245	9.6	715	28.1	9.0	11.3	329	2181	440	A A O
	<b>235/60 R18 103H</b>	7.0	6.5 - 8.5	3.5	51	875	1929	246	9.4	737	29.1	9.0	11.3	338	2248	440	A A O
	<b>235/60 R18 XL 107V</b>	7.0	6.5 - 8.5	3.4	50	975	2150	240	9.4	739	29.1	9.0	11.3	339	2254	440	A A O
	<b>235/65 R18 XL 110V</b>	7.0	6.5 - 8.5	3.4	50	1060	2337	240	9.4	738	29.1	9.0	11.3	338	2251	440	A A O
	<b>225/55 R18 98H</b>	7.0	6.0 - 8.0	3.5	51	750	1653	240	9.4	703	27.7	9.0	11.3	324	2144	440	A A O
	<b>225/55 R18 98V</b>	7.0	6.0 - 8.0	3.5	51	750	1653	233	9.2	705	27.8	9.0	11.3	325	2150	440	A A O
	<b>225/60 R18 XL 104V</b>	6.5	6.0 - 8.0	3.4	50	900	1984	232	9.4	725	29.1	9.0	11.3	333	2211	440	A A O
	<b>215/55 R18 95V</b>	7.0	6.0 - 7.5	3.5	51	690	1521	226	8.9	693	27.3	9.0	11.3	321	2114	440	A A O
<b>215/55 R18 XL 99V</b>	7.0	6.0 - 7.5	3.4	50	775	1709	226	8.9	693	27.3	8.7	11.0	321	2114	440	A A O	

XL : Extra Load



# KL33

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				
<b>Black Sidewall</b>																	
<b>17"</b>	<b>245/55 R17 XL 106V</b>	7.5	7.0 - 8.5	3.4	50	950	2094	258	10.2	700	27.6	9.0	11.3	320	2135	440	A A O
	<b>245/65 R17 107V</b>	7.0	7.0 - 8.5	3.5	51	975	2149	248	9.8	750	29.5	9.5	12.0	340	2288	440	A A O
	<b>235/55 R17 XL 103V</b>	7.5	6.5 - 8.5	3.4	50	875	1929	245	9.6	690	27.2	9.0	11.3	317	2105	440	A A O
	<b>235/60 R17 102V</b>	7.0	6.5 - 8.5	3.5	51	850	1874	240	9.4	714	28.1	9.0	11.3	326	2178	440	A A O
	<b>235/65 R17 104H</b>	6.5	6.5 - 8.5	3.0	44	900	1984	235	9.3	738	29.1	8.8	11.1	344	2230	440	A A O
	<b>235/65 R17 104V</b>	7.0	6.5 - 8.5	3.5	51	900	1984	240	9.4	738	29.1	9.0	11.3	335	2251	440	A A O
	<b>235/70 R17 111H</b>	7.0	6.0 - 8.0	3.5	51	1030	2271	240	9.4	762	30.0	8.8	11.1	345	2324	440	A A O
	<b>225/60 R17 99H</b>	7.0	6.0 - 8.0	3.0	44	775	1709	233	9.2	702	27.6	8.2	10.3	329	2130	440	A A O
	<b>225/60 R17 99V</b>	6.5	6.0 - 8.0	3.5	51	775	1709	236	9.3	701	27.6	9.0	10.6	321	2138	440	A A O
	<b>225/65 R17 102V</b>	6.5	6.0 - 8.0	3.5	51	850	1874	228	9.0	724	28.5	9.0	11.3	330	2208	440	A A O
<b>215/60 R17 XL 100V</b>	6.5	6.0 - 7.5	3.4	50	800	1764	224	8.8	700	27.6	9.0	11.3	320	2135	440	A A O	
<b>16"</b>	* <b>245/70 R16 XL 111H</b>	7.0	6.5 - 8.0	3.4	50	1090	2403	248	9.8	750	29.5	8.8	11.1	337	2288	* * * *	
	<b>235/60 R16 100V</b>	7.0	6.5 - 8.5	3.5	51	800	1764	240	9.4	688	27.1	9.0	11.3	313	2098	440	A A O
	<b>235/70 R16 XL 109H</b>	7.0	6.0 - 8.0	3.4	50	1030	2271	240	9.4	700	27.6	9.0	11.3	318	2135	440	A A O
	<b>225/65 R16 100V</b>	6.5	6.0 - 8.0	3.5	51	800	1764	231	9.1	700	27.6	9.0	11.3	318	2135	440	A A O
	* <b>225/65 R16 XL 104T</b>	6.5	6.0 - 8.0	3.4	50	800	1764	228	9.0	698	27.5	8.8	11.1	317	2129	* * * O	
	* <b>225/70 R16 103T</b>	6.5	6.0 - 7.5	3.5	51	875	1929	228	9.0	722	28.4	8.8	11.1	326	2202	* * * *	
	<b>225/70 R16 103H</b>	6.5	6.0 - 7.5	3.5	51	875	1929	227	8.9	720	28.3	9.0	11.3	326	2196	440	A A O
	* <b>215/65 R16 98H</b>	6.5	6.0 - 7.5	3.5	51	750	1653	221	8.7	686	27.0	8.8	11.1	312	2092	* * * O	
	<b>215/65 R16 98V</b>	6.5	6.0 - 7.5	3.5	51	750	1653	226	8.9	686	27.0	8.4	10.6	312	2092	440	A A O
	* <b>215/65 R16 XL 102H</b>	6.5	6.0 - 7.5	3.4	50	850	1874	221	8.7	686	27.0	8.8	11.1	312	2092	* * * O	
<b>215/70 R16 100H</b>	6.5	5.5 - 7.0	3.5	51	800	1760	216	8.5	706	27.8	9.0	11.3	320	2153	440	A A O	
<b>15"</b>	* <b>265/70 R15 112T</b>	8.0	7.0 - 9.0	3.5	51	1120	2469	272	10.7	753	29.6	8.8	11.1	336	2297	* * * *	
	* <b>255/70 R15 108H</b>	7.5	6.5 - 8.5	3.5	51	1000	2205	260	10.2	739	29.1	8.8	11.1	330	2254	* * * *	
	* <b>235/75 R15 105T</b>	6.5	6.0 - 8.0	3.5	51	925	2039	235	9.3	733	28.9	8.8	11.1	328	2236	* * * *	
	* <b>225/70 R15 100T</b>	6.5	6.0 - 7.5	3.5	51	800	1764	228	9.0	697	27.4	8.8	11.1	314	2126	* * * *	
	* <b>215/70 R15 98H</b>	6.5	5.5 - 7.0	3.5	51	750	1653	221	8.7	683	26.9	8.8	11.1	308	2083	* * * *	
	* <b>205/70 R15 96T</b>	6.0	5.0 - 7.0	3.5	51	710	1565	209	8.2	669	26.3	8.8	11.1	303	2040	* * * *	

XL : Extra Load

\* Available at the 2nd Quarter of 2017