

Medida	IC/RV	Uso	Capas	Tipo de Pared	Rin Recomendado	Presión de aire Máx.		Carga Máxima				Diámetro Exterior		Ancho de Sección		Ancho de Banda		Profundidad		Radio Estático de Carga	RPM	Circunferencia de Rodado
						Sencillo	Dual	Sencillo		Dual		mm	pulg	mm	pulg	mm	pulg	mm	pulg (32")			
						psi		kg	lb	kg	lb											

Métrico

80

195/80R15T	96T	-	04	DSB	5.50	44	-	710	1565	-	-	691	27.2	194	7.6	145	5.7	10.0	12.6	311	763	2108
205/80R16T XL	104T	-	04	DSB	5.50	50	-	900	1984	-	-	732	28.8	199	7.8	152	6.0	10.0	12.6	330	720	2233
215/80R15	109/107S	C	06	DSB	6.00	55	55	1030	2270	975	2150	724	28.5	212	8.3	154	6.1	9.7	12.2	336	733	2193
215/80R15S	102S	-	04	DSB	6.00	44	-	850	1874	-	-	727	28.6	211	8.3	160	6.3	10.0	12.6	325	725	2217
235/80R16S	109S	-	04	DSB	6.50	44	-	1030	2271	-	-	782	30.8	221	8.7	178	7.0	12.6	15.9	-	-	-

75

P225/75R15S	102S	-	04	OWL	6.00	44	-	850	1874	-	-	718	28.3	226	8.9	167	6.6	10.5	13.2	321	735	2188
P225/75R16T	104T	-	04	DSB	9.00	51	-	900	1984	-	-	743	29.3	238	9.4	169	6.7	9.7	12.2	334	710	2266
P225/75R16T XL	106T	-	04	OWL	6.00	50	-	950	2094	-	-	743	29.2	224	8.8	172	6.8	10.5	13.2	334	710	2265
235/75R15T XL	109T	-	04	OWL	6.50	50	-	1030	2271	-	-	732	28.8	236	9.3	174	6.9	10.0	12.6	327	721	2232
P235/75R15S XL	108S	-	04	OWL	6.50	50	-	990	2183	-	-	732	28.8	236	9.3	172	6.8	10.0	12.6	327	721	2231
P235/75R16T	106T	-	04	OWL	6.50	50	-	950	2094	-	-	759	29.9	234	9.2	178	7.0	10.5	13.2	-	-	-
P235/75R16T XL	109T	-	04	OWL	6.50	50	-	1030	2271	-	-	757	29.8	234	9.2	178	7.0	10.5	13.2	340	696	2309
P235/75R17T	108T	-	04	OWL	6.50	44	-	1000	2205	-	-	782	30.8	233	9.2	178	7.0	10.5	13.2	352	674	2385
P245/75R16T	109T	-	04	DSB	7.00	44	-	1030	2271	-	-	773	30.4	246	9.7	186	7.3	10.5	13.2	346	682	2358
P245/75R17T	110T	-	04	DSB	7.00	44	-	1060	2337	-	-	802	31.6	247	9.7	187	7.4	10.5	13.2	360	657	2446
P255/75R17T	110T	-	04	DSB	7.00	44	-	1060	2337	-	-	802	31.6	247	9.7	187	7.4	10.5	13.2	360	657	2446
P265/75R16T	114T	-	04	OWL	7.50	44	-	1180	2601	-	-	804	31.6	261	10.3	202	8.0	10.5	13.2	358	656	2450

70

205/70R15	104/102S	-	06	DSB	6.00	55	55	900	1985	1875	667	26.3	210	8.3	154	6.1	9.2	11.6	312	796	2021	
205/70R15	106/104S	-	08	DSB	6.00	65	65	950	2095	900	1985	667	26.3	208	8.2	158	6.2	10.7	13.4	312	796	2021
205/70R15S	96S	-	04	DSB	6.00	44	-	710	1565	-	-	669	26.3	210	8.3	157	6.2	10.0	12.6	302	789	2039
205/70R15T	96T	-	04	DSB	6.00	44	-	710	1565	-	-	669	26.3	210	8.3	157	6.2	10.0	12.6	302	789	2039
P215/70R16S	99S	-	04	DSB	6.00	44	-	775	1709	-	-	707	27.9	221	8.7	172	6.8	10.0	12.6	-	-	-
P225/70R15T	100T	-	04	DSB	6.50	44	-	795	1753	-	-	697	27.4	221	8.7	172	6.8	10.5	13.2	313	757	2125
P225/70R16T	103T	-	04	DSB	6.50	44	-	875	1929	-	-	721	28.4	230	9.1	176	6.9	10.5	13.2	325	731	2199
235/70R15S	103S	F	04	OWL	6.50	44	-	875	1929	-	-	735	29.0	239	9.4	177	7.0	9.6	12.1	-	-	-
P235/70R15S	102S	-	04	OWL	7.00	44	-	860	1896	-	-	710	27.9	239	9.4	177	7.0	9.6	12.1	318	743	2164
P235/70R16T	104T	-	04	DSB	7.00	51	-	900	1984	-	-	736	29.0	240	9.4	184	7.2	10.0	12.6	331	717	2244
P235/70R16T XL	107T	-	04	OWL	7.00	50	-	975	2149	-	-	736	29.0	240	9.4	184	7.2	10.5	13.2	331	717	2244
245/70R16T	107T	C	04	OWL	7.00	51	-	975	2150	-	-	750	29.5	251	9.9	186	7.3	9.5	12.0	337	704	2286
P245/70R16T	106T	-	04	OWL	7.00	51	-	950	2094	-	-	751	29.6	252	9.9	191	7.5	9.9	12.5	337	702	2291
P245/70R16T XL	111T	-	04	DSB	7.00	50	-	1090	2403	-	-	750	29.5	248	9.8	192	7.6	10.5	13.2	337	704	2286
P245/70R17T	108T	-	04	OWL	7.00	44	-	1000	2205	-	-	775	30.5	247	9.7	186	7.3	10.5	13.2	349	681	2363
255/70R15	112/110L	-	06	DSB	7.50	55	55	1120	2470	1060	2335	739	29.1	260	10.2	196	7.7	10.7	13.4	342	718	2239
255/70R15	112/110L	-	06	DSB	7.50	55	55	1120	2470	1060	2335	739	29.1	260	10.2	196	7.7	10.7	13.4	342	718	2239
P255/70R15T	108T	-	04	DSB	7.50	44	-	990	2183	-	-	735	29.0	263	10.4	194	7.6	10.5	13.2	328	717	2242
255/70R16T	111T	Z	04	OWL	7.50	44	-	1090	2403	-	-	763	30.0	260	10.2	194	7.6	10.5	13.2	342	691	2327
P255/70R16T	109T	-	04	OWL	7.50	44	-	1030	2271	-	-	763	30.0	260	10.2	194	7.6	10.5	13.2	342	691	2327
P255/70R17T	110T	-	04	OWL	7.50	44	-	1060	2337	-	-	789	31.1	259	10.2	194	7.6	10.5	13.2	355	668	2406
P255/70R18T	112T	-	04	DSB	7.50	44	-	1120	2469	-	-	814	32.0	261	10.3	194	7.6	10.5	13.2	367	648	2481
P265/70R15S	110S	-	04	DSB	8.00	51	-	1060	2337	-	-	751	29.6	272	10.7	212	8.3	9.7	12.2	334	703	2289
265/70R16T	112T	-	04	OWL	8.00	51	-	1120	2469	-	-	778	30.6	273	10.7	202	8.0	10.5	13.2	347	678	2371
P265/70R16T	111T	-	04	OWL	8.00	51	-	1090	2403	-	-	779	30.7	272	10.7	207	8.1	10.1	12.7	348	677	2376
265/70R17T	115T	F	04	OWL	8.00	51	-	1215	2679	-	-	803	31.6	269	10.6	202	8.0	9.5	12.0	360	657	2447
P265/70R17T	113T	F	04	DSB	8.00	44	-	1150	2535	-	-	803	31.6	269	10.6	202	8.0	10.5	13.2	360	657	2447
P265/70R18T	114T	-	04	DSB	8.00	44	-	1180	2601	-	-	827	32.6	271	10.7	202	8.0	10.5	13.2	372	638	2522
275/70R16T	114T	-	04	DSB	8.00	51	-	1180	2601	-	-	790	31.1	274	10.8	209	8.2	9.5	12.0	352	667	2410
P285/70R17T	117T	-	04	DSB	8.50	51	-	1285	2833	-	-	831	32.7	288	11.3	218	8.6	10.0	12.6	371	635	2533

Medida	IC/RV	Uso	Capas	Tipo de Pared	Rin Recomendado	Presión de aire Máx.		Carga Máxima					Diámetro Exterior		Ancho de Sección		Ancho de Banda		Profundidad		Radio Estático de Carga	RPM	Circunferencia de Rodado
						Sencillo	Dual	Sencillo		Dual		mm	pulg	mm	pulg	mm	pulg	mm	pulg (32")				
						psi		kg	lb	kg	lb												

65

225/65R17T XL	106T	C-	04	DSB	6.50	50	-	950	2094	-	-	721	28.4	232	9.1	180	7.1	8.7	11.0	328	731	2199
235/65R17T	104T	C-	04	DSB	7.00	51	-	900	1984	-	-	737	29.0	246	9.7	184	7.2	9.5	12.0	334	716	2247
P235/65R17S	104S	-	04	DSB	7.00	44	-	900	1984	-	-	737	29.0	240	9.4	178	7.0	8.0	10.0	335	715	2248
P235/65R17T	103T	-	04	DSB	7.00	44	-	875	1929	-	-	737	29.0	246	9.7	184	7.2	10.5	13.2	334	716	2247
245/65R17T	107T	C-	04	DSB	7.00	51	-	975	2150	-	-	750	29.5	256	10.1	192	7.6	9.5	12.0	339	703	2287
P245/65R17S	105S	CU	04	OWL	7.00	44	-	925	2039	-	-	748	29.5	256	10.1	190	7.5	9.6	12.1	339	705	2282
P245/65R17T	105T	-	04	OWL	7.00	44	-	925	2039	-	-	748	29.5	256	10.1	190	7.5	9.6	12.1	339	705	2282
245/65R17T XL	111T	-	04	DSB	7.00	50	-	1090	2403	-	-	750	29.5	256	10.1	192	7.6	10.5	13.2	339	703	2287
P255/65R16T	106T	-	04	DSB	7.50	44	-	950	2094	-	-	737	29.0	265	10.4	204	8.0	10.5	13.2	332	715	2249
255/65R17S	110S	CR	04	DSB	7.00	51	-	1060	2337	-	-	763	30.0	256	10.1	194	7.6	9.3	11.7	345	691	2327
255/65R17T	110T	F	04	DSB	7.00	51	-	1060	2337	-	-	763	30.0	256	10.1	194	7.6	9.3	11.7	345	691	2327
P255/65R17T	110T	-	04	OWL	7.50	44	-	1060	2337	-	-	763	30.0	264	10.4	198	7.8	10.5	13.2	345	691	2327
265/65R17T	112T	C-	04	DSB	8.00	51	-	1120	2470	-	-	776	30.5	270	10.6	206	8.1	9.5	12.0	350	680	2366
P265/65R17T	110T	-	04	DSB	8.00	51	-	1060	2337	-	-	777	30.6	282	11.1	212	8.3	9.9	12.5	350	679	2370
P265/65R18T	112T	-	04	DSB	8.00	44	-	1120	2469	-	-	801	31.6	278	10.9	207	8.1	10.5	13.2	362	658	2444
275/65R17T	115T	-	04	DSB	8.00	51	-	1215	2679	-	-	789	31.1	279	11.0	214	8.4	9.5	12.0	355	668	2407
P275/65R18T	114T	-	04	OWL	8.00	44	-	1180	2601	-	-	815	32.1	285	11.2	214	8.4	10.5	13.2	368	647	2485
285/65R17T	116T	-	04	DSB	8.50	51	-	1250	2756	-	-	801	31.5	294	11.6	222	8.7	9.5	12.0	359	658	2443

60

215/60R17T XL	100T	C-	04	DSB	6.50	50	-	800	1764	-	-	687	27.1	229	9.0	181	7.1	8.7	11.0	315	768	2095
225/60R17T XL	103T	C-	04	DSB	6.50	50	-	875	1929	-	-	699	27.5	237	9.3	190	7.5	8.7	11.0	320	754	2132
235/60R16T	100T	-	04	DSB	7.00	44	-	800	1764	-	-	684	26.9	239	9.4	184	7.2	10.5	13.2	311	771	2085
P235/60R16T	100T	-	04	DSB	7.00	44	-	800	1764	-	-	684	26.9	239	9.4	184	7.2	10.5	13.2	311	771	2085
235/60R18T XL	107T	C-	04	DSB	7.00	50	-	975	2149	-	-	737	29.0	244	9.6	188	7.4	9.5	12.0	337	716	2246
P235/60R18T	102T	-	04	DSB	7.00	44	-	850	1874	-	-	737	29.0	249	9.8	184	7.2	10.5	13.2	337	716	2246
P245/60R18T	104T	-	04	DSB	7.00	44	-	900	1984	-	-	750	29.5	256	10.1	194	7.6	8.7	11.0	342	704	2286
P255/60R18T	107T	-	04	DSB	7.50	44	-	975	2149	-	-	760	29.9	272	10.7	200	7.9	10.5	13.2	346	694	2316
265/60R18T	110T	F	04	DSB	8.00	51	-	1060	2337	-	-	775	30.5	268	10.6	192	7.6	9.9	12.5	352	681	2363
265/60R18T XL	114T	-	04	DSB	8.00	50	-	1180	2601	-	-	775	30.5	280	11.0	212	8.3	10.5	13.2	352	681	2363
P265/60R18T	109T	-	04	DSB	8.00	51	-	1030	2271	-	-	776	30.5	284	11.2	217	8.5	9.9	12.5	352	680	2365
P275/60R20T	114T	-	04	DSB	8.00	44	-	1180	2601	-	-	834	32.8	292	11.5	232	9.1	10.0	12.6	380	633	2542

55

255/55R19H	107H	-	04	DSB	8.00	51	-	975	2149	-	-	760	29.9	278	10.9	214	8.4	10.7	13.4	349	694	2318
255/55R19H XL	111H	-	04	DSB	8.00	50	-	1090	2403	-	-	760	29.9	270	10.6	209	8.2	9.5	12.0	349	694	2318
275/55R20T	113T	F	04	DSB	8.50	51	-	1150	2535	-	-	815	32.1	282	11.1	225	8.9	9.7	12.2	373	647	2485
275/55R20T XL	117T	-	04	DSB	8.50	50	-	1285	2833	-	-	806	31.7	289	11.4	234	9.2	10.0	12.6	370	654	2459
P275/55R20S	111S	F	04	DSB	8.50	51	-	1090	2403	-	-	810	31.9	298	11.7	231	9.1	10.0	12.6	371	651	2471

50

305/50R20T XL	120T	-	04	DSB	9.50	50	-	1400	3086	-	-	811	31.9	320	12.6	267	10.5	10.0	12.6	372	650	2473
---------------	------	---	----	-----	------	----	---	------	------	---	---	-----	------	-----	------	-----	------	------	------	-----	-----	------

45

305/45R22T XL	118T	-	04	DSB	10.00	50	-	1320	2910	-	-	831	32.7	308	12.1	268	10.6	10.0	12.6	385	635	2534
---------------	------	---	----	-----	-------	----	---	------	------	---	---	-----	------	-----	------	-----	------	------	------	-----	-----	------

LT - Métrico

85

LT215/85R16	115/112R	-	10	DSB	6.00	80	80	1215	2680	1120	2470	768	30.3	210	8.3	164	6.5	12.6	15.9	357	691	2328
LT235/85R16	108/104R	C-	06	OWL	6.50	50	50	1000	2205	910	2006	804	31.6	221	8.7	178	7.0	11.6	14.7	372	661	2434
LT235/85R16	120/116R	-	10	DSB	6.50	80	80	1380	3042	1260	2778	804	31.6	221	8.7	178	7.0	13.1	16.5	372	661	2434

80

LT235/80R17	120/117R	-	10	DSB	6.50	80	80	1400	3085	1285	2835	805	31.7	223	8.8	180	7.1	13.1	16.5	374	659	2439
-------------	----------	---	----	-----	------	----	----	------	------	------	------	-----	------	-----	-----	-----	-----	------	------	-----	-----	------

75

LT215/75R15	100/97S	-	06	OWL	6.00	50	50	800	1765	730	1610	707	27.8	214	8.4	164	6.5	12.1	15.3	328	751	2141
LT225/75R16	115/112S	-	10	DSB	6.00	80	80	1215	2680	1120	2470	742	29.2	217	8.5	174	6.9	12.6	15.9	345	716	2247

Medida	IC/RV	Uso	Capas	Tipo de Pared	Rin Recomendado	Presión de aire Máx.		Carga Máxima				Diámetro Exterior		Ancho de Sección		Ancho de Banda		Profundidad		Radio Estático de Carga	RPM	Circunferencia de Rodado
						Sencillo	Dual	Sencillo		Dual		mm	pulg	mm	pulg	mm	pulg	mm	pulg (32")			
						psi		kg	lb	kg	lb											

75

LT225/75R17	116/113R	-	10	DSB	6.00	80	80	1250	2755	1150	2535	772	30.4	217	8.5	174	6.9	12.6	15.9	360	688	2339
LT235/75R15	104/101R	-	06	OWL	6.50	50	50	900	1985	825	1820	732	28.8	230	9.1	180	7.1	13.1	16.5	339	726	2216
LT245/75R16	120/116S	-	10	OWL	7.00	80	80	1380	3042	1260	2778	771	30.4	244	9.6	188	7.4	13.1	16.5	358	688	2336
LT245/75R17	121/118S	-	10	OWL	7.00	80	80	1450	3195	1320	2910	800	31.5	239	9.4	190	7.5	12.6	15.9	372	664	2422
LT265/75R16	112/109R	-	06	DSB	7.50	50	50	1120	2470	1030	2270	803	31.6	258	10.2	206	8.1	13.1	16.5	371	661	2432
LT265/75R16	123/120R	C	10	DSB	7.50	80	80	1550	3415	1400	3085	803	31.6	258	10.2	206	8.1	13.1	16.5	371	661	2432
LT285/75R16	126/123R	-	10	OWL	8.00	80	80	1700	3750	1550	3415	832	32.8	274	10.8	218	8.6	13.1	16.5	384	638	2522
LT315/75R16	121R	-	08	OWL	8.50	50	-	1450	3195	-	-	878	34.6	298	11.7	244	9.6	13.1	16.5	403	605	2660

70

LT225/70R17	110/107S	-	08	OWL	7.00	50	50	1060	2337	975	2149	789	31.1	218	8.6	180	7.1	12.1	15.3	-	-	-
LT235/70R16	104/101S	C	06	OWL	7.00	50	50	900	1985	825	1820	734	28.9	238	9.4	188	7.4	10.2	12.8	342	723	2224
LT245/70R16	106/103Q	C	06	OWL	7.00	50	50	950	2095	875	1930	750	29.5	244	9.6	188	7.4	11.6	14.7	349	708	2271
LT245/70R17	119/116R	-	10	OWL	7.00	80	80	1360	3000	1250	2755	775	30.5	241	9.5	188	7.4	13.1	16.5	361	685	2349
LT265/70R16	110/107R	C	06	OWL	8.00	50	50	1060	2335	975	2150	776	30.5	266	10.5	204	8.0	11.6	14.7	360	684	2350
LT265/70R16	117/114R	-	08	OWL	8.00	65	65	1285	2835	1180	2600	776	30.5	266	10.5	204	8.0	13.1	16.5	360	684	2350
LT265/70R17	121/118S	-	10	OWL	8.00	80	80	1450	3195	1320	2910	803	31.6	266	10.5	206	8.1	12.6	15.9	373	661	2433
LT265/70R18	124/121R	-	10	DSB	8.00	80	80	1600	3527	1450	3197	829	32.6	264	10.4	206	8.1	12.6	15.9	386	641	2510
LT275/70R16	112/109R	C	06	OWL	8.00	50	50	1120	2470	1030	2270	791	31.1	274	10.8	212	8.3	11.6	14.7	366	671	2396
LT275/70R17	121/118R	-	10	OWL	8.00	80	80	1450	3195	1320	2910	816	32.1	270	10.6	214	8.4	12.6	15.9	379	650	2473
LT275/70R18	125/122S	CA	10	DSB	8.00	80	80	1650	3640	1500	3305	841	33.1	269	10.6	212	8.3	12.6	15.9	391	631	2549
LT285/70R17	121/118S	-	10	OWL	8.50	80	80	1450	3195	1320	2910	830	32.7	284	11.2	220	8.7	13.1	16.5	385	639	2516
LT295/70R17	121/118R	-	10	OWL	8.50	80	80	1450	3195	1320	2910	846	33.3	291	11.5	228	9.0	13.1	16.5	391	628	2562
LT305/70R16	124/121R	-	10	OWL	9.00	65	65	1600	3525	1450	3195	833	32.8	302	11.9	240	9.4	13.1	16.5	384	637	2523
LT315/70R17	121/118R	-	08	OWL	9.50	50	50	1450	3195	1320	2910	872	34.3	310	12.2	244	9.6	13.1	16.5	403	609	2642

65

LT235/65R17	107T	C	08	OWL	7.00	51	-	975	2149	-	-	737	29.0	244	9.6	198	7.8	10.7	13.4	-	-	-
LT265/65R17	109T	F	06	OWL	8.00	50	-	1030	2270	-	-	786	31.0	270	10.6	212	8.3	10.7	13.4	366	675	2382
LT265/65R17	120/117S	-	08	DSB	8.00	80	80	1400	3085	1285	2835	775	30.5	267	10.5	204	8.0	11.6	14.7	361	685	2348
LT275/65R17	120/117S	C	10	DSB	8.00	80	80	1400	3085	1285	2835	775	30.5	267	10.5	204	8.0	11.6	14.7	361	685	2348
LT275/65R18	123/120S	-	10	DSB	8.00	80	80	1550	3415	1400	3085	813	32.0	275	10.8	212	8.3	13.1	16.5	379	653	2464
LT275/65R18	127/124Q	CL	12	DSB	8.00	95	95	1750	3860	1600	3525	813	32.0	275	10.8	212	8.3	13.1	16.5	379	653	2464
LT275/65R20	126/123S	-	10	DSB	8.00	80	80	1700	3750	1550	3415	864	34.0	280	11.0	212	8.3	12.6	15.9	405	614	2619
LT285/65R17	121/118Q	C	08	DSB	8.00	80	80	1450	3195	1320	2910	802	31.6	286	11.3	220	8.7	12.6	15.9	-	-	-
LT285/65R18	121/118S	CA	08	DSB	8.50	65	65	1450	3195	1320	2910	825	32.5	286	11.3	220	8.7	12.6	15.9	385	643	2500
LT285/65R18	125/122S	CA	10	DSB	8.50	80	80	1650	3640	1500	3305	825	32.5	286	11.3	220	8.7	12.6	15.9	385	643	2500
LT325/65R18	127/124S	-	10	DSB	9.50	65	65	1750	3860	1600	3525	878	34.6	322	12.7	250	9.8	12.6	15.9	407	605	2660

60

LT265/60R18	119/116S	C	10	DSB	9.00	80	80	1360	3000	1250	2755	775	30.5	283	11.1	206	8.1	11.6	14.5	-	-	-
LT325/60R18	124/121S	-	10	DSB	9.50	65	65	1600	3525	1450	3195	845	33.3	329	13.0	250	9.8	12.6	15.9	393	628	2559
LT325/60R20	126/123S	-	10	DSB	9.50	65	65	1700	3750	1550	3415	897	35.3	324	12.8	274	10.8	12.6	15.9	419	592	2717

55

LT285/55R20	122/119S	-	10	DSB	9.00	80	80	1500	3305	1360	3000	821	32.3	289	11.4	246	9.7	12.6	15.9	387	647	2487
LT305/55R20	121/118S	-	10	DSB	9.50	65	65	1450	3195	1320	2910	843	33.2	307	12.1	262	10.3	12.6	15.9	396	630	2554

50

LT325/50R22	122S	-	10	DSB	10.00	65	-	1500	3305	-	-	884	34.8	327	12.9	280	11.0	12.6	15.9	417	600	2678
-------------	------	---	----	-----	-------	----	---	------	------	---	---	-----	------	-----	------	-----	------	------	------	-----	-----	------

Flotación

205R16	110/108R	-	08	DSB	6.00	65	65	1060	2337	1000	2205	732	28.8	206	8.1	156	6.1	10.7	13.4	341	725	2218
30X9.50R15	104R	-	06	SBL	7.50	50	-	900	1985	-	-	750	29.5	230	9.1	184	7.2	13.1	16.5	347	708	2272
31X10.50R15	109R	-	06	DSB	8.50	50	-	1030	2270	-	-	775	30.5	256	10.1	206	8.1	13.1	16.5	357	685	2347
33X12.50R15LT	108R	-	06	OWL	10.00	35	-	1000	2205	-	-	828	32.6	305	12.0	244	9.6	13.1	16.5	380	641	2508
33X12.50R15	108R	Z	06	OWL	10.00	35	-	1000	2205	-	-	828	32.6	305	12.0	244	9.6	13.1	16.5	380	641	2508