

Medida	IC/RV	Uso	Capas	Tipo de Pared	Rin Recomendado	Presión de aire Máx.		Carga Máxima				Diámetro Exterior		Ancho de Sección		Ancho de Banda		Profundidad		Radio Estático de Carga	RPM	Circunferencia de Rodado
						Sencillo	Dual	Sencillo		Dual		mm	pulg	mm	pulg	mm	pulg	mm	pulg (32")			
						psi		kg	lb	kg	lb											

70

LT285/70R17	121/118S	-	10	DSB	8.50	80	80	1450	3195	1320	2910	830	32.7	284	11.2	228	9.0	12.6	15.9	385	639	2516
LT295/70R17	121/118S	-	10	OBL	8.50	80	80	1450	3195	1320	2910	844	33.2	294	11.6	236	9.3	12.6	15.9	391	629	2558
LT295/70R18	129/126S	-	10	SBL	8.50	80	80	1850	4080	1700	3750	876	34.5	291	11.5	236	9.3	13.6	17.1	406	606	2654
LT305/70R16	124/121S	-	10	SBL	9.00	65	65	1600	3525	1450	3195	834	32.8	302	11.9	244	9.6	12.6	15.9	384	636	2527
LT315/70R17	121/118S	-	10	SBL	9.50	65	65	1450	3195	1320	2910	873	34.4	312	12.3	252	9.9	12.6	15.9	403	608	2645

65

Z15/65R16C	106/104T	I-	06	DSB	6.50	65	65	950	2094	900	1984	686	27.0	224	8.8	175	6.9	8.3	10.4	322	774	2078
LT225/65R17	107/103S	-	10	DSB	6.50	65	65	975	2149	875	1929	724	28.5	218	8.6	180	7.1	12.1	15.1	-	-	-
LT245/65R17	110/108S	-	08	DSB	7.00	65	65	1060	2337	1000	2205	750	29.5	245	9.6	196	7.7	13.0	16.3	-	-	-
LT255/65R17	114/110S	I-	08	DSB	7.50	80	80	1180	2601	1060	2337	763	30.1	252	9.9	199	7.8	11.2	14.0	-	-	-
LT265/65R17	120/117S	IZ	10	DSB	8.00	80	80	1400	3085	1285	2835	773	30.4	271	10.7	222	8.7	10.7	13.4	360	687	2342
LT265/65R18	121/119S	-	10	DSB	8.00	80	80	1450	3197	1360	2998	802	31.6	271	10.7	222	8.7	10.7	13.4	-	-	-
LT275/65R17	120/117S	-	10	DSB	8.00	80	80	1400	3085	1285	2835	775	30.5	267	10.5	204	8.0	11.6	14.7	361	685	2348
LT275/65R18	123/120S	-	10	DSB	8.00	80	80	1550	3415	1400	3085	814	32.0	279	11.0	231	9.1	12.1	15.3	380	652	2466
LT275/65R20	126/123S	G	10	DSB	8.00	80	80	1700	3750	1550	3415	864	34.0	284	11.2	231	9.1	11.6	14.7	405	614	2619
LT285/65R18	125/122S	-	10	DSB	8.50	80	80	1650	3640	1500	3305	825	32.5	292	11.5	239	9.4	11.6	14.7	385	643	2500
LT285/65R20	127/124S	-	10	DSB	8.50	80	80	1750	3858	1600	3527	879	34.6	292	11.5	239	9.4	11.6	14.7	-	-	-
LT295/65R20	129/126S	-	10	DSB	8.50	80	80	1800	4078	1700	3748	892	35.1	291	11.5	236	9.3	11.6	14.7	-	-	-
LT305/65R18	124/121S	-	10	DSB	9.00	65	65	1600	3527	1450	3197	854	33.6	302	11.9	244	9.6	11.6	14.7	-	-	-
LT325/65R18	127/124S	-	10	SBL	9.50	65	65	1750	3860	1600	3525	878	34.6	328	12.9	272	10.7	11.6	14.7	407	605	2660

60

LT265/60R18	119/116S	-	10	DSB	9.00	80	80	1360	3000	1250	2755	775	30.5	283	11.1	206	8.1	11.6	14.5	-	-	-
LT265/60R20	120/118S	-	10	DSB	9.50	65	65	1400	3086	1320	2910	826	32.5	271	10.7	222	8.7	11.6	14.5	-	-	-
LT275/60R20	119/116S	-	08	DSB	8.00	65	65	1360	3000	1250	2755	836	32.9	283	11.1	232	9.1	11.6	14.7	393	635	2534
LT285/60R18	118/115S	I-	08	DSB	8.50	65	65	1320	2910	1215	2679	799	31.5	292	11.5	239	9.4	11.6	14.5	-	-	-
LT285/60R20	125/122S	-	10	DSB	8.50	65	65	1650	3638	1500	3307	850	33.5	292	11.5	239	9.4	11.6	14.5	-	-	-
LT295/60R20	126/123S	-	10	DSB	8.50	65	65	1700	3748	1550	3417	892	35.1	291	11.5	236	9.3	12.1	15.1	-	-	-
LT325/60R18	124/121S	-	10	SBL	9.50	65	65	1600	3525	1450	3195	846	33.3	336	13.2	272	10.7	11.6	14.7	393	627	2563
LT325/60R20	126/123S	-	10	SBL	9.50	65	65	1700	3750	1550	3415	897	35.3	328	12.9	274	10.8	12.6	15.9	419	592	2717

55

LT275/55R20	115/112S	-	08	DSB	8.50	65	65	1215	2680	1120	2470	810	31.9	291	11.5	230	9.1	11.6	14.7	382	655	2454
LT285/55R20	122/119S	-	10	DSB	9.00	80	80	1500	3305	1360	3000	822	32.4	282	11.1	239	9.4	13.1	16.5	387	646	2490
LT295/55R20	123/120S	-	10	DSB	9.50	80	80	1550	3415	1400	3085	837	33.0	313	12.3	248	9.8	13.1	16.5	393	634	2536
LT305/55R20	121/118S	-	10	DSB	9.50	65	65	1450	3195	1320	2910	844	33.2	312	12.3	256	10.1	13.1	16.5	396	629	2555

50

LT325/50R22	122S	-	10		10.00	65	-	1500	3305	-	-	885	34.8	338	13.3	274	10.8	13.1	16.5	418	600	2681
-------------	------	---	----	--	-------	----	---	------	------	---	---	-----	------	-----	------	-----	------	------	------	-----	-----	------

Flotación

205R16	110/108R	IZ	08	OWL	6.00	65	65	1060	2337	1000	2205	732	28.8	205	8.1	164	6.5	10.2	12.8	341	725	2217
205R16C	110/108R	Z	08	OWL	6.00	65	65	1060	2337	1000	2205	732	28.8	205	8.1	164	6.5	10.2	12.8	341	725	2217
30X9.50R15	104S	I-	06	OBL	7.50	50	-	900	1985	-	-	750	29.5	225	8.9	194	7.6	12.6	15.9	347	708	2272
31X10.50R15	109S	I-	06	OWL	8.50	50	-	1030	2270	-	-	774	30.5	252	9.9	214	8.4	12.6	15.9	357	686	2345
32X11.50R15	113S	-	06	OWL	9.00	50	-	1150	2530	-	-	807	31.8	274	10.8	230	9.1	14.6	18.3	371	658	2444
33X12.50R15	108S	-	06	OWL	10.00	50	-	1000	2225	-	-	828	32.6	305	12.0	244	9.6	13.1	16.5	380	641	2508
33X12.50R18	118S	-	12	OWL	10.00	50	-	1320	2910	-	-	832	32.7	310	12.2	267	10.5	13.1	16.5	387	638	2519
33X12.50R20	114S	-	12	OWL	10.00	65	-	1180	2600	-	-	832	32.8	321	12.6	267	10.5	13.6	17.1	391	638	2520
35X12.50R17	121S	-	10	OWL	10.00	65	-	1450	3195	-	-	877	34.5	312	12.3	254	10.0	12.6	15.9	405	605	2657
35X12.50R18	123S	-	10	DSB	10.00	65	-	1550	3415	-	-	877	34.5	310	12.2	254	10.0	12.1	15.3	407	605	2658
35X12.50R20	121S	-	10	DSB	10.00	65	-	1450	3195	-	-	882	34.7	314	12.4	267	10.5	14.1	17.7	412	602	2672
35X12.50R22	121S	-	12	DSB	10.00	65	-	1450	3195	-	-	887	34.9	314	12.4	267	10.5	13.0	16.3	-	-	-

Medida	IC/RV	Uso	Capas	Tipo de Pared	Rin Recomendado	Presión de aire Máx.		Carga Máxima				Diámetro Exterior		Ancho de Sección		Ancho de Banda		Profundidad		Radio Estático de Carga	RPM	Circunferencia de Rodado
						Sencillo	Dual	Sencillo		Dual		mm	pulg	mm	pulg	mm	pulg	mm	pulg (32")			
						psi		kg	lb	kg	lb											

Métrico

80

215/80R15T	102T	IZ	04	DSB	6.00	51	-	850	1874	-	-	723	28.5	207	8.1	172	6.8	10.0	12.6	323	729	2205
------------	------	----	----	-----	------	----	---	-----	------	---	---	-----	------	-----	-----	-----	-----	------	------	-----	-----	------

75

225/75R16T XL	108T	I-	04	OWL	6.00	50	-	990	2183	-	-	743	29.2	222	8.7	180	7.1	10.0	12.6	334	710	2265
235/75R15T XL	109T	I-	04	OWL	6.50	50	-	1030	2271	-	-	731	28.8	233	9.2	188	7.4	9.5	12.0	327	722	2229
235/75R16T XL	112T	I-	04	SBL	6.50	50	-	1120	2469	-	-	756	29.8	232	9.1	188	7.4	10.0	12.6	339	698	2305
235/75R17T	109T	I-	04	OBL	6.50	51	-	1030	2271	-	-	783	30.8	234	9.2	188	7.4	10.0	12.6	352	673	2388
245/75R16T	111T	I-	04	OBL	7.00	51	-	1090	2403	-	-	773	30.4	244	9.6	196	7.7	10.0	12.6	346	682	2358
245/75R17T	112T	A-	04	OWL	7.00	51	-	1120	2469	-	-	799	31.4	252	9.9	196	7.7	10.0	12.6	359	660	2436
255/75R17T	115T	A-	04	OWL	7.00	51	-	1215	2679	-	-	813	32.0	253	10.0	204	8.0	10.0	12.6	364	649	2479
265/75R16T	116T	I-	04	OWL	7.50	51	-	1250	2756	-	-	802	31.6	264	10.4	212	8.3	10.0	12.6	357	657	2446

70

215/70R16T	100T	I-	04	OWL	6.50	51	-	800	1764	-	-	706	27.8	218	8.6	172	6.8	9.2	11.6	320	747	2153
225/70R15T	100T	-	04	OWL	6.50	51	-	800	1764	-	-	697	27.4	226	8.9	178	7.0	9.2	11.6	313	757	2125
225/70R16S	103T	C-	04	OWL	6.00	51	-	875	1929	-	-	722	28.4	226	8.9	180	7.1	10.0	12.6	326	731	2200
225/70R16T	103T	I-	04	OWL	6.00	51	-	875	1929	-	-	722	28.4	226	8.9	180	7.1	10.0	12.6	326	731	2200
235/70R16T XL	109T	I-	04	SBL	7.00	50	-	1030	2271	-	-	735	28.9	239	9.4	188	7.4	10.0	12.6	331	718	2241
245/70R16T XL	111T	I-	04	OWL	7.00	50	-	1090	2403	-	-	750	29.5	244	9.6	196	7.7	10.0	12.6	337	703	2287
245/70R17T	110T	I-	04	OBL	8.00	51	-	1060	2337	-	-	775	30.5	247	9.7	196	7.7	10.0	12.6	349	681	2363
255/70R15T	108T	IZ	04	OWL	7.50	51	-	1000	2205	-	-	740	29.1	255	10.0	204	8.0	10.0	12.6	330	713	2257
255/70R16T	111T	I-	04	SBL	7.50	51	-	1090	2403	-	-	763	30.0	260	10.2	204	8.0	10.0	12.6	342	691	2327
255/70R17T	112T	I-	04	OWL	7.50	51	-	1120	2469	-	-	789	31.1	259	10.2	204	8.0	10.0	12.6	355	668	2406
255/70R18T	113T	A-	04	OWL	7.50	51	-	1150	2535	-	-	814	32.0	272	10.7	204	8.0	10.0	12.6	367	648	2482
265/70R16T	112T	I-	04	OBL	8.00	51	-	1120	2469	-	-	778	30.6	272	10.7	212	8.3	10.0	12.6	347	678	2371
265/70R17T	115T	AN	04	SBL	8.00	51	-	1215	2679	-	-	803	31.6	269	10.6	212	8.3	10.0	12.6	360	657	2447
265/70R18T	116T	I-	04	DSB	8.00	51	-	1250	2756	-	-	828	32.6	270	10.6	212	8.3	10.0	12.6	373	637	2525
P285/70R17T	117T	I-	04	DSB	8.50	51	-	1285	2833	-	-	831	32.7	288	11.3	218	8.6	10.0	12.6	371	635	2533

65

215/65R16H	98H	C-	04	OWL	6.50	51	-	750	1653	-	-	684	26.9	225	8.9	164	6.5	8.2	10.3	311	771	2086
215/65R17T	99T	-	04	OWL	6.50	51	-	775	1709	-	-	711	28.0	224	8.8	154	6.1	8.5	10.8	324	742	2167
225/65R17H	102H	F	04	OWL	7.00	51	-	850	1874	-	-	722	28.4	235	9.3	172	6.8	8.3	10.4	329	730	2202
235/65R17H	104H	AK	04	OWL	7.00	51	-	900	1984	-	-	737	29.0	244	9.6	198	7.8	10.0	12.6	334	716	2247
235/65R17S	104S	C-	04	OWL	7.00	51	-	900	1984	-	-	737	29.0	244	9.6	198	7.8	10.0	12.6	334	716	2247
235/65R17T	104T	I-	04	SBL	7.00	51	-	900	1984	-	-	737	29.0	244	9.6	198	7.8	10.0	12.6	334	716	2247
235/65R18H XL	110H	-	04	SBL	7.00	51	-	1060	2337	-	-	761	29.9	242	9.5	188	7.4	9.2	11.6	346	693	2319
245/65R17T XL	111T	I-	04	SBL	7.00	50	-	1090	2403	-	-	751	29.6	255	10.0	206	8.1	10.0	12.6	340	702	2290
255/65R16T	109T	I-	04	SBL	7.50	51	-	1030	2271	-	-	738	29.0	260	10.2	214	8.4	10.0	12.6	332	715	2249
255/65R17T	110T	I-	04	SBL	7.50	51	-	1060	2337	-	-	765	30.1	265	10.4	214	8.4	9.5	12.0	345	690	2331
265/65R17T	112T	I-	04	OBL	8.00	51	-	1120	2469	-	-	774	30.5	276	10.9	222	8.7	9.5	12.0	349	681	2360
265/65R18T	114T	I-	04	SBL	8.00	51	-	1180	2601	-	-	800	31.5	276	10.9	224	8.8	9.5	12.0	362	660	2438
275/65R18T	116T	I-	04	DSB	8.00	51	-	1250	2756	-	-	815	32.1	285	11.2	231	9.1	9.5	12.0	368	647	2485
285/65R17T	116T	I-	04	DSB	8.50	51	-	1250	2756	-	-	801.2	31.5	294.0	11.6	222.0	8.7	9.5	12.0	359	658	2443

60

215/60R17S	96S	C-	04	DSB	6.50	51	-	710	1565	-	-	688	27.1	203	8.0	168	6.6	8.5	10.8	315	767	2098
225/60R17H	99H	G	04	DSB	6.50	51	-	775	1709	-	-	700	27.6	240	9.4	180	7.1	8.2	10.3	320	753	2135
235/60R16H	100H	C-	04	DSB	7.00	51	-	800	1764	-	-	688	27.1	245	9.6	198	7.8	10.0	12.6	313	767	2098
235/60R16T	100T	IZ	04	DSB	7.00	51	-	800	1764	-	-	688	27.1	245	9.6	198	7.8	10.0	12.6	313	767	2098
235/60R18T	103T	IZ	04	DSB	7.00	51	-	875	1929	-	-	738	29.1	252	9.9	198	7.8	10.0	12.6	338	715	2250
245/60R18H	105H	AK	04	DSB	7.00	51	-	925	2039	-	-	749	29.5	259	10.2	196	7.7	8.2	10.3	342	704	2283
255/60R18T	108T	A-	04	SBL	7.50	51	-	1000	2205	-	-	761	30.0	284	11.2	214	8.4	10.0	12.6	347	693	2321

Medida	IC/RV	Uso	Capas	Tipo de Pared	Rin Recomendado	Presión de aire Máx.		Carga Máxima				Diámetro Exterior		Ancho de Sección		Ancho de Banda		Profundidad		Radio Estático de Carga	RPM	Circunferencia de Rodado
						Sencillo	Dual	Sencillo		Dual		mm	pulg	mm	pulg	mm	pulg	mm	pulg (32")			
						psi		kg	lb	kg	lb											

60

265/60R18T XL	114T	A-	04	SBL	8.00	50	-	1180	2601	-	-	773	30.4	286	11.3	222	8.7	10.0	12.6	351	682	2358
275/60R20T	115T	A-	04	SBL	8.00	51	-	1215	2679	-	-	836	32.9	303	11.9	232	9.1	10.0	12.6	382	630	2551

55

255/55R19H XL	111H	IZ	04	DSB	8.00	50	-	1090	2403	-	-	760	29.9	273	10.7	214	8.4	9.0	11.4	349	694	2318
275/55R20T	113T	-	04	DSB	8.50	51	-	1150	2535	-	-	807	31.8	292	11.5	231	9.1	10.0	12.6	370	653	2462

50

255/50R20H XL	109H	-	04	SBL	8.00	50	-	1030	2271	-	-	760	29.9	281	11.1	221	8.7	7.9	9.9	352	694	2316
265/50R20T XL	112T	I-	04	SBL	8.50	50	-	1120	2469	-	-	771	30.4	282	11.1	224	8.8	8.3	10.4	356	684	2352
285/50R20H XL	116H	I-	04	SBL	9.00	50	-	1250	2756	-	-	791	31.2	302	11.9	242	9.5	8.3	10.4	364	666	2413
305/50R20T XL	120T	A-	04	SBL	9.50	50	-	1400	3086	-	-	812	32.0	331	13.0	256	10.1	10.5	13.2	372	649	2476

45

275/45R20H XL	110H	I-	04	DSB	9.00	50	-	1060	2337	-	-	753	29.7	278	10.9	238	9.4	8.7	11.0	349	700	2297
285/45R22T	110T	-	04	DSB	9.50	51	-	1060	2337	-	-	812	32.0	291	11.5	248	9.8	10.0	12.6	378	649	2477
305/45R22T XL	118T	-	04	DSB	10.00	50	-	1320	2910	-	-	831	32.7	307	12.1	265	10.4	10.0	12.6	385	635	2534

LT - Métrico

85

LT215/85R16	115/112S	I-	10	OWL	6.00	80	80	1215	2680	1120	2470	769	30.3	206	8.1	172	6.8	12.1	15.3	357	690	2330
LT235/85R16	120/116S	I-	10	SBL	6.50	80	80	1380	3042	1260	2778	804	31.6	219	8.6	178	7.0	13.1	16.5	372	661	2434

80

LT235/80R17	120/117S	A-	10	SBL	6.50	80	80	1400	3085	1285	2835	806	31.7	230	9.1	188	7.4	12.6	15.9	374	659	2442
-------------	----------	----	----	-----	------	----	----	------	------	------	------	-----	------	-----	-----	-----	-----	------	------	-----	-----	------

75

LT215/75R15	100/97S	IZ	06	DSB	6.00	50	50	800	1765	730	1610	701	27.6	216	8.5	172	6.8	11.6	14.7	326	757	2124
LT225/75R16	115/112S	A-	10	SBL	6.00	80	80	1215	2680	1120	2470	742	29.2	229	9.0	180	7.1	12.1	15.3	345	716	2247
LT225/75R17	116/113S	A-	10	DSB	6.00	80	80	1250	2755	1150	2535	768	30.2	223	8.8	180	7.1	12.1	15.3	358	691	2327
LT235/75R15	104/101S	I-	06	OWL	6.50	50	50	900	1985	825	1820	733	28.8	229	9.0	188	7.4	12.6	15.9	339	725	2219
LT245/75R16	120/116S	I-	10	OWL	7.00	80	80	1380	3042	126	2778	772	30.4	242	9.5	196	7.7	12.6	15.9	358	688	2339
LT245/75R17	121/118S	I-	10	OWL	7.00	80	80	1450	3195	1320	2910	798	31.4	241	9.5	196	7.7	12.1	15.3	371	665	2418
LT255/75R17	121/118Q	-	06	OWL	7.00	80	80	1450	3195	1320	2910	817	32.2	252	9.9	199	7.8	14.6	18.3	379	649	2476
LT265/75R16	112/109S	IZ	06	DSB	7.50	50	50	1120	2470	1030	2270	804	31.7	255	10.0	212	8.3	12.6	15.9	372	660	2436
LT265/75R16	123/120S	A-	10	OBL	7.50	80	80	1550	3415	1400	3085	804	31.7	262	10.3	212	8.3	12.6	15.9	372	660	2436
LT285/75R16	126/123S	-	10	DSB	8.00	80	80	1700	3750	1550	3415	834	32.8	271	10.7	228	9.0	12.6	15.9	385	636	2527
LT285/75R17	121/118S	-	10	DSB	8.00	80	80	1450	3195	1320	2910	859	33.8	271	10.7	228	9.0	12.6	15.9	-	-	-
LT285/75R18	129/126S	-	10	DSB	8.00	80	80	1850	4080	1700	3750	885	34.8	271	10.7	228	9.0	12.6	15.9	-	-	-
LT315/75R16	121/118S	-	08	OWL	8.50	50	50	1450	3195	1320	2910	877	34.5	294	11.6	252	9.9	12.6	15.9	403	605	2658

70

LT225/70R17	110/107S	I-	08	OWL	7.00	50	50	1060	2337	975	2149	789	31.1	218	8.6	180	7.1	12.1	15.3	-	-	-
LT235/70R15	102/99S	IZ	06	OWL	7.00	50	50	850	1875	775	1710	709	27.9	238	9.4	188	7.4	10.2	12.8	329	749	2148
LT235/70R16	104/101S	C-	06	OWL	7.00	50	50	900	1985	825	1820	734	28.9	238	9.4	188	7.4	10.2	12.8	342	723	2224
LT245/70R17	119/116S	I-	10	OWL	7.00	80	80	1360	3000	1250	2755	775	30.5	245	9.6	196	7.7	12.6	15.9	361	685	2347
LT255/70R16	121/117S	I-	10	OWL	7.50	80	80	1450	3195	1285	2835	763	30.1	252	9.9	199	7.8	14.6	18.3	-	-	-
LT255/70R17	110T	IF	06	OWL	7.50	80	-	1060	2337	-	-	763	30.1	252	9.9	199	7.8	14.6	18.3	-	-	-
LT265/70R15	109/105S	IZ	06	OWL	8.00	50	50	1030	2270	925	2040	751	29.6	266	10.5	212	8.3	12.6	15.9	347	707	2275
LT265/70R16	117/114S	I-	08	SBL	8.00	65	65	1285	2835	1180	2600	777	30.6	266	10.5	212	8.3	12.6	15.9	360	683	2354
LT265/70R17	121/118S	-	10	SBL	8.00	80	80	1450	3195	1320	2910	803	31.6	266	10.5	212	8.3	12.1	15.3	373	661	2433
LT265/70R18	124/121S	I-	10	SBL	8.00	80	80	1600	3525	1450	3195	829	32.6	266	10.5	212	8.3	12.1	15.3	386	641	2510
LT275/70R16	112/109S	I-	08	OWL	8.00	80	80	1120	2470	1030	2270	791	31.1	274	10.8	212	8.3	11.6	14.7	366	671	2396
LT275/70R17	121/118S	-	10	OBL	8.00	80	80	1450	3195	1320	2910	817	32.1	272	10.7	220	8.7	12.1	15.3	379	650	2473
LT275/70R18	125/122S	-	10	DSB	8.00	80	80	1650	3640	1500	3305	841	33.1	274	10.8	220	8.7	12.1	15.3	391	631	2549