

Medida	IC/RV	Uso	Capas	Tipo de Pared	Rin Recomendado	Presión de aire Máx.		Carga Máxima				Diámetro Exterior		Ancho de Sección		Ancho de Banda		Profundidad		Radio Estático de Carga	RPM	Circunferencia de Rodado
						Sencillo	Dual	Sencillo		Dual		mm	pulg	mm	pulg	mm	pulg	mm	pulg (32")			
						psi		kg	lb	kg	lb											

LT - Métrico

85

LT215/85R16	115/112Q	-	10	SBL	6.00	80	80	1215	2680	1120	2470	775	30.5	210	8.3	170	6.7	14.6	18.3	359	685	2347
LT235/85R16	120/116Q	-	10	SBL	6.50	80	80	1380	3042	1260	2778	810	31.9	226	8.9	186	7.3	14.6	18.3	374	656	2453

75

LT215/75R15	100/97Q	-	06	OWL	6.00	50	50	800	1765	730	1610	709	27.9	214	8.4	172	6.8	13.1	16.5	329	749	2147
LT215/75R16	115/112Q	-	10	SBL	6.00	80	80	1215	2680	1120	2470	746	29.4	219	8.6	175	6.9	14.6	18.3	347	712	2259
LT225/75R16	115/112Q	-	10	SBL	6.00	80	80	1215	2680	1120	2470	746	29.4	219	8.6	175	6.9	14.6	18.3	347	712	2259
LT235/75R15	104/101Q	-	06	OWL	6.50	50	50	900	1985	825	1820	739	29.1	230	9.1	184	7.2	14.1	17.7	342	719	2238
LT245/75R16	120/116Q	-	10	SBL	7.00	80	80	1380	3042	1260	2778	777	30.6	244	9.6	196	7.7	14.6	18.3	360	683	2353
LT255/75R17	111/108Q	CU	06	SBL	7.00	80	80	1090	2403	1000	2205	817	32.2	252	9.9	199	7.8	14.6	18.3	379	649	2476
LT255/75R17	121/118Q	-	10	SBL	7.00	80	80	1450	3195	1320	2910	817	32.2	252	9.9	199	7.8	14.6	18.3	379	649	2476
LT265/75R16	119/116Q	-	08	OWL	7.50	65	65	1360	3000	1250	2755	807	31.8	259	10.2	208	8.2	14.6	18.3	373	657	2446
LT265/75R16	123/120Q	-	10	OWL	7.50	80	80	1550	3415	1400	3085	807	31.8	259	10.2	208	8.2	14.6	18.3	373	657	2446
LT265/75R16	126/123Q	Q	10	OWL	8.00	80	80	1700	3750	1550	3415	838	33.0	276	10.9	220	8.7	14.6	18.3	386	633	2540
LT285/75R16	122/119Q	-	08	OWL	8.00	65	65	1500	3305	1360	3000	832	32.8	274	10.8	222	8.8	14.6	18.3	384	638	2522
LT285/75R16	126/123Q	-	10	OWL	8.00	80	80	1700	3750	1550	3415	838	33.0	276	10.9	220	8.7	14.6	18.3	386	633	2540
LT295/75R16	123/120Q	-	08	OWL	8.00	65	65	1550	3415	1400	3085	854	33.6	284	11.2	228	9.0	15.5	19.6	393	622	2587
LT315/75R16	121Q	C-	08	OWL	8.50	50	-	1450	3195	-	-	884	34.8	302	11.9	240	9.4	15.5	19.6	406	601	2677
LT315/75R16	127Q	-	10	OWL	8.50	65	-	1750	3860	-	-	884	34.8	302	11.9	240	9.4	15.5	19.6	406	601	2677

70

LT235/70R16	104/101Q	CR	06	OWL	7.00	50	50	900	1985	825	1820	738	29.1	235	9.3	183	7.2	14.1	17.7	344	719	2236
LT265/70R16	110/107Q	-	06	OWL	8.00	50	50	1060	2335	975	2150	784	30.9	263	10.4	210	8.3	14.6	18.3	363	677	2374
LT265/70R17	121/118Q	-	10	SBL	8.00	80	80	1450	3195	1320	2910	809	31.9	263	10.4	210	8.3	14.6	18.3	376	656	2451
LT285/70R17	121/118Q	-	08	SBL	8.50	65	65	1450	3195	1320	2910	837	33.0	282	11.1	226	8.9	15.5	19.6	388	634	2536
LT305/70R16	118/115Q	-	08	SBL	9.00	50	50	1320	2910	1215	2680	840	33.1	300	11.8	240	9.4	15.5	19.6	387	632	2544
LT315/70R17	121/118Q	-	08	SBL	9.50	50	50	1450	3195	1320	2910	879	34.6	308	12.1	246	9.7	15.5	19.6	406	604	2663

65

LT255/65R16	111/108Q	-	06	SBL	7.00	65	65	1090	2403	1000	2205	738	29.1	270	10.6	199	7.8	15.5	19.6	-	-	-
LT275/65R18	123/120Q	-	10	SBL	8.00	80	80	1550	3415	1400	3085	822	32.3	264	10.4	218	8.6	16.0	20.2	383	646	2489
LT325/65R18	127/124Q	-	10	SBL	9.50	65	65	1750	3860	1600	3525	885	34.8	320	12.6	256	10.1	15.5	19.6	410	600	2680

60

LT325/60R18	124/121Q	-	10	SBL	9.50	65	65	1600	3525	1450	3195	853	33.6	320	12.6	256	10.1	15.5	19.6	396	623	2583
-------------	----------	---	----	-----	------	----	----	------	------	------	------	-----	------	-----	------	-----	------	------	------	-----	-----	------

Flotación

28X8.50R15	102Q	-	08	SBL	7.00	65	-	850	1875	-	-	700	27.6	216	8.5	166	6.5	13.8	17.4	325	759	2120
30X9.50R15LT	104Q	-	06	OWL	7.50	50	-	900	1985	-	-	757	29.8	240	9.4	192	7.6	14.1	17.7	350	701	2293
30X9.50R15	104Q	I-	06	OWL	7.50	50	-	900	1985	-	-	755	29.7	224	8.8	188	7.4	13.6	17.1	349	703	2287
31X10.50R15LT	109Q	-	06	OWL	8.50	50	-	1030	2270	-	-	781	30.7	268	10.6	214	8.4	14.6	18.3	360	680	2366
31X10.50R15	109Q	P	06	SBL	8.50	50	-	1030	2270	-	-	781	30.7	268	10.6	214	8.4	14.6	18.3	360	680	2366
31X11.50R15	110Q	-	06	OWL	9.00	50	-	1060	2335	-	-	780	30.7	286	11.3	230	9.1	14.6	18.3	360	681	2363
32X11.50R15	113Q	-	06	OWL	9.00	50	-	1150	2535	-	-	807	31.8	274	10.8	230	9.1	14.6	18.3	371	658	2444
33X12.50R15	108Q	-	06	OWL	10.00	35	-	1000	2205	-	-	833	32.8	310	12.2	248	9.8	14.6	18.3	382	637	2523
33X12.50R18	118Q	-	10	OWL	10.00	65	-	1320	2910	-	-	832	32.7	310	12.2	267	10.5	13.1	16.5	387	638	2519
33X12.50R20	114Q	-	10	OWL	10.00	65	-	1180	2600	-	-	832	32.8	320	12.6	264	10.4	14.6	18.3	391	638	2520
35X12.50R15	113Q	-	06	OWL	10.00	35	-	1150	2535	-	-	883	34.8	310	12.2	248	9.8	15.5	19.6	403	601	2674
35X12.50R17	119Q	C-	08	SBL	10.00	65	-	1360	3000	-	-	883	34.8	310	12.2	248	9.8	16.0	20.2	407	601	2674
35X12.50R17	121Q	-	10	SBL	10.00	65	-	1450	3195	-	-	883	34.8	310	12.2	248	9.8	16.0	20.2	407	601	2674
35X12.50R18	119Q	C-	08	SBL	10.00	65	-	1360	3000	-	-	883	34.8	310	12.2	248	9.8	16.0	20.2	409	601	2674