

SE11

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				
Black Sidewall																	
17"	215/45 R17 XL 91V	7.0	7.0 - 8.0	3.4	50	615	1356	213	8.4	626	24.6	7.1	8.9	292	1909	400	A A O
16"	205/55 R16 91H	6.5	5.0 - 7.5	3.5	51	615	1356	214	8.4	632	24.9	7.1	8.9	291	1928	400	A A O
	205/60 R16 92H	6.0	5.5 - 7.5	3.5	51	630	1389	209	8.2	652	25.7	7.1	8.9	299	1989	400	A A O
15"	195/65 R15 91H	6.0	5.5 - 7.0	3.5	51	615	1356	201	7.9	635	25.0	7.1	8.9	290	1937	400	A A O
	185/65 R15 88S	5.5	5.0 - 6.5	3.5	51	560	1235	189	7.4	621	24.4	7.1	8.9	284	1894	400	A A O
	175/65 R15 84S	5.0	5.0 - 6.0	3.5	51	500	1102	177	7.0	609	24.0	6.1	7.7	279	1857	400	A A O
14"	185/70 R14 88S	5.5	4.5 - 6.0	3.5	51	560	1235	189	7.4	616	24.3	7.1	8.9	279	1879	400	A A O
	175/65 R14 82S	5.0	5.0B - 6.0	3.5	51	475	1047	177	7.0	584	23.0	6.1	7.7	267	1781	400	A A O
	175/70 R14 84S	5.0	4.5 - 6.0	3.5	51	500	1102	177	7.0	602	23.7	6.1	7.7	274	1836	400	A A O
	165/70 R14 81S	5.0	4.0 - 5.5	3.5	51	462	1019	170	6.7	588	23.1	6.1	7.7	268	1793	400	A A O
	155/65 R14 75S	4.5	4.5B - 5.5	3.5	51	387	853	157	6.2	558	22.0	6.1	7.7	257	1702	400	A A O
13"	155/65 R13 73S	4.5	4.5B - 5.5	3.5	51	365	805	157	6.2	532	20.9	6.1	7.7	244	1623	400	A A O
	145/80 R13 75S	4.0	3.5B - 5.0B	3.5	51	387	853	145	5.7	562	22.1	6.1	7.7	256	1714	400	A A O

XL : Extra Load