

# KH27

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG		Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"					
<b>Black Sidewall</b>																		
<b>17"</b>	<b>235/55 R17 99H</b>	7.5	6.5 - 8.5	3.5	51	775	1709	245	9.6	690	27.2	7.6	9.6	317	2105	420	A A	-
	<b>215/45 R17 87V</b>	7.0	7.0 - 8.0	3.5	51	545	1201	213	8.4	626	24.6	8.0	10.1	292	1909	420	A A	O
	<b>205/55 R17 91W</b>	6.5	5.5 - 7.5	3.5	51	615	1356	214	8.4	658	25.9	7.5	9.4	304	2007	420	A A	O
<b>16"</b>	<b>235/60 R16 100H</b>	7.0	6.5 - 8.5	3.5	51	800	1764	240	9.4	688	27.1	7.6	9.6	313	2098	420	A A	-
	<b>225/60 R16 98V</b>	6.5	6.0 - 8.0	3.5	51	750	1653	228	9.0	676	26.6	7.6	9.6	308	2062	420	A A	O
	<b>225/70 R16 103H</b>	6.5	6.0 - 7.5	3.5	51	875	1929	228	9.0	722	28.4	7.6	9.6	326	2202	420	A A	-
	<b>215/60 R16 95V</b>	6.5	6.0 - 7.5	3.5	51	690	1521	221	8.7	664	26.1	7.6	9.6	304	2025	420	A A	O
	<b>215/60 R16 XL 99V</b>	6.5	6.0 - 7.5	3.4	50	775	1709	221	8.7	664	26.1	7.6	9.6	304	2025	420	A A	O
	<b>215/60 R16 XL 99H</b>	6.5	6.0 - 7.5	3.4	50	775	1709	221	8.7	664	26.1	7.6	9.6	304	2025	420	A A	O
	<b>215/65 R16 98H</b>	6.5	6.0 - 7.5	3.5	51	750	1653	221	8.7	686	27.0	7.6	9.6	312	2092	420	A A	-
	<b>205/50 R16 87V</b>	6.5	5.5 - 7.5	3.5	51	545	1201	214	8.4	612	24.1	8.0	10.1	283	1867	420	A A	-
	<b>205/55 R16 91H</b>	6.5	5.5 - 7.5	3.0	44	615	1356	214	8.4	634	25.0	7.6	9.6	296	1915	420	A A	-
	<b>205/60 R16 92H</b>	6.0	5.5 - 7.5	3.5	51	630	1389	209	8.2	652	25.7	7.1	8.9	299	1989	420	A A	-
	<b>205/60 R16 92V</b>	6.0	5.5 - 7.5	3.5	51	630	1389	211	8.7	653	26.0	7.0	8.8	305	315	420	A A	-
	<b>205/60 R16 XL 96V</b>	6.0	5.5 - 7.5	3.4	50	710	1565	209	8.2	652	25.7	7.1	8.9	299	1989	420	A A	-
	<b>205/65 R16 95W</b>	6.0	5.5 - 7.5	3.5	51	690	1521	214	9.0	673	27.0	7.9	10.0	310	318	420	A A	-
	<b>195/50 R16 84H</b>	6.0	5.5 - 7.0	3.5	51	500	1102	201	7.9	602	23.7	7.6	9.6	279	1836	420	A A	-
	<b>195/55 R16 87H</b>	6.0	5.5 - 7.0	3.5	51	545	1201	201	7.9	620	24.4	7.6	9.6	287	1891	420	A A	-
	<b>195/60 R16 89V</b>	6.0	5.5 - 7.0	3.5	51	580	1279	201	7.9	640	25.2	7.6	9.6	294	1952	420	A A	-
<b>15"</b>	<b>215/60 R15 94V</b>	6.5	6.0 - 7.5	3.5	51	670	1477	221	8.7	639	25.2	7.6	9.6	291	1949	420	A A	-
	<b>215/65 R15 96H</b>	6.5	6.0 - 7.5	3.5	51	710	1565	221	8.7	661	26.0	7.6	9.6	300	2016	420	A A	-
	<b>215/65 R15 XL 100V</b>	6.5	6.0 - 7.5	3.4	50	800	1764	221	8.7	661	26.0	7.6	9.6	300	2016	420	A A	-
	<b>205/60 R15 91H</b>	6.0	5.5 - 7.5	3.5	51	615	1356	209	8.2	627	24.7	7.6	9.6	286	1912	420	A A	-
	<b>205/60 R15 91V</b>	6.0	5.5 - 7.5	3.5	51	615	1356	209	8.2	627	24.7	7.6	9.6	286	1912	420	A A	-
	<b>205/65 R15 94H</b>	6.0	5.5 - 7.5	3.5	51	670	1477	209	8.2	647	25.5	7.6	9.6	294	1973	420	A A	-
	<b>195/50 R15 82H</b>	6.0	5.5 - 7.0	3.5	51	475	1047	201	7.9	577	22.7	7.6	9.6	267	1760	420	A A	-
	<b>195/55 R15 85H</b>	6.0	5.5 - 7.0	3.5	51	515	1135	201	7.9	595	23.4	7.6	9.6	274	1815	420	A A	-
	<b>195/60 R15 88H</b>	6.0	5.5 - 7.0	3.5	51	560	1235	201	7.9	615	24.2	7.6	9.6	282	1876	420	A A	-
	<b>195/60 R15 88V</b>	6.0	5.5 - 7.0	3.5	51	560	1235	201	7.9	615	24.2	7.6	9.6	282	1876	420	A A	-
	<b>195/65 R15 91T</b>	6.0	5.5 - 7.0	3.5	51	615	1356	201	7.9	635	25.0	7.6	9.6	290	1937	420	A A	-
	<b>195/65 R15 91H</b>	6.0	5.5 - 7.0	3.5	51	615	1356	201	7.9	635	25.0	7.6	9.6	290	1937	420	A A	-
	<b>195/65 R15 91V</b>	6.0	5.5 - 7.0	3.5	51	615	1356	201	7.9	635	25.0	7.6	9.6	290	1937	420	A A	-
	<b>195/65 R15 XL 95H</b>	6.0	5.5 - 7.0	3.4	50	690	1521	201	7.9	635	25.0	7.6	9.6	290	1937	420	A A	-
	<b>185/55 R15 82H</b>	6.0	5.0 - 6.5	3.5	51	475	1047	194	7.6	585	23.0	7.6	9.6	270	1784	420	A A	-
	<b>185/55 R15 XL 86V</b>	6.0	5.0 - 6.5	3.4	50	530	1168	194	7.6	585	23.0	7.6	9.6	270	1784	420	A A	-
	<b>185/60 R15 84T</b>	5.5	5.0 - 6.5	3.5	51	500	1102	189	7.4	603	23.7	7.6	9.6	277	1839	420	A A	-
	<b>185/60 R15 84H</b>	5.5	5.0 - 6.5	3.5	51	500	1102	189	7.4	603	23.7	7.6	9.6	277	1839	420	A A	-
	<b>185/60 R15 XL 88H</b>	5.5	5.0 - 6.5	3.4	50	560	1235	189	7.4	603	23.7	7.6	9.6	277	1839	420	A A	-
	<b>185/65 R15 88T</b>	5.5	5.0 - 6.5	3.5	51	560	1235	189	7.4	621	24.4	7.6	9.6	284	1894	420	A A	-
	<b>185/65 R15 88H</b>	5.5	5.0 - 6.5	3.0	44	560	1235	195	7.7	619	24.4	8.2	10.3	286	1888	420	A A	-
	<b>185/65 R15 88V</b>	5.5	5.0 - 6.5	3.5	51	560	1235	189	7.4	621	24.4	7.6	9.6	284	1894	420	A A	-
	<b>175/50 R15 75H</b>	5.5	5.0 - 6.0	3.5	51	387	853	182	7.2	557	21.9	7.6	9.6	259	1699	420	A A	-
<b>175/55 R15 77T</b>	5.5	5.0 - 6.0	3.5	51	412	908	182	7.2	573	22.6	7.6	9.6	265	1748	420	A A	-	
<b>175/60 R15 81H</b>	5.0	5.0 - 6.0	3.5	51	462	1019	177	7.0	591	23.3	7.4	9.3	272	1803	420	A A	-	
<b>175/65 R15 84T</b>	5.0	5.0 - 6.0	3.5	51	500	1102	177	7.0	609	24.0	7.4	9.3	279	1857	420	A A	-	
<b>175/65 R15 84H</b>	5.0	5.0 - 6.0	3.5	51	500	1102	177	7.0	609	24.0	7.4	9.3	279	1857	420	A A	-	

XL : Extra Load



# KH27

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				
<b>Black Sidewall</b>																	
<b>15"</b>	<b>165/65 R15 81H</b>	5.0	4.5 - 6.0	3.5	51	462	1019	170	6.7	595	23.4	7.4	9.3	274	1815	420	A A -
	<b>145/65 R15 72T</b>	4.5	4.0 - 5.0	3.5	51	355	783	150	5.9	569	22.4	7.3	9.2	264	1735	420	A A -
<b>14"</b>	<b>195/60 R14 86H</b>	6.0	5.5 - 7.0	3.5	51	530	1168	201	7.9	590	23.2	7.6	9.6	269	1800	420	A A -
	<b>195/60 R14 86V</b>	6.0	5.5 - 7.0	3.5	51	530	1168	201	7.9	590	23.2	7.6	9.6	269	1800	420	A A -
	<b>195/65 R14 89H</b>	6.0	5.5 - 7.0	3.5	51	580	1279	201	7.9	610	24.0	7.6	9.6	277	1861	420	A A -
	<b>195/70 R14 91T</b>	6.0	5.0 - 6.5	3.5	51	615	1356	201	7.9	630	24.8	7.6	9.6	285	1922	420	A A -
	<b>195/70 R14 91H</b>	6.0	5.0 - 6.5	3.5	51	615	1356	201	7.9	630	24.8	7.6	9.6	285	1922	420	A A -
	<b>185/55 R14 80H</b>	6.0	5.0 - 6.5	3.5	51	450	992	194	7.6	560	22.0	7.6	9.6	258	1708	420	A A -
	<b>185/60 R14 82T</b>	5.5	5.0 - 6.5	3.5	51	475	1047	189	7.4	578	22.8	7.6	9.6	265	1763	420	A A -
	<b>185/60 R14 82H</b>	5.5	5.0 - 6.5	3.5	51	475	1047	189	7.4	578	22.8	7.6	9.6	265	1763	420	A A -
	<b>185/65 R14 86T</b>	5.5	5.0 - 6.5	3.5	51	530	1168	189	7.4	596	23.5	7.6	9.6	272	1818	420	A A -
	<b>185/65 R14 86H</b>	5.5	5.0 - 6.5	3.5	51	530	1168	189	7.4	596	23.5	7.6	9.6	272	1818	420	A A -
	<b>185/70 R14 88T</b>	5.5	4.5 - 6.0	3.5	51	560	1235	189	7.4	616	24.3	7.6	9.6	279	1879	420	A A -
	<b>185/70 R14 88H</b>	5.5	4.5 - 6.0	3.5	51	560	1235	189	7.4	616	24.3	7.6	9.6	279	1879	420	A A -
	<b>175/60 R14 79T</b>	5.0	5.0 - 6.0	3.5	51	437	963	177	7.0	566	22.3	7.4	9.3	260	1726	420	A A -
	<b>175/60 R14 79H</b>	5.0	5.0 - 6.0	3.5	51	437	963	177	7.0	566	22.3	7.4	9.3	260	1726	420	A A -
	<b>175/65 R14 82T</b>	5.0	5.0 - 6.0	3.5	51	475	1047	177	7.0	584	23.0	7.8	9.8	267	1781	420	A A -
	<b>175/65 R14 82H</b>	5.0	5.0 - 6.0	3.5	51	475	1047	177	7.0	584	23.0	7.8	9.8	267	1781	420	A A -
	<b>175/70 R14 84T</b>	5.0	4.5 - 6.0	3.5	51	500	1102	177	7.0	602	23.7	7.8	9.8	274	1836	420	A A -
	<b>175/70 R14 XL 88T</b>	5.0	4.5 - 6.0	3.4	50	560	1235	177	7.0	602	23.7	7.8	9.8	274	1836	420	A A -
	<b>175/70 R14 84H</b>	5.0	4.5 - 6.0	3.5	51	500	1102	177	7.0	602	23.7	7.8	9.8	274	1836	420	A A -
	<b>175/80 R14 88T</b>	5.0	4.5 - 6.0	3.5	51	560	1235	177	7.0	636	25.0	7.4	9.3	287	1940	420	A A -
<b>165/60 R14 75H</b>	5.0	4.5 - 6.0	3.5	51	387	853	170	6.7	554	21.8	7.4	9.3	255	1690	420	A A -	
<b>165/65 R14 79T</b>	5.0	4.5 - 6.0	3.5	51	437	963	170	6.7	570	22.4	7.6	9.6	261	1739	420	A A -	
<b>165/70 R14 81T</b>	5.0	4.0 - 5.5	3.5	51	462	1019	170	6.7	588	23.1	7.6	9.6	268	1793	420	A A -	
<b>155/65 R14 75T</b>	4.5	4.5 - 5.5	3.5	51	387	853	157	6.2	558	22.0	7.3	9.2	257	1702	420	A A -	

XL : Extra Load