

# HS51

| Rim                       | Tire Size                  | Measuring Rim Width | Approved Rim Width | Max. Air Pressure |     | Max. Load |      | Section Width |      | Overall Diameter |      | Tread Depth |       | Static Loaded Radius | Rolling Circumference | UTQG |     | Rim Protector |
|---------------------------|----------------------------|---------------------|--------------------|-------------------|-----|-----------|------|---------------|------|------------------|------|-------------|-------|----------------------|-----------------------|------|-----|---------------|
|                           |                            |                     |                    | bar               | psi | kg        | lbs  | mm            | inch | mm               | inch | mm          | x/32" |                      |                       | mm   | mm  |               |
| <b>Black Sidewall</b>     |                            |                     |                    |                   |     |           |      |               |      |                  |      |             |       |                      |                       |      |     |               |
| <b>18"</b>                | <b>235/45 ZR18 XL 98W</b>  | 8.0                 | 7.5 - 9.0          | 3.4               | 50  | 750       | 1653 | 236           | 9.3  | 669              | 26.3 | 8.2         | 10.3  | 311                  | 2040                  | 380  | A A | O             |
| <b>17"</b>                | <b>245/45 ZR17 95W</b>     | 8.0                 | 7.5 - 9.0          | 3.5               | 51  | 690       | 1521 | 243           | 9.6  | 652              | 25.7 | 8.2         | 10.3  | 302                  | 1989                  | 380  | A A | O             |
|                           | <b>235/45 ZR17 XL 97W</b>  | 8.0                 | 7.5 - 9.0          | 3.4               | 50  | 730       | 1609 | 236           | 9.3  | 644              | 25.4 | 8.2         | 10.3  | 299                  | 1964                  | 380  | A A | O             |
|                           | <b>235/55 ZR17 XL 103W</b> | 7.5                 | 6.5 - 8.5          | 3.4               | 50  | 875       | 1929 | 245           | 9.6  | 690              | 27.2 | 8.2         | 10.3  | 317                  | 2105                  | 380  | A A | O             |
|                           | <b>235/65 R17 104V</b>     | 7.0                 | 6.5 - 8.5          | 3.0               | 44  | 900       | 1984 | 240           | 9.4  | 738              | 29.1 | 8.2         | 10.3  | 335                  | 2251                  | 380  | A A | O             |
|                           | <b>225/45 ZR17 91W</b>     | 7.0                 | 7.0 - 8.5          | 3.5               | 51  | 615       | 1356 | 220           | 8.7  | 634              | 25.0 | 8.0         | 10.1  | 298                  | 1922                  | 380  | A A | O             |
|                           | <b>225/45 ZR17 XL 94W</b>  | 7.5                 | 7.0 - 8.5          | 3.4               | 50  | 670       | 1477 | 225           | 8.9  | 634              | 25.0 | 8.2         | 10.3  | 295                  | 1934                  | 380  | A A | O             |
|                           | <b>225/50 ZR17 94W</b>     | 7.0                 | 6.0 - 8.0          | 3.5               | 51  | 670       | 1477 | 233           | 9.2  | 658              | 25.9 | 8.2         | 10.3  | 304                  | 2007                  | 380  | A A | O             |
|                           | <b>225/50 ZR17 XL 98W</b>  | 7.0                 | 6.0 - 8.0          | 3.4               | 50  | 750       | 1653 | 233           | 9.2  | 658              | 14.1 | 8.2         | 10.3  | 187                  | 1092                  | 380  | A A | O             |
|                           | <b>225/55 ZR17 XL 101W</b> | 7.0                 | 6.0 - 8.0          | 3.4               | 50  | 825       | 1819 | 233           | 9.2  | 680              | 26.8 | 8.2         | 10.3  | 313                  | 2074                  | 380  | A A | O             |
|                           | <b>215/40 ZR17 XL 87W</b>  | 7.5                 | 7.0 - 8.5          | 3.4               | 50  | 545       | 1201 | 218           | 8.6  | 604              | 23.8 | 8.2         | 10.3  | 283                  | 1842                  | 380  | A A | O             |
|                           | <b>215/45 ZR17 XL 91W</b>  | 7.0                 | 7.0 - 8.0          | 3.4               | 50  | 615       | 1356 | 213           | 8.4  | 626              | 24.6 | 8.2         | 10.3  | 292                  | 1909                  | 380  | A A | O             |
|                           | <b>215/50 ZR17 91W</b>     | 7.0                 | 6.0 - 7.5          | 3.5               | 51  | 615       | 1356 | 226           | 8.9  | 648              | 25.5 | 8.2         | 10.3  | 300                  | 1976                  | 380  | A A | O             |
|                           | <b>215/50 ZR17 XL 95W</b>  | 7.0                 | 6.0 - 7.5          | 3.4               | 50  | 690       | 1521 | 226           | 8.9  | 648              | 25.5 | 8.2         | 10.3  | 300                  | 1976                  | 380  | A A | O             |
|                           | <b>215/55 ZR17 94W</b>     | 7.0                 | 6.0 - 7.5          | 3.5               | 51  | 670       | 1477 | 226           | 8.9  | 668              | 26.3 | 8.2         | 10.3  | 308                  | 2037                  | 380  | A A | O             |
|                           | <b>205/40 ZR17 XL 84W</b>  | 7.5                 | 7.0 - 8.0          | 3.4               | 50  | 500       | 1102 | 212           | 8.3  | 596              | 23.5 | 8.2         | 10.3  | 280                  | 1818                  | 380  | A A | O             |
|                           | <b>205/45 ZR17 XL 88W</b>  | 7.0                 | 6.5 - 7.5          | 3.4               | 50  | 560       | 1235 | 206           | 8.1  | 616              | 24.3 | 8.2         | 10.3  | 288                  | 1879                  | 380  | A A | O             |
|                           | <b>205/50 ZR17 XL 93W</b>  | 6.5                 | 5.5 - 7.5          | 3.4               | 50  | 650       | 1433 | 214           | 8.4  | 638              | 25.1 | 8.2         | 10.3  | 296                  | 1946                  | 380  | A A | O             |
|                           | <b>205/55 R17 91V</b>      | 6.5                 | 5.5 - 7.5          | 3.5               | 51  | 615       | 1356 | 214           | 8.4  | 658              | 25.9 | 8.2         | 10.3  | 304                  | 2007                  | 380  | A A | O             |
| <b>205/55 R17 XL 95V</b>  | 6.5                        | 5.5 - 7.5           | 3.4                | 50                | 690 | 1521      | 214  | 8.4           | 658  | 25.9             | 8.2  | 10.3        | 304   | 2007                 | 380                   | A A  | O   |               |
| <b>195/40 ZR17 XL 81W</b> | 7.0                        | 6.5 - 7.5           | 3.4                | 50                | 462 | 1019      | 200  | 7.9           | 588  | 23.1             | 8.2  | 10.3        | 277   | 1793                 | 380                   | A A  | O   |               |
| <b>195/45 ZR17 XL 85W</b> | 6.5                        | 6.0 - 7.5           | 3.4                | 50                | 515 | 1135      | 195  | 7.7           | 608  | 23.9             | 8.2  | 10.3        | 285   | 1854                 | 380                   | A A  | O   |               |
| <b>16"</b>                | <b>235/60 R16 XL 104V</b>  | 7.0                 | 6.5 - 8.5          | 3.4               | 50  | 900       | 1984 | 240           | 9.4  | 688              | 27.1 | 8.0         | 10.1  | 313                  | 2098                  | 380  | A A | O             |
|                           | <b>225/50 R16 92V</b>      | 7.0                 | 6.0 - 8.0          | 3.5               | 51  | 630       | 1389 | 233           | 9.2  | 632              | 24.9 | 8.2         | 10.3  | 291                  | 1928                  | 380  | A A | O             |
|                           | <b>225/50 ZR16 92W</b>     | 7.0                 | 6.0 - 8.0          | 3.5               | 51  | 630       | 1389 | 233           | 9.2  | 632              | 24.9 | 8.2         | 10.3  | 291                  | 1928                  | 380  | A A | O             |
|                           | <b>225/55 ZR16 95W</b>     | 7.0                 | 6.0 - 8.0          | 3.5               | 51  | 690       | 1521 | 233           | 9.2  | 654              | 25.7 | 8.2         | 10.3  | 300                  | 1995                  | 380  | A A | O             |
|                           | <b>225/55 ZR16 XL 99W</b>  | 7.0                 | 6.0 - 8.0          | 3.4               | 50  | 775       | 1709 | 233           | 9.2  | 654              | 25.7 | 8.2         | 10.3  | 300                  | 1995                  | 380  | A A | O             |
|                           | <b>225/60 ZR16 98W</b>     | 6.5                 | 6.0 - 8.0          | 3.5               | 51  | 750       | 1653 | 228           | 9.0  | 676              | 26.6 | 8.0         | 10.1  | 308                  | 2062                  | 380  | A A | O             |
|                           | <b>215/40 ZR16 XL 86W</b>  | 7.5                 | 7.5 - 8.5          | 3.4               | 50  | 530       | 1168 | 218           | 8.6  | 578              | 22.8 | 8.2         | 10.3  | 270                  | 1763                  | 380  | A A | O             |
|                           | <b>215/45 R16 XL 90V</b>   | 7.0                 | 7.0 - 8.0          | 3.4               | 50  | 600       | 1323 | 213           | 8.4  | 600              | 23.6 | 8.2         | 10.3  | 279                  | 1830                  | 380  | A A | O             |
|                           | <b>215/55 R16 93V</b>      | 7.0                 | 6.0 - 7.5          | 3.5               | 51  | 650       | 1433 | 226           | 8.9  | 642              | 25.3 | 8.2         | 10.3  | 295                  | 1958                  | 380  | A A | O             |
|                           | <b>215/55 ZR16 93W</b>     | 7.0                 | 6.0 - 7.5          | 3.5               | 51  | 650       | 1433 | 226           | 8.9  | 642              | 25.3 | 8.2         | 10.3  | 295                  | 1958                  | 380  | A A | O             |
|                           | <b>215/55 ZR16 XL 97W</b>  | 7.0                 | 6.0 - 7.5          | 3.4               | 50  | 730       | 1609 | 226           | 8.9  | 642              | 25.3 | 8.2         | 10.3  | 295                  | 1958                  | 380  | A A | O             |
|                           | <b>215/60 R16 95V</b>      | 6.5                 | 6.0 - 7.5          | 3.0               | 44  | 690       | 1521 | 221           | 8.7  | 664              | 26.1 | 8.0         | 10.1  | 304                  | 2025                  | 380  | A A | O             |
|                           | <b>215/60 ZR16 XL 99W</b>  | 6.5                 | 6.0 - 7.5          | 3.4               | 50  | 775       | 1709 | 221           | 8.7  | 664              | 26.1 | 8.0         | 10.1  | 304                  | 2025                  | 380  | A A | O             |
|                           | <b>205/45 ZR16 XL 87W</b>  | 7.0                 | 6.5 - 7.5          | 3.4               | 50  | 545       | 1201 | 206           | 8.1  | 590              | 23.2 | 8.2         | 10.3  | 275                  | 1800                  | 380  | A A | O             |
|                           | <b>205/50 R16 87V</b>      | 6.5                 | 5.5 - 7.5          | 3.5               | 51  | 545       | 1201 | 214           | 8.4  | 612              | 24.1 | 8.2         | 10.3  | 283                  | 1867                  | 380  | A A | O             |
|                           | <b>205/50 ZR16 87W</b>     | 6.5                 | 5.5 - 7.5          | 3.5               | 51  | 545       | 1201 | 214           | 8.4  | 612              | 24.1 | 8.2         | 10.3  | 283                  | 1867                  | 380  | A A | O             |
|                           | <b>205/55 R16 91V</b>      | 6.5                 | 5.5 - 7.5          | 3.5               | 51  | 615       | 1356 | 214           | 8.4  | 632              | 24.9 | 8.2         | 10.3  | 291                  | 1928                  | 380  | A A | O             |
|                           | <b>205/55 ZR16 91W</b>     | 6.5                 | 5.5 - 7.5          | 3.5               | 51  | 615       | 1356 | 214           | 8.4  | 632              | 24.9 | 8.2         | 10.3  | 291                  | 1928                  | 380  | A A | O             |
| <b>205/55 R16 XL 94V</b>  | 6.5                        | 5.5 - 7.5           | 3.4                | 50                | 670 | 1477      | 214  | 8.4           | 632  | 24.9             | 8.2  | 10.3        | 291   | 1928                 | 380                   | A A  | O   |               |
| <b>205/55 ZR16 XL 94W</b> | 6.5                        | 5.5 - 7.5           | 3.4                | 50                | 670 | 1477      | 214  | 8.4           | 632  | 24.9             | 8.2  | 10.3        | 291   | 1928                 | 380                   | A A  | O   |               |
| <b>205/60 R16 92H</b>     | 6.0                        | 5.5 - 7.5           | 3.0                | 44                | 630 | 1389      | 209  | 8.2           | 652  | 25.7             | 8.0  | 10.1        | 299   | 1989                 | 380                   | A A  | O   |               |
| <b>195/45 R16 80V</b>     | 6.5                        | 6.0 - 7.5           | 3.5                | 51                | 450 | 992       | 195  | 7.7           | 582  | 22.9             | 8.2  | 10.3        | 272   | 1775                 | 380                   | A A  | O   |               |
| <b>195/45 R16 XL 84V</b>  | 6.5                        | 6.0 - 7.5           | 3.4                | 50                | 500 | 1102      | 195  | 7.7           | 582  | 22.9             | 8.2  | 10.3        | 272   | 1775                 | 380                   | A A  | O   |               |

XL : Extra Load



# HS51

| Rim                   | Tire Size                | Measuring Rim Width | Approved Rim Width | Max. Air Pressure |     | Max. Load |      | Section Width |      | Overall Diameter |      | Tread Depth |       | Static Loaded Radius | Rolling Circumference | UTQG | Rim Protector |
|-----------------------|--------------------------|---------------------|--------------------|-------------------|-----|-----------|------|---------------|------|------------------|------|-------------|-------|----------------------|-----------------------|------|---------------|
|                       |                          |                     |                    | bar               | psi | kg        | lbs  | mm            | inch | mm               | inch | mm          | x/32" |                      |                       |      |               |
| <b>Black Sidewall</b> |                          |                     |                    |                   |     |           |      |               |      |                  |      |             |       |                      |                       |      |               |
| <b>16"</b>            | <b>195/50 ZR16 84W</b>   | 6.0                 | 5.5 - 7.0          | 3.5               | 51  | 500       | 1102 | 201           | 7.9  | 602              | 23.7 | 8.2         | 10.3  | 279                  | 1836                  | 380  | A A O         |
|                       | <b>195/50 R16 XL 88V</b> | 6.0                 | 5.5 - 7.0          | 3.4               | 50  | 560       | 1235 | 201           | 7.9  | 602              | 23.7 | 8.2         | 10.3  | 279                  | 1836                  | 380  | A A O         |
|                       | <b>195/55 R16 87V</b>    | 6.0                 | 5.5 - 7.0          | 3.5               | 51  | 545       | 1201 | 201           | 7.9  | 620              | 24.4 | 8.2         | 10.3  | 287                  | 1891                  | 380  | A A O         |
|                       | <b>195/55 ZR16 87W</b>   | 6.0                 | 5.5 - 7.0          | 3.5               | 51  | 545       | 1201 | 201           | 7.9  | 620              | 24.4 | 8.2         | 10.3  | 287                  | 1891                  | 380  | A A O         |
|                       | <b>185/50 R16 81V</b>    | 6.0                 | 5.0 - 6.5          | 3.5               | 51  | 462       | 1019 | 194           | 7.6  | 592              | 23.3 | 8.2         | 10.3  | 276                  | 1806                  | 380  | A A O         |
|                       | <b>185/55 R16 83V</b>    | 6.0                 | 5.0 - 6.5          | 3.5               | 51  | 487       | 1074 | 194           | 7.6  | 610              | 24.0 | 8.2         | 10.3  | 283                  | 1861                  | 380  | A A O         |
|                       | <b>165/40 R16 XL 73V</b> | 6.0                 | 6.0 - 6.0          | 3.4               | 50  | 365       | 805  | 170           | 6.7  | 538              | 21.2 | 7.5         | 9.4   | 255                  | 1641                  | 380  | A A O         |
|                       | <b>165/45 R16 XL 74V</b> | 6.5                 | 6.0 - 7.5          | 3.4               | 50  | 375       | 827  | 195           | 7.7  | 582              | 22.9 | 7.5         | 9.4   | 272                  | 1775                  | 380  | A A O         |
|                       | <b>165/50 R16 75V</b>    | 5.0                 | 4.5 - 6.0          | 3.5               | 51  | 387       | 853  | 170           | 6.7  | 572              | 22.5 | 7.5         | 9.4   | 268                  | 1745                  | 380  | A A O         |
| <b>15"</b>            | <b>225/60 ZR15 96W</b>   | 6.5                 | 6.0 - 8.0          | 3.5               | 51  | 710       | 1565 | 228           | 9.0  | 651              | 25.6 | 8.0         | 10.1  | 296                  | 1986                  | 380  | A A O         |
|                       | <b>205/50 R15 86V</b>    | 6.5                 | 5.5 - 7.5          | 3.5               | 51  | 530       | 1168 | 214           | 8.4  | 587              | 23.1 | 8.2         | 10.3  | 271                  | 1790                  | 380  | A A O         |
|                       | <b>205/55 R15 88V</b>    | 6.5                 | 5.5 - 7.5          | 3.5               | 51  | 560       | 1235 | 214           | 8.4  | 607              | 23.9 | 8.2         | 10.3  | 279                  | 1851                  | 380  | A A O         |
|                       | <b>205/60 R15 91V</b>    | 6.0                 | 5.5 - 7.5          | 3.5               | 51  | 615       | 1356 | 209           | 8.2  | 627              | 24.7 | 8.2         | 10.3  | 286                  | 1912                  | 380  | A A O         |
|                       | <b>205/65 R15 94V</b>    | 6.0                 | 5.5 - 7.5          | 3.5               | 51  | 670       | 1477 | 209           | 8.2  | 647              | 25.5 | 8.2         | 10.3  | 294                  | 1973                  | 380  | A A O         |
|                       | <b>195/45 R15 78V</b>    | 6.5                 | 6.0 - 7.5          | 3.5               | 51  | 425       | 937  | 195           | 7.7  | 557              | 21.9 | 8.2         | 10.3  | 259                  | 1699                  | 380  | A A O         |
|                       | <b>195/50 R15 82V</b>    | 6.0                 | 5.5 - 7.0          | 3.5               | 51  | 475       | 1047 | 201           | 7.9  | 577              | 22.7 | 8.2         | 10.3  | 267                  | 1760                  | 380  | A A O         |
|                       | <b>195/55 R15 85V</b>    | 6.0                 | 5.5 - 7.0          | 3.5               | 51  | 515       | 1135 | 201           | 7.9  | 595              | 23.4 | 8.2         | 10.3  | 274                  | 1815                  | 380  | A A O         |
|                       | <b>195/65 R15 91V</b>    | 6.0                 | 5.5 - 7.0          | 3.5               | 51  | 615       | 1356 | 201           | 7.9  | 635              | 25.0 | 8.2         | 10.3  | 290                  | 1937                  | 380  | A A O         |
|                       | <b>185/55 R15 82V</b>    | 6.0                 | 5.0 - 6.5          | 3.5               | 51  | 475       | 1047 | 194           | 7.6  | 585              | 23.0 | 8.2         | 10.3  | 270                  | 1784                  | 380  | A A O         |
|                       | <b>165/50 R15 73V</b>    | 5.0                 | 4.5 - 6.0          | 3.5               | 51  | 365       | 805  | 170           | 6.7  | 547              | 21.5 | 7.5         | 9.4   | 255                  | 1668                  | 380  | A A O         |
|                       | <b>165/55 R15 75V</b>    | 5.0                 | 4.5 - 6.0          | 3.5               | 51  | 387       | 853  | 170           | 6.7  | 563              | 22.2 | 7.5         | 9.4   | 261                  | 1717                  | 380  | A A O         |
| <b>14"</b>            | <b>205/60 R14 88H</b>    | 6.0                 | 5.5 - 7.5          | 3.5               | 51  | 560       | 1235 | 209           | 8.2  | 602              | 23.7 | 8.2         | 10.3  | 274                  | 1836                  | 380  | A A O         |
|                       | <b>205/65 R14 91V</b>    | 6.0                 | 5.5 - 7.5          | 3.5               | 51  | 615       | 1356 | 209           | 8.2  | 622              | 24.5 | 8.2         | 10.3  | 282                  | 1897                  | 380  | A A O         |
|                       | <b>165/55 R14 XL 76V</b> | 5.0                 | 4.5 - 6.0          | 3.4               | 50  | 400       | 882  | 170           | 6.7  | 538              | 21.2 | 7.5         | 9.4   | 249                  | 1641                  | 380  | A A O         |
|                       | <b>155/55 R14 69V</b>    | 5.0                 | 4.5 - 5.5          | 3.5               | 51  | 325       | 716  | 162           | 6.4  | 526              | 20.7 | 7.5         | 9.4   | 244                  | 1604                  | 380  | A A O         |

XL : Extra Load