

PA31

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				
Black Sidewall																	
18"	245/40 R18 XL 97V	8.5	8.0 - 9.5	3.4	50	730	1609	248	9.8	653	25.7	8.5	10.7	305	1992	500	A A O
	245/55 R18 103V	7.5	7.0 - 8.5	3.5	51	875	1929	253	10.0	727	28.6	8.5	10.7	334	2217	500	A A O
	235/40 R18 XL 95V	8.5	8.0 - 9.5	3.4	50	690	1521	241	9.5	645	25.4	8.5	10.7	302	1967	500	A A O
	235/50 R18 97V	7.5	6.5 - 8.5	3.5	51	730	1609	245	9.6	693	27.3	8.5	10.7	321	2114	500	A A O
	235/55 R18 100V	7.5	6.5 - 8.5	3.5	51	800	1764	245	9.6	715	28.1	8.5	10.7	329	2181	500	A A O
	225/40 R18 XL 92V	8.0	7.5 - 9.0	3.4	50	630	1389	230	9.1	637	25.1	8.5	10.7	299	1943	500	A A O
	225/45 R18 XL 95V	7.5	7.0 - 8.5	3.4	50	690	1521	225	8.9	659	25.9	8.5	10.7	307	2010	500	A A O
	225/50 R18 95V	7.0	6.0 - 8.0	3.5	51	690	1521	233	9.2	683	26.9	8.5	10.7	317	2083	500	A A O
	215/35 R18 XL 84V	7.5	7.0 - 8.5	3.4	50	500	1102	218	8.6	607	23.9	8.5	10.7	287	1851	500	A A O
	215/45 R18 89V	7.0	7.0 - 8.0	3.5	51	580	1279	213	8.4	651	25.6	8.5	10.7	304	1986	500	A A O
215/55 R18 95V	7.0	6.0 - 7.5	3.5	51	690	1521	226	8.9	693	27.3	8.5	10.7	321	2114	500	A A O	
17"	245/45 R17 XL 99V	8.0	7.5 - 9.0	3.4	50	775	1709	243	9.6	652	25.7	8.5	10.7	302	1989	500	A A O
	235/45 R17 XL 97V	8.0	7.5 - 9.0	3.4	50	730	1609	236	9.3	644	25.4	8.5	10.7	299	1964	500	A A O
	235/50 R17 96V	7.5	6.5 - 8.5	3.5	51	710	1565	245	9.6	668	26.3	8.5	10.7	308	2037	500	A A O
	235/55 R17 99V	7.5	6.5 - 8.5	3.5	51	775	1709	245	9.6	690	27.2	8.8	11.1	317	2105	500	A A O
	225/45 R17 XL 94V	7.5	7.0 - 8.5	3.4	50	670	1477	225	8.9	634	25.0	8.5	10.7	295	1934	500	A A O
	225/50 R17 94V	7.0	6.0 - 8.0	3.5	51	670	1477	233	9.2	658	25.9	8.5	10.7	304	2007	500	A A O
	225/55 R17 97V	7.0	6.0 - 8.0	3.5	51	730	1609	233	9.2	680	26.8	8.5	10.7	313	2074	500	A A O
	215/45 R17 XL 91V	7.0	7.0 - 8.0	3.4	50	615	1356	213	8.4	626	24.6	8.5	10.7	292	1909	500	A A O
	215/50 R17 XL 95V	7.0	6.0 - 7.5	3.4	50	690	1521	226	8.9	648	25.5	8.5	10.7	300	1976	500	A A O
	215/55 R17 94V	7.0	6.0 - 7.5	3.5	51	670	1477	226	8.9	668	26.3	8.5	10.7	308	2037	500	A A O
205/45 R17 84V	7.0	6.5 - 7.5	3.5	51	500	1102	206	8.1	616	24.3	8.5	10.7	288	1879	500	A A O	
205/50 R17 XL 93V	6.5	5.5 - 7.5	3.4	50	650	1433	214	8.4	638	25.1	8.8	11.1	296	1946	500	A A O	
16"	245/50 R16 97V	7.5	7.0 - 8.5	3.5	51	730	1609	253	10.0	652	25.7	8.5	10.7	299	1989	500	A A O
	235/60 R16 100V	7.0	6.5 - 8.5	3.5	51	800	1764	240	9.4	688	27.1	8.5	10.7	313	2098	500	A A O
	225/50 R16 92V	7.0	6.0 - 8.0	3.5	51	630	1389	233	9.2	632	24.9	8.5	10.7	291	1928	500	A A O
	225/55 R16 XL 99V	7.0	6.0 - 8.0	3.4	50	775	1709	233	9.2	654	25.7	8.5	10.7	300	1995	500	A A O
	215/55 R16 XL 97V	7.0	6.0 - 7.5	3.4	50	730	1609	226	8.9	642	25.3	8.5	10.7	295	1958	500	A A O
	215/60 R16 95V	6.5	6.0 - 7.5	3.5	51	690	1521	221	8.7	664	26.1	8.5	10.7	304	2025	500	A A O
	205/50 R16 XL 91V	6.5	5.5 - 7.5	3.4	50	615	1356	214	8.4	612	24.1	8.5	10.7	283	1867	500	A A O
	205/55 R16 91V	6.5	5.5 - 7.5	3.5	51	615	1356	214	8.4	632	24.9	8.5	10.7	291	1928	500	A A O
	195/55 R16 87V	6.0	5.5 - 7.0	3.5	51	545	1201	201	7.9	620	24.4	8.5	10.7	287	1891	500	A A O
	195/60 R16 89V	6.0	5.5 - 7.0	3.5	51	580	1279	201	7.9	640	25.2	8.5	10.7	294	1952	500	A A O
185/55 R16 83V	6.0	5.0 - 6.5	3.5	51	487	1074	194	7.6	610	24.0	8.5	10.7	283	1861	500	A A O	
15"	205/50 R15 86V	6.5	5.5 - 7.5	3.5	51	530	1168	214	8.4	587	23.1	8.5	10.7	271	1790	500	A A O
	195/50 R15 82V	6.0	5.5 - 7.0	3.5	51	475	1047	201	7.9	577	22.7	8.5	10.7	267	1760	500	A A O
	195/55 R15 85V	6.0	5.5 - 7.0	3.5	51	515	1135	201	7.9	595	23.4	8.5	10.7	274	1815	500	A A O
	185/55 R15 82V	6.0	5.0 - 6.5	3.5	51	475	1047	194	7.6	585	23.0	8.5	10.7	270	1784	500	A A O
	175/65 R15 84V	5.0	5.0 - 6.0	3.5	51	500	1102	177	7.0	609	24.0	8.5	10.7	279	1857	500	A A O

XL : Extra Load