

PS31

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				
Black Sidewall																	
18"	275/35 ZR18 XL 99W	9.5	9.0 - 11.0	3.4	50	775	1709	278	10.9	649	25.6	8.2	10.3	303	1979	400	A A O
	275/40 ZR18 99W	9.5	9.0 - 11.0	3.5	51	775	1709	278	10.9	677	26.7	8.2	10.3	314	2065	400	A A O
	265/35 ZR18 XL 97W	9.5	9.0 - 10.5	3.4	50	730	1609	271	10.7	643	25.3	8.2	10.3	301	1961	400	A A O
	255/35 ZR18 XL 94W	9.0	8.5 - 10.0	3.4	50	670	1477	260	10.2	635	25.0	8.2	10.3	298	1937	400	A A O
	255/45 ZR18 99W	8.5	8.0 - 9.5	3.5	51	775	1709	255	10.0	687	27.0	8.2	10.3	318	2095	400	A A O
	* 245/40 ZR18 93W	8.5	8.0 - 9.5	3.5	51	650	1433	248	9.8	653	25.7	8.2	10.3	305	1992	400	A A *
	245/40 ZR18 XL 97W	8.5	8.0 - 9.5	3.4	50	730	1609	248	9.8	653	25.7	8.2	10.3	305	1992	400	A A O
	245/45 ZR18 XL 100W	8.0	7.5 - 9.0	3.4	50	800	1764	243	9.6	677	26.7	8.2	10.3	314	2065	400	A A O
	245/50 ZR18 100W	7.5	7.0 - 8.5	3.5	51	800	1764	253	10.0	703	27.7	8.2	10.3	324	2144	400	A A O
	235/40 ZR18 XL 95W	8.5	8.0 - 9.5	3.4	50	690	1521	241	9.5	645	25.4	8.2	10.3	302	1967	400	A A O
	235/45 ZR18 XL 98W	8.0	7.5 - 9.0	3.4	50	750	1653	236	9.3	669	26.3	8.2	10.3	311	2040	400	A A O
	235/50 ZR18 XL 101W	7.5	6.5 - 8.5	3.4	50	825	1819	245	9.6	693	27.3	8.2	10.3	321	2114	400	A A O
	225/40 ZR18 XL 92W	8.0	7.5 - 9.0	3.4	50	630	1389	230	9.1	637	25.1	8.2	10.3	299	1943	400	A A O
	225/45 ZR18 91W	7.5	7.0 - 8.5	3.5	51	615	1356	225	8.9	659	25.9	8.2	10.3	307	2010	400	A A O
	225/50 ZR18 95W	7.0	6.0 - 8.0	3.5	51	690	1521	233	9.2	683	26.9	8.2	10.3	317	2083	400	A A O
	215/40 ZR18 XL 89W	7.5	7.0 - 8.5	3.4	50	580	1279	218	8.6	629	24.8	8.2	10.3	296	1918	400	A A O
215/45 ZR18 XL 93W	7.0	7.0 - 8.0	3.4	50	650	1433	213	8.4	651	25.6	8.2	10.3	304	1986	400	A A O	
17"	275/40 ZR17 98W	9.5	9.0 - 11.0	3.5	51	750	1653	278	10.9	652	25.7	8.2	10.3	302	1989	400	A A O
	255/40 ZR17 94W	9.0	8.5 - 10.0	3.5	51	670	1477	260	10.2	636	25.0	8.2	10.3	296	1940	400	A A O
	245/40 ZR17 91W	8.5	8.0 - 9.5	3.5	51	615	1356	248	9.8	628	24.7	8.2	10.3	292	1915	400	A A O
	245/45 ZR17 95W	8.0	7.5 - 9.0	3.5	51	690	1521	243	9.6	652	25.7	8.2	10.3	302	1989	400	A A O
	235/45 ZR17 94W	8.0	7.5 - 9.0	3.5	51	670	1477	236	9.3	644	25.4	8.2	10.3	299	1964	400	A A O
	* 235/45 ZR17 XL 97W	7.0	6.5 - 7.5	3.4	50	462	1019	200	7.9	588	23.1	8.2	10.3	277	1793	400	A A *
	235/50 ZR17 XL 100W	7.5	6.5 - 8.5	3.4	50	800	1764	245	9.6	668	26.3	8.2	10.3	308	2037	400	A A O
	235/55 ZR17 XL 103W	7.5	6.5 - 8.5	3.4	50	875	1929	245	9.6	690	27.2	8.2	10.3	317	2105	400	A A O
	* 225/45 ZR17 91W	8.0	7.5 - 9.0	3.4	50	730	1609	236	9.3	644	25.4	8.2	10.3	299	1964	400	A A *
	225/45 ZR17 XL 94W	7.5	7.0 - 8.5	3.4	50	670	1477	225	8.9	634	25.0	8.2	10.3	295	1934	400	A A O
	225/50 ZR17 XL 98W	7.0	6.0 - 8.0	3.4	50	750	1653	233	9.2	658	25.9	8.2	10.3	304	2007	400	A A O
	225/55 ZR17 XL 101W	7.0	6.0 - 8.0	3.4	50	825	1819	233	9.2	680	26.8	8.2	10.3	313	2074	400	A A O
	215/40 ZR17 XL 87W	7.5	7.0 - 8.5	3.4	50	545	1201	218	8.6	604	23.8	8.2	10.3	283	1842	400	A A O
	215/45 ZR17 XL 91W	7.0	7.0 - 8.0	3.4	50	615	1356	213	8.4	626	24.6	8.2	10.3	292	1909	400	A A O
	215/50 ZR17 XL 95W	7.0	6.0 - 7.5	3.4	50	690	1521	226	8.9	648	25.5	8.2	10.3	300	1976	400	A A O
	215/55 ZR17 94W	7.0	6.0 - 7.5	3.5	51	670	1477	226	8.9	668	26.3	8.2	10.3	308	2037	400	A A O
205/40 ZR17 XL 84W	7.5	7.0 - 8.0	3.4	50	500	1102	212	8.3	596	23.5	8.2	10.3	280	1818	400	A A O	
205/45 ZR17 XL 88W	7.0	6.5 - 7.5	3.4	50	560	1235	206	8.1	616	24.3	8.2	10.3	288	1879	400	A A O	
205/50 ZR17 XL 93W	6.5	5.5 - 7.5	3.4	50	650	1433	214	8.4	638	25.1	8.2	10.3	296	1946	400	A A O	
* 195/40 ZR17 XL 81W	7.5	7.0 - 8.5	3.5	51	615	1356	225	8.9	634	25.0	8.2	10.3	295	1934	400	A A *	

XL : Extra Load

* Available at the 1st Quarter of 2017

* Available at the 2nd Quarter of 2017



PS31

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				
Black Sidewall																	
16"	* 235/60 R16 XL 104V	6.5	6.0 - 7.5	3.4	50	500	1102	195	7.7	582	22.9	8.2	10.3	272	1775	400	A A *
	225/50 ZR16 92W	7.0	6.0 - 8.0	3.5	51	630	1389	233	9.2	632	24.9	8.2	10.3	291	1928	400	A A O
	225/55 ZR16 95W	7.0	6.0 - 8.0	3.5	51	690	1521	233	9.2	654	25.7	8.2	10.3	300	1995	400	A A O
	215/55 ZR16 XL 97W	7.0	6.0 - 7.5	3.4	50	730	1609	226	7.6	642	25.3	8.2	10.3	295	1958	400	A A O
	* 215/60 R16 95V	6.0	5.0 - 6.5	3.5	51	462	1019	194	8.9	592	23.3	8.2	10.3	276	1806	400	A A *
	205/45 ZR16 XL 87W	7.0	6.5 - 7.5	3.4	50	545	1201	206	8.1	590	23.2	8.2	10.3	275	1800	400	A A O
	205/50 ZR16 87W	6.5	5.5 - 7.5	3.5	51	545	1201	214	8.4	612	24.1	8.2	10.3	283	1867	400	A A O
	* 205/55 R16 91V	6.5	5.5 - 7.5	3.5	51	615	1356	214	8.4	632	24.9	8.2	10.3	291	1928	400	A A *
	205/55 ZR16 91W	6.5	5.5 - 7.5	3.5	51	615	1356	214	8.4	632	24.9	8.2	10.3	291	1928	400	A A O
	* 205/60 R16 XL 96V	6.0	5.5 - 7.0	3.5	51	545	1202	201	7.9	620	24.4	8.2	10.3	287	1891	400	A A *
	* 195/45 R16 XL 84V	6.0	5.0 - 6.5	3.5	51	450	992	194	7.6	560	22.0	8.2	10.3	258	1708	400	A A *
	195/50 R16 XL 88V	6.0	5.5 - 7.0	2.9	42	560	1235	201	7.9	602	23.7	8.0	10.1	235	1836	400	A A O
	* 195/55 R16 87V	7.0	6.5 - 8.5	3.4	50	900	1984	240	9.4	688	27.1	8.2	10.3	313	2098	400	A A *
	* 185/50 R16 81V	6.5	6.0 - 7.5	3.5	51	690	1521	221	8.7	664	26.1	8.2	10.3	304	2025	400	A A *
15"	205/50 R15 86V	6.5	5.5 - 7.5	3.5	51	530	1168	214	8.4	587	23.1	8.2	10.3	271	1790	400	A A O
	205/55 R15 88V	6.5	5.5 - 7.5	3.5	51	560	1235	214	8.4	607	23.9	8.2	10.3	279	1851	400	A A O
	* 205/60 R15 91V	6.0	5.5 - 7.5	3.4	50	710	1565	209	8.2	652	25.7	8.2	10.3	299	1989	400	A A *
	* 205/65 R15 94V	6.0	5.5 - 7.5	3.5	51	615	1356	209	8.2	627	24.7	8.2	10.3	286	1912	400	A A *
	195/45 R15 78V	6.5	6.0 - 7.5	2.5	36	425	937	195	7.7	557	21.9	8.0	10.1	217	1699	400	A A O
	195/50 R15 82V	6.0	5.5 - 7.0	3.5	51	475	1047	201	7.9	577	22.7	8.2	10.3	267	1760	400	A A O
	195/55 R15 85V	6.0	5.5 - 7.0	3.5	51	515	1135	201	7.9	595	23.4	8.2	10.3	274	1815	400	A A O
	* 195/60 R15 88V	6.0	5.5 - 7.0	3.5	51	560	1235	201	7.9	615	24.2	8.2	10.3	282	1876	400	A A *
	* 195/65 R15 91V	5.5	5.0 - 6.5	3.5	51	500	1102	189	7.4	603	23.7	8.2	10.3	277	1839	400	A A *
	185/55 R15 82V	6.0	5.0 - 6.5	3.5	51	475	1047	194	7.6	585	23.0	8.2	10.3	270	1784	400	A A O
	* 185/60 R15 84V	5.5	5.0 - 6.5	3.5	51	475	1047	189	7.4	578	22.8	8.2	10.3	265	1763	400	A A *
165/50 R15 73V	5.0	4.5 - 6.0	2.5	42	355	783	170	6.7	547	21.5	8.0	10.1	217	1699	400	A A O	
14"	* 185/55 R14 80H	5.5B	5.0B - 6.5	3.5	51	450	992	189	7.4	552	21.7	8.2	10.3	252	1684	400	A A *
	* 185/60 R14 82V	6.0	5.5 - 7.5	3.5	51	670	1477	209	8.2	647	25.5	8.2	10.3	294	1973	400	A A *
	* 185/65 R14 86V	6.0	5.5 - 7.0	3.5	51	615	1356	201	7.9	635	25.0	8.2	10.3	290	1937	400	A A *
	165/55 R14 XL 76V	5.0	4.5 - 6.0	3.4	50	400	882	170	6.7	538	21.2	8.2	10.3	249	1641	400	A A O
13"	* 185/60 R13 80H	5.5	5.0 - 6.5	3.5	51	530	1168	189	7.4	596	23.5	8.2	10.3	272	1818	400	A A *

XL : Extra Load

* Available at the 1st Quarter of 2017

* Available at the 2nd Quarter of 2017