

PS71

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				
Black Sidewall																	
20"	275/30 ZR20 XL 97Y	9.5	9.0 - 10.0	3.4	50	730	1609	278	10.9	675	26.6	8.0	10.2	319	2059	* * *	O
	275/35 ZR20 XL 102Y	9.5	9.0 - 11.0	3.4	50	850	1874	278	10.9	701	27.6	8.0	10.2	329	2138	* * *	O
	255/30 ZR20 XL 92Y	9.0	8.5 - 9.5	3.4	50	630	1389	260	10.2	663	26.1	8.0	10.2	314	2022	* * *	O
	245/30 ZR20 XL 90Y	8.5	8.0 - 9.0	3.4	50	600	1323	248	9.8	657	25.9	8.0	10.2	312	2004	* * *	O
	245/35 ZR20 XL 95Y	8.5	8.0 - 9.5	3.4	50	690	1521	248	9.8	681	26.8	8.0	10.2	321	2077	* * *	O
	245/40 ZR20 XL 99Y	8.5	8.0 - 9.5	3.4	50	775	1709	248	9.8	705	27.8	8.0	10.2	331	2150	* * *	O
	235/30 ZR20 XL 88Y	8.5	8.5 - 8.5	3.4	50	560	1235	241	9.5	651	25.6	8.0	10.2	310	1986	* * *	O
	225/35 ZR20 XL 90Y	8.0	7.5 - 9.0	3.4	50	600	1323	230	9.1	667	26.3	8.0	10.2	316	2034	* * *	O
19"	* 295/35 ZR19 XL 104Y	9.5	9.0 - 10.0	3.4	50	710	1565	278	10.9	649	25.6	8.0	10.1	306	1979	* * *	*
	275/40 ZR19 XL 105Y	9.5	9.0 - 11.0	3.4	50	925	2039	278	10.9	704	27.7	8.0	10.2	328	2147	* * *	O
	255/35 ZR19 XL 96Y	9.0	8.5 - 10.0	3.4	50	710	1565	260	10.2	662	26.1	8.0	10.2	311	2019	* * *	O
	245/30 ZR19 XL 89Y	8.5	8.0 - 9.0	3.4	50	580	1279	248	9.8	632	24.9	8.0	10.2	300	1928	* * *	O
	* 245/40 ZR19 XL 98Y	8.0	7.5 - 9.0	3.4	50	560	1235	230	9.1	641	25.2	8.0	10.1	303	1955	* * *	*
	245/45 ZR19 XL 102Y	8.0	7.5 - 9.0	3.4	50	850	1874	243	9.6	704	27.7	8.0	10.2	328	2147	* * *	O
	235/40 ZR19 XL 96Y	8.5	8.0 - 9.5	3.4	50	710	1565	241	9.5	672	26.5	8.0	10.2	315	2050	* * *	O
	* 225/35 ZR19 XL 88Y	8.5	8.0 - 9.5	3.4	50	750	1653	248	9.8	679	26.7	8.0	10.1	318	2071	* * *	*
	* 225/40 ZR19 XL 93Y	8.0	7.5 - 9.0	3.4	50	650	1433	230	9.1	663	26.1	8.0	10.1	312	2022	* * *	*
225/45 ZR19 XL 96Y	7.5	7.0 - 8.5	3.4	50	710	1565	225	8.9	686	27.0	8.0	10.2	321	2092	* * *	O	
18"	255/35 ZR18 XL 94Y	9.0	8.5 - 10.0	3.4	50	670	1477	260	10.2	636	25.0	8.0	10.2	298	1940	* * *	O
	255/40 ZR18 XL 99Y	9.0	8.5 - 10.0	3.4	50	775	1709	260	10.2	662	26.1	8.0	10.2	308	2019	* * *	O
	255/45 ZR18 XL 103Y	8.5	8.0 - 9.5	3.4	50	875	1929	255	10.0	688	27.1	8.0	10.2	319	2098	* * *	O
	245/35 ZR18 XL 92Y	8.5	8.0 - 9.5	3.4	50	630	1389	248	9.8	630	24.8	8.0	10.2	296	1922	* * *	O
	245/40 ZR18 XL 97Y	8.5	8.0 - 9.5	3.4	50	730	1609	248	9.8	654	25.7	8.0	10.2	305	1995	* * *	O
	245/45 ZR18 XL 100Y	8.0	7.5 - 9.0	3.4	50	800	1764	243	9.6	678	26.7	8.0	10.2	315	2068	* * *	O
	245/50 ZR18 100Y	7.5	7.0 - 8.5	3.5	51	800	1764	249	9.8	704	27.7	8.0	10.2	325	2147	* * *	O
	235/40 ZR18 XL 95Y	8.5	8.0 - 9.5	3.4	50	690	1521	241	9.5	646	25.4	8.0	10.2	302	1970	* * *	O
	235/45 ZR18 XL 98Y	8.0	7.5 - 9.0	3.4	50	750	1653	236	9.3	670	26.4	8.0	10.2	312	2044	* * *	O
	* 235/50 ZR18 XL 101Y	9.0	8.5 - 10.5	3.5	51	875	1929	273	10.7	705	27.8	8.0	10.1	325	2150	* * *	*
	225/35 ZR18 XL 87Y	8.0	7.5 - 9.0	3.4	50	545	1202	230	9.1	616	24.3	8.0	10.2	291	1879	* * *	O
	225/40 ZR18 XL 92Y	8.0	7.5 - 9.0	3.4	50	630	1389	230	9.1	638	25.1	8.0	10.2	299	1946	* * *	O
	225/45 ZR18 XL 95Y	7.5	7.0 - 8.5	3.4	50	690	1521	225	8.9	660	26.0	8.0	10.2	308	2013	* * *	O
	* 215/40 ZR18 XL 89Y	7.0	7.0 - 8.0	3.4	50	650	1433	213	8.4	651	25.6	8.0	10.1	304	1986	* * *	*
* 215/45 ZR18 XL 93Y	7.5	6.5 - 8.5	3.4	50	825	1819	245	9.6	693	27.3	8.0	10.1	321	2114	* * *	*	
17"	245/40 ZR17 XL 95Y	8.5	8.0 - 9.5	3.4	50	690	1521	248	9.8	629	24.8	8.0	10.2	293	1918	* * *	O
	245/45 ZR17 XL 99Y	8.0	7.5 - 9.0	3.4	50	775	1709	243	9.6	653	25.7	8.0	10.2	302	1992	* * *	O
	235/45 ZR17 XL 97Y	8.0	7.5 - 9.0	3.4	50	730	1609	236	9.3	645	25.4	8.0	10.2	299	1967	* * *	O
	235/45 ZR17 94Y	8.0	7.5 - 9.0	3.5	51	670	1477	236	9.3	645	25.4	8.0	10.2	299	1967	* * *	O
	225/45 ZR17 91Y	7.5	7.0 - 8.5	3.5	51	615	1356	225	8.9	635	25.0	8.0	10.2	295	1937	* * *	O
	225/45 ZR17 XL 94Y	7.5	7.0 - 8.5	3.4	50	670	1477	225	8.9	635	25.0	8.0	10.2	295	1937	* * *	O
	225/50 ZR17 XL 98Y	7.0	6.0 - 8.0	3.4	50	750	1653	228	9.0	659	25.9	8.0	10.2	305	2010	* * *	O
	* 225/55 ZR17 97Y	7.5	7.0 - 8.5	3.4	50	545	1202	218	8.6	604	23.8	8.0	10.1	283	1842	* * *	*
	215/45 ZR17 XL 91Y	7.0	7.0 - 8.0	3.4	50	615	1356	213	8.4	627	24.7	8.0	10.2	292	1912	* * *	O
	205/40 ZR17 XL 84Y	7.5	7.0 - 8.0	3.4	50	500	1102	212	8.3	597	23.5	8.0	10.2	280	1821	* * *	O
	205/45 ZR17 XL 88Y	7.0	6.5 - 7.5	3.4	50	560	1235	206	8.1	617	24.3	8.0	10.2	288	1882	* * *	O
205/50 ZR17 XL 93Y	6.5	5.5 - 7.5	3.4	50	650	1433	214	8.4	639	25.2	8.0	10.2	297	1949	* * *	O	

XL : Extra Load

* Available at the 3rd Quarter of 2017



PS71 Run-flat

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector		
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"					mm	mm
Black Sidewall																			
19"	* 245/40 ZR19 XL 98Y	8.5	8.0 - 9.5	3.4	50	750	1653	248	9.8	679	26.7	*	*	318	2071	*	*	*	*
18"	* 245/40 ZR18 93Y	8.5	8.0 - 9.5	3.5	51	650	1433	248	9.8	653	25.7	*	*	305	1992	*	*	*	*
	* 245/45 ZR18 96Y	8.0	7.5 - 9.0	3.5	51	560	1235	230	9.1	637	25.1	*	*	299	1943	*	*	*	*
	* 245/50 ZR18 100Y	8.0	7.5 - 9.0	3.5	51	710	1565	243	9.6	677	26.7	*	*	314	2065	*	*	*	*
	* 235/50 R18 97V	7.5	7.0 - 8.5	3.5	51	615	1356	225	8.9	659	25.9	*	*	307	2010	*	*	*	*
	* 225/40 ZR18 88Y	7.5	7.0 - 8.5	3.5	51	800	1764	253	10.0	703	27.7	*	*	324	2144	*	*	*	*
	* 225/45 ZR18 91Y	7.5	6.5 - 8.5	3.5	51	730	1609	245	9.6	693	27.3	*	*	321	2114	*	*	*	*
17"	* 255/40 ZR17 94W	9.0	8.5 - 10.0	3.5	51	670	1477	260	10.2	636	25.0	*	*	296	1940	*	*	*	*
	* 225/45 ZR17 91W	7.5	7.0 - 8.5	3.5	51	615	1356	225	8.9	634	25.0	*	*	295	1934	*	*	*	*
	* 225/50 ZR17 94W	7.0	6.5 - 7.5	3.5	51	500	1102	206	8.1	616	24.3	*	*	288	1879	*	*	*	*
	* 225/55 ZR17 97Y	7.0	6.0 - 8.0	3.5	51	670	1477	233	9.2	659	25.9	*	*	305	2010	*	*	*	*
	* 205/45 R17 84V	6.5	5.5 - 7.5	3.4	50	650	1433	214	8.4	638	25.1	*	*	296	1946	*	*	*	*
	* 205/50 ZR17 XL 93W	7.0	6.0 - 8.5	3.5	51	730	1609	233	9.2	680	26.8	*	*	313	2074	*	*	*	*

XL : Extra Load

* Available at the 3rd Quarter of 2017