

Medida	IC/RV	Uso	Capas	Tipo de Pared	Rin Recomendado	Presión de aire Máx.		Carga Máxima		Diámetro Exterior		Ancho de Sección		Ancho de Banda		Profundidad		Radio Estático de Carga	RPM	Circunferencia de Rodado
						psi	kg	lb	mm	pulg	mm	pulg	mm	pulg	mm	pulg (32")				

80

185/80R17T	93T	-	04	DSB	5.00	44	650	1433	566	22.3	180	7.1	126	5.0	7.9	9.9	-	-	-
------------	-----	---	----	-----	------	----	-----	------	-----	------	-----	-----	-----	-----	-----	-----	---	---	---

70

175/70R13H	82H	-	04	DSB	5.00	44	475	1047	574	22.6	179	7.0	126	5.0	8.1	10.1	260	919	1751
175/70R14H	84H	-	04	DSB	5.00	44	500	1102	599	23.6	179	7.0	126	5.0	8.1	10.1	272	880	1828
175/70R14T	84T	CD	04	DSB	5.00	51	500	1102	599	23.6	179	7.0	126	5.0	8.1	10.1	272	880	1828
185/70R13H	86H	I	04	DSB	5.50	44	530	1168	587	23.1	191	7.5	134	5.3	8.2	10.3	265	899	1790
185/70R14H	88H	-	04	DSB	5.50	44	560	1235	612	24.1	192	7.6	134	5.3	8.2	10.3	277	861	1867
195/70R14H	91H	-	04	DSB	6.00	44	615	1356	627	24.7	203	8.0	140	5.5	8.3	10.4	283	841	1913
205/70R14H	95H	-	04	DSB	6.00	44	690	1521	640	25.2	208	8.2	148	5.8	8.2	10.3	288	824	1953
215/70R16H	100H	I	04	DSB	6.50	51	800	1764	706	27.8	218	8.6	166	6.5	7.9	9.9	320	747	2153

65

145/65R15H	72H	-	04	DSB	4.50	44	355	783	566	22.3	164	6.5	110	4.3	7.4	9.3	262	932	1725
165/65R15H	81H	-	04	DSB	5.00	44	462	1019	590	23.2	176	6.9	120	4.7	7.5	9.4	271	895	1798
175/65R14H	82H	-	04	DSB	5.00	44	475	1047	580	22.9	182	7.2	134	5.3	8.3	10.4	265	909	1770
175/65R14T	82T	CJ	04	DSB	5.00	44	475	1047	584	23.0	192	7.6	134	5.3	7.6	9.5	266	903	1781
175/65R15H	84H	-	04	DSB	5.00	44	500	1102	605	23.8	182	7.2	134	5.3	7.7	9.7	277	872	1844
185/65R14H	86H	-	04	DSB	5.50	44	530	1168	592	23.3	194	7.6	140	5.5	8.3	10.4	270	891	1806
185/65R14T	86T	CD	04	DSB	5.50	51	530	1168	597	23.5	200	7.9	140	5.5	8.1	10.1	271	884	1820
185/65R15H	88H	H	04	DSB	5.50	44	560	1235	617	24.3	195	7.7	136	5.4	7.8	9.8	282	855	1881
195/65R14H	89H	-	04	DSB	6.00	44	580	1279	607	23.9	206	8.1	148	5.8	8.2	10.3	276	868	1852
195/65R15H	91H	H	04	DSB	6.00	51	615	1356	633	24.9	207	8.1	148	5.8	7.8	9.8	288	833	1930
195/65R15T	91T	K	04	ASB	6.00	51	615	1356	633	24.9	207	8.1	148	5.8	7.4	9.3	288	833	1930
195/65R15T XL	95T	X	04	DSB	6.00	50	690	1521	633	24.9	207	8.1	148	5.8	7.8	9.8	288	833	1930
195/65R15V	91V	-	04	DSB	6.00	51	615	1356	635	25.0	204	8.0	152	6.0	7.8	9.8	289	831	1936
205/65R15H	94H	I	04	DSB	6.00	44	670	1477	643	25.3	212	8.3	152	6.0	8.0	10.0	292	821	1960
205/65R15H XL	99H	-	04	DSB	6.00	50	775	1709	643	25.3	214	8.4	156	6.1	8.3	10.4	292	821	1960
205/65R15V	94V	-	04	RSB	6.50	44	670	1477	643	25.3	212	8.3	152	6.0	8.0	10.0	292	821	1960
205/65R16H	99H	H	04	RSB	6.50	44	670	1477	643	25.3	212	8.3	152	6.0	8.0	10.0	292	821	1960
205/65R16H XL	99H	I-	04	DSB	6.00	50	775	1709	669	26.3	215	8.5	172	6.8	8.7	11.0	305	788	2041
205/65R16T	95T	CR	04	DSB	5.50	44	690	1521	667	26.3	212	8.3	150	5.9	8.1	10.1	304	791	2033
205/65R16V	95V	C-	04	SBL	5.50	44	690	1521	667	26.3	212	8.3	150	5.9	8.1	10.1	304	791	2033
215/65R15H	96H	-	04	DSB	6.50	44	710	1565	659	25.9	226	8.9	164	6.5	8.3	10.5	298	801	2009
215/65R16H	98H	CJ	04	DSB	6.50	44	750	1653	681	26.8	232	9.1	158	6.2	8.1	10.1	310	775	2076
215/65R16S	98S	CJ	04	DSB	6.50	44	750	1653	681	26.8	232	9.1	158	6.2	8.1	10.1	310	775	2076
215/65R16T	98T	CJ	04	DSB	6.50	44	750	1653	683	26.9	232	9.1	158	6.2	8.1	10.1	310	772	2082
215/65R16V	98V	H	04	DSB	6.50	44	750	1653	679	26.7	229	9.0	158	6.2	7.8	9.8	309	776	2072
225/65R17H	102H	I-	04	DSB	6.50	51	850	1874	721	28.4	238	9.4	180	7.1	9.0	11.4	328	731	2199
235/65R17H	104H	I-	04	DSB	7.00	51	900	1984	736	29.0	242	9.5	176	6.9	8.5	10.8	334	716	2245
235/65R17W	104W	CD	04	DSB	7.00	51	900	1984	736	29.0	242	9.5	176	6.9	8.5	10.8	334	716	2245

60

165/60R14H	75H	-	04	DSB	5.00	44	387	853	548	21.6	177	7.0	120	4.7	7.5	9.4	252	962	1672
175/60R14H	79H	-	04	DSB	5.00	44	437	963	565	22.3	189	7.4	132	5.2	7.3	9.2	259	933	1724
175/60R15H	81H	-	04	DSB	5.00	51	462	1019	588	23.1	189	7.4	130	5.1	7.6	9.5	271	898	1792
175/60R16H	82H	-	04	DSB	5.00	51	475	1047	613	24.1	189	7.4	140	5.5	7.2	9.0	283	860	1870
185/60R14H	82H	-	04	SBL	5.50	44	475	1047	575	22.7	194	7.6	140	5.5	8.4	10.6	263	917	1754
185/60R15H	84H	I	04	DSB	5.50	44	500	1102	596	23.5	201	7.9	136	5.4	7.8	9.8	274	885	1817
185/60R15H XL	88H	-	04	DSB	6.00	50	560	1235	605	23.8	197	7.8	150	5.9	8.4	10.6	277	872	1845
185/60R15T	84T	CG	04	DSB	6.00	51	500	1102	602	23.7	195	7.7	140	5.5	8.1	10.1	276	876	1836
185/60R15V	84V	-	04	SBL	5.50	51	500	1102	602	23.7	195	7.7	140	5.5	8.1	10.1	276	876	1836
195/60R14H	86H	-	04	DSB	6.00	51	530	1168	588	23.2	207	8.1	152	6.0	8.1	10.1	268	897	1794

Medida	IC/RV	Uso	Capas	Tipo de Pared	Rin Recomendado	Presión de aire Máx.		Carga Máxima		Diámetro Exterior		Ancho de Sección		Ancho de Banda		Profundidad		Radio Estático de Carga	RPM	Circunferencia de Rodado
						psi	kg	lb	mm	pulg	mm	pulg	mm	pulg	mm	pulg (32")				

60

195/60R15H	88H	-	04	DSB	6.00	44	560	1235	612	24.1	207	8.1	148	5.8	8.2	10.3	280	862	1865
195/60R15V	88V	-	04	SBL	6.00	44	560	1235	612	24.1	207	8.1	148	5.8	8.2	10.3	280	862	1865
195/60R16H	89H	CD	04	DSB	6.00	51	580	1279	637	25.1	207	8.2	152	6.0	7.8	9.8	293	828	1943
205/60R15H	91H	-	04	DSB	6.00	44	615	1356	623	24.5	215	8.5	156	6.1	8.3	10.4	284	847	1899
205/60R15V	91V	-	04	SBL	6.00	44	615	1356	623	24.5	215	8.5	156	6.1	8.3	10.4	284	847	1899
205/60R16H	92H	I	04	DSB	6.50	44	630	1389	647	25.5	222	8.7	154	6.1	8.0	10.0	297	815	1973
205/60R16H XL	96H	E	04	VSBL	6.00	50	710	1565	649	25.6	214	8.4	164	6.5	8.0	10.0	297	812	1980
205/60R16V	92V	I	04	RSB	6.50	44	630	1389	647	25.5	220	8.7	154	6.1	8.0	10.0	297	815	1973
215/60R15V	94V	-	04	DSB	6.50	51	670	1477	636	25.0	236	9.3	172	6.8	9.0	11.4	289	829	1939
215/60R16H	95H	CD	04	DSB	6.50	51	690	1521	665	26.2	224	8.8	166	6.5	7.7	9.7	304	793	2028
215/60R16T	95T	V	04	VSBL	6.50	51	690	1521	665	26.2	224	8.8	166	6.5	7.7	9.7	304	793	2028
215/60R16V	95V	-	04	DSB	6.50	51	690	1521	665	26.2	224	8.8	166	6.5	7.7	9.7	304	793	2028
215/60R16V XL	99V	-	04	DSB	6.50	50	775	1709	660	26.0	226	8.9	164	6.5	8.3	10.5	302	799	2013
215/60R17H	96H	-	04	DSB	6.50	51	71	1565	687	27.1	231	9.1	172	6.8	8.0	10.0	315	768	2095
225/60R15V	96V	-	04	DSB	6.50	44	710	1565	649	25.5	234	9.2	170	6.7	8.3	10.5	294	813	1978
225/60R16S	98S	CP	04	SBL	6.50	44	750	1653	673	26.5	234	9.2	170	6.7	8.3	10.5	307	783	2053
225/60R16V	98V	K	04	DSB	6.50	44	750	1653	673	26.5	234	9.2	170	6.7	8.3	10.5	307	783	2053
225/60R16W	98W	-	04	VSBL	6.50	44	750	1653	673	26.5	234	9.2	170	6.7	8.3	10.5	307	783	2053
225/60R17H	99H	I	04	RSB	6.50	44	775	1709	700	27.6	235	9.3	170	6.7	8.3	10.4	320	753	2136
225/60R18H	100H	-	04	DSB	6.50	44	800	1764	720	28.3	238	9.4	170	6.7	8.3	10.5	331	733	2195
235/60R16W	100W	-	04	DSB	7.00	44	800	1764	685	27.0	245	9.6	178	7.0	8.3	10.5	311	770	2089

55

165/55R15V	75V	J	04	DSB	5.00	44	387	853	560	22.0	181	7.1	132	5.2	7.4	9.3	260	942	1707
185/55R15H	82H	I	04	DSB	6.00	44	475	1047	581	22.9	191	7.5	120	4.7	7.8	9.8	268	908	1772
185/55R15V	82V	CJ	04	DSB	6.00	44	475	1047	581	22.9	191	7.5	120	4.7	7.8	9.8	268	908	1772
185/55R15V XL	86V	CU	04	DSB	6.00	50	530	1168	583	23.0	197	7.8	144	5.7	7.9	9.9	269	905	1778
185/55R16S	87S	CG	04	DSB	5.00	51	545	1202	605	23.8	190	7.5	138	5.4	3.6	4.5	280	872	1845
195/55R15H	85H	I	04	DSB	6.00	44	515	1135	589	23.2	208	8.2	152	6.0	8.1	10.1	271	896	1795
195/55R15T	85T	CG	04	VSBL	6.00	44	515	1135	590	23.2	212	8.3	148	5.8	7.8	9.8	272	894	1800
195/55R15V	85V	CH	04	VSBL	6.00	44	515	1135	590	23.2	212	8.3	148	5.8	7.8	9.8	272	894	1800
195/55R16H	87H	-	04	DSB	6.00	51	545	1201	616	24.3	213	8.4	156	6.1	8.0	10.0	284	856	1878
195/55R16V	87V	CU	04	VSBL	6.00	51	545	1201	616	24.3	213	8.4	156	6.1	8.0	10.0	284	856	1878
205/55R15V	88V	I	04	DSB	6.50	51	560	1235	604	23.8	224	8.8	170	6.7	8.2	10.3	277	874	1841
205/55R16H	91H	H	04	DSB	6.00	44	615	1356	632	24.9	221	8.7	160	6.3	7.8	9.8	291	835	1927
205/55R16H XL	94H	T	04	DSB	6.00	50	670	1477	630	24.8	216	8.5	168	6.6	7.8	9.8	290	837	1922
205/55R16V	91V	V	04	DSB	6.50	51	615	1356	628	24.7	224	8.8	164	6.5	7.8	9.8	289	840	1915
215/55R16H	93H	F	04	DSB	7.00	51	650	1433	638	25.1	231	9.1	171	6.7	8.0	10.0	293	827	1946
215/55R16H XL	97H	-	04	DSB	7.00	50	730	1609	638	25.1	231	9.1	172	6.8	8.0	10.0	293	827	1946
215/55R16V	93V	F	04	ASB	7.00	51	650	1433	638	25.1	225	8.9	180	7.1	8.1	10.1	293	827	1945
215/55R17V	94V	H	04	DSB	7.00	44	670	1477	660	26.0	235	9.2	170	6.7	7.8	9.8	305	799	2014
215/55R17W	94W	J	04	DSB	7.00	51	670	1477	668	26.3	238	9.4	172	6.8	7.7	9.7	308	790	2037
225/55R16H	95H	-	04	DSB	7.00	51	690	1521	650	25.6	245	9.6	179	7.0	8.0	10.0	298	811	1983
225/55R17V	97V	H	04	DSB	6.50	44	730	1609	682	26.8	238	9.4	170	6.7	7.8	9.8	313	774	2078
225/55R18H	98H	I	04	VSBL	6.50	44	750	1653	699	27.5	236	9.3	170	6.7	8.3	10.4	322	754	2132
235/55R17V	99V	K	04	DSB	7.50	51	775	1709	686	27.0	253	10.0	187	7.4	8.0	10.0	315	769	2092
235/55R18H	100H	I	04	DSB	7.00	44	800	1764	708	27.9	248	9.8	180	7.1	8.3	10.4	326	745	2160
235/55R18V XL	104V	I-	04	DSB	7.50	50	900	1984	712	28.0	253	10.0	188	7.4	8.0	10.0	327	741	2170

50

165/50R16V	73V	-	04	DSB	5.00	44	365	805	571	22.5	177	7.0	132	5.2	8.0	10.0	-	-	-
175/50R15H	75H	CH	04	DSB	5.50	44	387	853	550	21.6	194	7.6	146	5.7	7.3	9.2	256	960	1676
195/50R16H	84H	H	04	DSB	5.50	44	500	1102	600	23.6	213	8.4	150	5.9	7.8	9.8	278	879	1830

Medida	IC/RV	Uso	Capas	Tipo de Pared	Rin Recomendado	Presión de aire Máx.		Carga Máxima		Diámetro Exterior		Ancho de Sección		Ancho de Banda		Profundidad		Radio Estático de Carga	RPM	Circunferencia de Rodado
						psi	kg	lb	mm	pulg	mm	pulg	mm	pulg	mm	pulg (32")				

50

195/50R16V	84V	CU	04	DSB	5.50	44	500	1102	600	23.6	213	8.4	150	5.9	7.8	9.8	278	879	1830
195/50R16V XL	88V	CU	04	DSB	6.00	50	560	1235	599	23.6	204	8.0	156	6.1	7.9	9.9	278	880	1827
205/50R16V	87V	-	04	DSB	6.50	51	545	1201	608	23.9	226	8.9	164	6.5	8.0	10.0	281	867	1855
205/50R17W XL	93W	CR	04	DSB	6.00	50	650	1433	634	25.0	224	8.8	164	6.5	8.0	10.0	294	832	1934
215/50R17H	91H	K	04	SBL	7.00	44	615	1356	644	25.4	238	9.4	171	6.7	8.0	10.0	298	819	1964
215/50R17V	91V	-	04	DSB	7.00	44	615	1356	644	25.4	238	9.4	171	6.7	8.0	10.0	298	819	1964
215/50R17W	91W	F	04	VSB	7.00	51	615	1356	644	25.4	238	9.4	171	6.7	8.0	10.0	298	819	1964
225/50R16V	92V	-	04	DSB	7.00	51	630	1389	628	24.7	247	9.7	179	7.0	8.0	10.0	289	839	1916
225/50R17H	94H	CD	04	DSB	7.00	51	670	1477	657	25.9	248	9.8	186	7.3	8.0	10.0	303	803	2003
225/50R17V	94V	-	04	SBL	7.00	51	670	1477	654	25.8	247	9.7	179	7.0	8.0	10.0	302	806	1995
225/50R17W XL	98W	S	04	DSB	7.00	60	750	1653	654	25.8	247	9.7	189	7.4	8.0	10.0	302	806	1995
235/50R18V	97V	H	04	DSB	7.50	44	730	1609	684	26.9	254	10.0	186	7.3	7.8	9.8	316	772	2084
235/50R19H	99H	G	04	VSB	7.00	44	775	1709	718	28.3	245	9.6	212	8.3	8.2	10.3	333	735	2189
245/50R18V	100V	H	04	DSB	7.50	44	800	1764	690	27.1	270	10.6	194	7.6	7.8	9.8	319	765	2103

45

205/45R16H	83H	CD	04	DSB	7.00	51	487	1074	586	23.1	214	8.4	172	6.8	7.8	9.8	273	900	1787
205/45R16H XL	87H	CD	04	DSB	7.00	50	545	1201	587	23.1	218	8.6	168	6.6	7.8	9.8	273	899	1790
205/45R16V	83V	K	04	DSB	7.00	51	487	1074	586	23.1	214	8.4	172	6.8	7.8	9.8	273	900	1787
205/45R16W	83W	V	04	VSB	7.00	51	487	1074	586	23.1	214	8.4	172	6.8	7.8	9.8	273	900	1787
215/45R16H	86H	CD	04	DSB	7.00	51	530	1168	599	23.6	227	8.9	180	7.1	7.8	9.8	278	881	1826
215/45ZR17W XL	91W	H	04	DSB	7.00	50	615	1356	620	24.4	222	8.7	182	7.2	8.0	10.0	289	851	1891
225/45R17V	91V	H	04	DSB	7.00	44	615	1356	629	24.8	234	9.2	180	7.1	7.8	9.8	292	839	1917
225/45R17V XL	94V	E	04	DSB	7.50	50	670	1477	630	24.8	233	9.2	189	7.4	8.0	10.0	293	837	1922
225/45R18V	91V	K	04	DSB	7.00	44	615	1356	654	25.7	233	9.2	180	7.1	8.0	10.0	305	807	1994
225/45R18V XL	95V	H	04	DSB	8.00	50	690	1521	650	25.6	250	9.8	190	7.5	7.8	9.8	303	812	1981
225/45R18W	91W	J	04	DSB	7.00	44	615	1356	654	25.7	233	9.2	180	7.1	8.0	10.0	305	807	1994
235/45R18W XL	95W	S	04	DSB	8.00	50	690	1521	650	25.6	250	9.8	190	7.5	7.8	9.8	303	812	1981

40

205/40R17V	80V	H	04	DSB	7.50	50	450	992	593	23.3	221	8.7	172	6.8	7.6	9.5	278	890	1808
205/40R17V XL	84V	I	04	DSB	7.50	50	500	1102	593	23.3	221	8.7	172	6.8	7.6	9.5	278	890	1808
225/40R18 XL	92V	H	04	VSB	8.00	50	630	1389	637	25.1	242	9.5	193	7.6	8.5	10.8	298	828	1942