

KC53

Rim	Tire Size	Ply Rating	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	
					bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"			mm
Black Sidewall																	
16"	235/65 R16C	S 115R	08	7.0	6.5 - 7.5	4.8	69	1215	2679	240	9.4	712	28.0	9.5	12.0	322	2172
		D 113						1150	2535								
	235/65 R16C	S 121R	10	7.0	6.5 - 7.5	5.7	83	1450	3195	240	9.4	712	28.0	10.0	12.6	322	2172
		D 119						1360	3000								
	225/65 R16C	S 112R	08	6.5	6.0 - 7.0	4.8	69	1120	2470	228	9.0	698	27.5	10.0	12.6	317	2129
		D 110						1060	2335								
	225/75 R16C	S 121R	10	6.0	6.0 - 7.0	5.7	83	1450	3195	223	8.8	744	29.3	10.0	12.6	335	2269
		D 120						1400	3085								
	215/60 R16C	S 103T	06	6.5	6.0 - 7.0	3.7	54	875	1929	221	8.7	664	26.1	9.0	11.3	304	2025
		D 101						825	1819								
	215/65 R16C	S 109T	08	6.5	6.0 - 7.0	4.8	69	1030	2271	221	8.7	686	27.0	9.7	12.2	312	2092
		D 107						975	2150								
	215/70 R16C	S 108T	06	6.5	5.5 - 7.0	3.8	55	1000	2205	221	8.7	708	27.9	9.2	11.6	321	2159
		D 106						950	2094								
	215/70 R16C	S 108T	08	6.5	5.5 - 7.0	3.8	55	1000	2205	221	8.7	708	27.9	9.2	11.6	321	2159
		D 106T						950	2094								
	215/75 R16C	S 113R	08	6.0	5.5 - 7.0	4.8	69	1150	2535	216	8.5	728	28.7	10.7	13.5	329	2220
		D 111						1090	2403								
	215/75 R16C	S 116R	10	6.0	5.5 - 7.0	5.2	76	1250	2756	216	8.5	728	28.7	10.7	13.5	329	2220
		D 114						1180	2601								
	205/65 R16C	S 107T	08	6.0	5.5 - 6.5	4.8	69	975	2150	209	8.2	672	26.5	10.0	12.6	307	2050
		D 105						925	2040								
	205/75 R16C	S 110R	08	5.5	5.5 - 6.5	4.8	69	1060	2335	203	8.0	714	28.1	10.0	12.6	323	2178
		D 108						1000	2205								
	195/60 R16C	S 99H	06	6.0	5.5 - 6.5	3.7	54	775	1709	201	7.9	640	25.2	9.0	11.3	294	1952
		D 97						730	1609								
	195/65 R16C	S 104T	08	6.0	5.5 - 6.0	4.8	69	900	1985	201	7.9	660	26.0	9.7	12.2	302	2013
		D 102						850	1875								
195/75 R16C	S 107T	08	5.5	5.0 - 6.0	4.8	69	975	2150	196	7.7	698	27.5	9.7	12.2	317	2129	
	D 105						925	2040									
195/75 R16C	S 110R	10	5.5	5.0 - 6.0	5.8	84	1060	2337	196	7.7	698	27.5	9.7	12.2	317	2129	
	D 108						1000	2205									
15"	225/70 R15C	S 112R	08	6.5	6.0 - 7.0	4.5	65	1120	2469	228	9.0	697	27.4	10.2	12.9	314	2126
		D 110						1060	2337								
	225/70 R15C	S 106Q	08	6.5	6.0 - 7.0	4.5	65	950	2094	228	9.0	697	27.4	10.5	13.2	314	2126
		D 103						875	1929								
	225/70 R15C	S 116R	10	6.5	6.0 - 7.0	5.5	80	1250	2756	228	9.0	697	27.4	10.5	13.2	314	2126
		D 114						1180	2601								
	215/65 R15C	S 104R	06	6.5	6.0 - 7.0	3.7	54	900	1984	221	8.7	661	26.0	8.7	11.0	300	2016
		D 102						850	1874								
	215/70 R15C	S 109T	08	6.5	5.5 - 7.0	4.5	65	1030	2271	221	8.7	683	26.9	9.7	12.2	308	2083
		D 107						975	2150								
	215/70 R15C	S 104S	08	6.5	6.0 - 7.0	4.5	65	900	1985	221	8.7	683	26.9	10.0	12.6	308	2083
		D 101						825	1820								
	205/65 R15C	S 102T	06	6.0	5.5 - 6.5	3.7	54	850	1874	209	8.2	647	25.5	9.0	11.3	294	1973
		D 100						800	1764								
205/70 R15C	S 104S	06	6.0	5.5 - 6.5	3.8	55	900	1985	209	8.2	669	26.3	9.7	12.2	303	2040	
	D 102						850	1875									



KC53

Rim	Tire Size	Ply Rating	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	
					bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"			mm
Black Sidewall																	
15"	205/70 R15C	S 106R	08	6.0	5.5 - 6.5	4.5	65	950	2095	209	8.2	669	26.3	9.7	12.2	303	2040
		D 104						900	1985								
	195 R15C	S 106R	08	5.5	5.0 - 6.0	4.5	65	950	2094	196	7.7	693	27.3	9.7	12.2	312	2114
		D 104						900	1984								
	195/70 R15C	S 100R	06	6.0	5.0 - 6.0	3.8	55	800	1764	201	7.9	655	25.8	9.7	12.2	297	1998
		D 98						750	1653								
	195/70 R15C	S 104R	08	6.0	5.0 - 6.0	4.5	65	900	1985	201	7.9	655	25.8	9.7	12.2	297	1998
		D 102						850	1875								
195/80 R15 LT	S 107R	08	5.5	5.0 - 6.0	4.5	65	975	2150	196	7.7	693	27.3	9.7	12.2	312	2114	
	D 105						925	2040									
14"	215 R14C	S 112Q	08	6.0	5.5 - 7.0	4.5	65	1120	2469	218	8.6	700	27.6	10.0	12.2	307	2092
		D 110						1060	2337								
	205 R14C	S 109Q	08	6.0	5.5 - 6.5	4.5	65	1030	2271	208	8.2	686	27.0	9.7	12.2	307	2092
		D 107						975	2150								
	195 R14C	S 102R	06	5.5	5.0 - 6.0	3.8	55	850	1874	198	7.8	666	26.2	9.7	12.2	299	2031
		D 100						800	1764								
	195 R14C	S 106R	08	5.5	5.0 - 6.0	4.5	65	950	2095	198	7.8	666	26.2	9.7	12.2	299	2031
		D 104						900	1985								
	195/75 R14C	S 106R	08	5.5	5.0 - 6.0	4.8	69	950	2094	196	7.7	648	25.5	10.0	12.6	292	1976
		D 104						900	1984								
	185 R14C	S 99R	06	5.5	5.0 - 6.0	3.8	55	775	1709	188	7.4	650	25.6	9.7	12.2	293	1983
		D 97						730	1609								
	185 R14C	S 102R	08	5.0	5.0 - 6.0	4.5	65	850	1875	188	7.4	650	25.6	9.7	12.2	293	1983
		D 100						800	1765								
	185 R14C	S 102Q	08	5.5	5.0 - 6.0	4.5	65	850	1875	188	7.4	653	25.7	9.5	12.0	294	1992
		D 100						800	1765								
	185/75 R14C	S 102R	08	5.0	5.0 - 6.0	4.8	69	850	1874	184	7.2	634	25.0	10.0	12.6	286	1934
		D 100						800	1764								
	175/65 R14C	S 90T	06	5.0	5.0 - 5.5	3.7	54	600	1323	177	7.0	584	23.0	9.0	11.3	267	1781
		D 88						560	1235								
165/70 R14C	S 89R	06	5.0	4.5 - 5.0	3.7	54	580	1279	170	6.7	588	23.1	9.0	11.3	268	1793	
	D 87						545	1201									
155/80 R14LT	S 88N	06	5.0	4.0 - 5.0	3.5	51	560	1235	156	6.1	603	23.7	9.0	11.3	274	1839	
	D 86						530	1168									
12"	155 R12C	S 83P	06	4.5	4.0 - 4.5	3.5	51	487	1074	157	6.2	556	21.9	9.0	11.3	250	1696
		D 81						462	1019								

Made in China