

Rim	Tire Size	Ply Rating	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	
					bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"			mm
<b>Black Sidewall</b>																	
<b>16"</b>	<b>215/75 R16C</b>	<b>S 116Q</b>	10	6.0	5.5 - 7.0	5.2	76	1250	2756	216	8.5	728	28.7	12.0	15.1	329	2220
	<b>195/75 R16C</b>	<b>S 110Q</b>	10	5.5	5.0 - 6.0	5.8	84	1060	2337	196	7.7	698	27.5	10.0	12.6	317	2129
<b>195/75 R16C</b>	<b>S 110Q</b>	10	5.5	5.0 - 6.0	5.8	84	1060	2337	196	7.7	698	27.5	10.0	12.6	317	2129	
																	<b>D 108</b>
<b>15"</b>	<b>215/70 R15C</b>	<b>S 109S</b>	08	6.5	5.5 - 7.0	4.5	65	900	1985	221	8.7	683	26.9	10.0	12.6	308	2083
	<b>205/70 R15C</b>	<b>S 104S</b>	06	6.0	5.5 - 6.5	3.8	55	900	1985	209	8.2	669	26.3	8.8	11.1	303	2040
	<b>205/70 R15C</b>	<b>S 106S</b>	08	6.0	5.5 - 6.5	4.5	65	950	2095	209	8.2	669	26.3	8.8	11.1	303	2040
	<b>195 R15C</b>	<b>S 106R</b>	08	5.5	5.0 - 6.0	4.5	65	950	2094	198	7.8	690	27.2	9.5	12.0	311	2105
<b>195/70 R15C</b>	<b>S 104R</b>	08	6.0	5.0 - 6.0	4.5	65	900	1984	201	7.9	655	25.8	9.8	12.3	297	1998	
																	<b>D 102</b>
<b>14"</b>	<b>205 R14C</b>	<b>S 109Q</b>	08	6.0	5.5 - 6.5	4.5	65	1030	2271	208	8.2	686	27.0	10.0	12.6	307	2092
	<b>205/75 R14C</b>	<b>S 109R</b>	08	5.5	5.5 - 6.5	4.8	69	1030	2271	203	8.0	664	26.1	8.8	11.1	301	2012
	<b>195 R14C</b>	<b>S 102R</b>	06	5.5	5.0 - 6.0	3.7	54	850	1874	198	7.8	666	26.2	9.0	11.3	299	2031
<b>195 R14C</b>	<b>S 106R</b>	08	5.5	5.0 - 6.0	4.5	65	950	2094	198	7.8	666	26.2	9.0	11.3	299	2031	
																	<b>D 104</b>
<b>175 R14C</b>	<b>S 99Q</b>	08	5.0	4.5 - 5.0	4.5	65	775	1709	178	7.0	634	25.0	9.1	11.5	286	1934	
																	<b>D 98</b>
<b>13"</b>	<b>175 R13C</b>	<b>S 94P</b>	06	5.0	4.5 - 5.5	3.8	54	670	1477	178	7.0	608	23.9	8.8	11.1	276	1842
	<b>155 R13C</b>	<b>S 90R</b>	08	4.5	4.0 - 5.0	4.5	65	595	1312	157	6.2	578	22.8	8.5	10.7	264	1751
<b>145 R13C</b>	<b>S 88R</b>	08	4.0	4.0 - 5.0	4.5	65	560	1235	144	5.7	564	22.2	8.5	10.7	259	1709	
																	<b>D 86</b>
<b>12"</b>	<b>145 R12C</b>	<b>S 81P</b>	06	4.0	3.5 - 4.0	3.5	51	462	1019	147	5.8	543	21.4	7.8	9.8	245	1656
	<b>155 R12C</b>	<b>S 83P</b>	06	4.5	4.0 - 5.0	3.5	51	487	1074	157	6.2	550	21.7	8.8	11.1	248	1678
	<b>155 R12C</b>	<b>S 83P</b>	06	4.5	4.0 5.0	3.5	51	487	1074	157	6.2	550	21.7	8.8	11.1	248	1678
	<b>155 R12C</b>	<b>S 88P</b>	08	4.5	4.0 5.0	4.5	65	560	1235	157	6.2	550	21.7	8.8	11.1	248	1678
<b>145 R12C</b>	<b>S 81P</b>	06	4.0	3.5 4.0	3.5	51	462	1019	147	5.8	543	21.4	7.8	9.8	245	1656	
																	<b>D 79</b>