



SIZE	Ply Rating	Load Index	Speed	Section Width	Overall Diameter	UTQG	NOTE
85 Series							
LT235/85R16	10PR	120/116	S	235	806	-	
75 Series							
205/75R15	-	99XL	S	203	689	440AA	
235/75R15	-	109XL	S	235	733	440AA	
245/75R16	-	109	S	248	774	440AA	
265/75R16	-	116	S	267	804	440AA	
LT215/75R15	6PR	100/97	S	216	703	-	
LT235/75R15	8PR	110/107	S	235	733	-	
LT245/75R16	10PR	120/116	Q	248	774	-	
LT265/75R16	10PR	123/120	Q	267	804	-	
LT285/75R16	10PR	126/123	R	286	834	-	
LT245/75R17	10PR	121/118	S	248	800	-	
70 Series							
205/70R14	-	98XL	T	209	644	440AA	
265/70R15	-	112	S	272	753	440AA	
215/70R16	-	100	H	221	708	440AA	
235/70R16	-	106	T	240	736	440AA	
245/70R16	-	111XL	S	248	750	440AA	
255/70R16	-	111	S	260	764	440AA	
265/70R16	-	112	S	272	778	440AA	
265/70R18	-	116	H	272	829	440AA	
LT255/70R15	8PR	113/110	S	260	739	-	
LT265/70R17	10PR	121/118	S	272	804	-	
LT285/70R17	10PR	121/118	S	292	832	-	
LT315/70R17	10PR	121/118	Q	323	874	-	
LT285/70R18	10PR	127/124	Q	-	-	-	

SIZE	Ply Rating	Load Index	Speed	Section Width	Overall Diameter	UTQG	NOTE
65 Series							
235/65R17	-	108XL	H	240	738	440AA	
245/65R17	-	107	H	248	750	440AA	
265/65R17	-	112	H	272	776	440AA	
275/65R17	-	115	H	279	790	440AA	
60 Series							
205/60R15	-	95XL	H	209	627	440AA	
275/60R17	-	110	H	279	762	440AA	
285/60R18	-	120XL	H	292	799	440AA	
275/60R20	-	115	H	279	838	440AA	
50 Series							
265/50R20	-	111XL	H	277	774	440AA	
31×10.50R15LT	6PR	109	Q	268	775	-	
30×9.50R15LT	6PR	104	Q	240	750	-	