

AT51

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector			
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"					mm	mm	
Black Sidewall																				
20"	* LT 305/55 R20	10 S	121R	9.5	8.5 - 11.0	5.6	80	1450	3197	316	12.4	884	34.8	12.4	15.6	401	2696	- - - *		
		D	118					1320	2910											
	LT 285/55 R20	10 S	122R	9.0	8.0 - 10.0	5.6	80	1500	3305	297	11.7	822	32.4	12.4	15.6	376	2507	- - - -		
		D	119					1360	3000											
	P 275/55 R20		111T	8.5	7.5 - 9.5	3.6	51	1090	2403	284	11.2	810	31.9	10.4	13.1	372	2471	540 A A -		
	P 275/60 R20		114T	8.0	7.5 - 9.5	3.6	51	1180	2601	279	11.0	838	33.0	10.4	13.1	383	2556	540 A A -		
20"	LT 275/65 R20	10 S	126R	8.0	7.5 - 9.5	5.6	80	1700	3750	279	11.0	866	34.1	12.4	15.6	394	2641	- - - -		
		D	123					1550	3415											
	* 35X12.5 R20LT 10		121R	10.0	8.5 - 11.0	5.6	80	1450	3197	318	12.5	877	34.5	12.4	15.6	398	2675	- - - *		
	19"	255/55 R19	XL	111T	8.0	7.0 - 9.0	3.5	50	1090	2403	265	10.4	763	30.0	10.4	13.1	351	2327	540 A A -	
	18"	LT 285/65 R18	10 S	125R	8.5	8.0 - 10.0	5.6	80	1650	3640	292	11.5	827	32.6	12.4	15.6	373	2522	- - - -	
			D	122					1500	3305										
P 275/65 R18			114T	8.0	7.5 - 9.5	3.6	51	1180	2601	279	11.0	815	32.1	10.4	13.1	368	2486	540 A A -		
LT 275/65 R18		10 S	123R	8.0	7.5 - 9.0	5.6	80	1550	3415	279	11.0	815	32.1	12.4	15.6	368	2486	- - - -		
		D	120					1400	3085											
LT 275/70 R18		10 S	125R	8.0	7.0 - 8.5	5.6	80	1650	3640	279	11.0	843	33.2	12.4	15.6	379	2571	- - - -		
		D	122					1500	3305											
265/60 R18			110T	8.0	7.5 - 9.5	3.6	51	1060	2337	272	10.7	775	30.5	10.4	13.1	353	2364	540 A A -		
265/65 R18			114T	8.0	7.5 - 9.5	3.6	51	1180	2601	272	10.7	801	31.5	10.4	13.1	363	2443	540 A A -		
P 265/70 R18			114T	8.0	7.0 - 9.0	3.6	51	1180	2601	272	10.7	829	32.6	10.4	13.1	374	2528	540 A A -		
LT 265/70 R18		10 S	124S	8.0	7.0 - 9.0	5.6	80	1600	3525	272	10.7	829	32.6	12.4	15.6	374	2528	- - - -		
		D	121					1450	3195											
17"	* 255/60 R18	XL	112T	7.5	7.0 - 9.0	3.5	50	1120	2469	260	10.2	763	30.0	10.4	13.1	348	2327	540 A A *		
	255/70 R18		113T	7.5	6.5 - 8.5	3.6	51	1150	2535	260	10.2	815	32.1	10.4	13.1	368	2486	540 A A -		
	LT 315/70 R17	08 S	121R	9.5	8.0 - 11.0	3.5	50	1450	3195	323	12.7	874	34.4	12.4	15.6	388	2666	- - - -		
		D	118					1320	2910											
	LT 285/70 R17	10 S	121R	8.5	7.5 - 9.0	5.6	80	1450	3195	292	11.5	832	32.8	12.4	15.6	372	2538	- - - -		
		D	118					1320	2910											
	LT 275/65 R17	10 S	121R	8.0	7.5 - 9.5	5.6	80	1450	3195	279	11.0	790	31.1	12.4	15.6	356	2410	- - - -		
		D	118					1320	2910											
	LT 275/70 R17	06 S	114R	8.0	7.0 - 8.5	3.5	50	1180	2600	279	11.0	818	32.2	12.4	15.6	367	2495	- - - -		
		D	110					1060	2335											
	265/65 R17		112T	8.0	7.5 - 9.5	3.6	51	1120	2469	272	10.7	776	30.6	10.4	13.1	350	2367	540 A A -		
	P 265/70 R17		113T	8.0	7.0 - 9.0	3.6	51	1150	2535	272	10.7	804	31.7	10.4	13.1	361	2452	540 A A -		
17"	LT 265/70 R17	10 S	121R	8.0	7.0 - 8.5	5.6	80	1450	3195	272	10.7	804	31.7	12.4	15.6	361	2452	- - - -		
		D	118					1320	2910											
	* 255/65 R17		110T	7.5	7.0 - 9.0	3.6	51	1060	2337	260	10.2	764	30.1	10.4	13.1	345	2330	540 A A *		
	P 255/70 R17		110T	7.5	6.5 - 8.5	3.6	51	1060	2337	260	10.2	790	31.1	10.4	13.1	356	2410	540 A A -		
	LT 255/75 R17	06 S	111R	7.0	6.5 - 8.5	3.5	50	1090	2405	255	10.0	814	32.0	12.4	15.6	365	2483	- - - -		
		D	108					1000	2205											
	P 245/65 R17		105T	7.0	7.0 - 8.5	3.6	51	925	2039	248	9.8	750	29.5	10.4	13.1	340	2288	540 A A -		
	P 245/70 R17		108T	7.0	6.5 - 8.0	3.6	51	1000	2205	248	9.8	776	30.6	10.4	13.1	350	2367	540 A A -		
	LT 245/70 R17	10 S	119R	7.0	6.5 - 8.0	5.6	80	1360	3000	248	9.8	776	30.6	12.4	15.6	350	2367	- - - -		
		D	116					1250	2755											
	LT 245/75 R17	10 S	121R	7.0	6.5 - 7.5	5.6	80	1450	3195	248	9.8	800	31.5	12.4	15.6	359	2440	- - - -		
		D	118					1320	2910											
235/65 R17	XL	108T	7.0	6.5 - 8.5	3.5	50	1000	2205	240	9.4	738	29.1	10.4	13.1	335	2251	540 A A -			
235/75 R17		109T	6.5	6.0 - 8.0	3.6	51	1030	2271	235	9.3	784	30.9	10.4	13.1	353	2391	540 A A -			

XL : Extra Load

* Available at the 2nd Quarter of 2017



AT51

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				
Black Sidewall																	
17"	LT 235/80 R17 10 S 120R	6.5	6.0 - 7.5	5.6	80	1400	3085	235	9.3	808	31.8	12.4	15.6	363	2464	- - -	-
	D 117	1285 2835															
	225/65 R17 XL 106T	6.5	6.0 - 8.0	3.5	50	950	2094	228	9.0	724	28.5	10.4	13.1	330	2208	540	A A -
16"	LT 315/75 R16 08 S 121R	8.5	8.0 - 11.0	3.5	50	1450	3195	313	12.3	878	34.6	12.4	15.6	387	2678	- - -	-
	D 118	1320 2910															
	LT 305/70 R16 10 S 124R	9.0	8.0 - 9.5	4.6	65	1600	3525	311	12.2	834	32.8	12.4	15.6	370	2544	- - -	-
	D 121	1450 3195															
	LT 285/75 R16 10 S 126R	8.0	7.5 - 9.0	5.6	80	1700	3750	286	11.3	834	32.8	12.4	15.6	370	2544	- - -	-
	D 123	1550 3415															
	LT 275/70 R16 08 S 119S	8.0	7.0 - 8.5	4.6	65	1360	2998	279	11.0	792	31.2	12.4	15.6	354	2416	- - -	-
	D 116	1250 2755															
	265/70 R16 112T	8.0	7.0 - 9.0	3.6	51	1120	2469	272	10.7	778	30.6	10.4	13.1	348	2373	540	A A -
	LT 265/70 R16 08 S 117R	8.0	7.0 - 8.5	4.6	65	1285	2835	272	10.7	778	30.6	12.4	15.6	348	2373	- - -	-
	D 114	1180 2600															
	P 265/75 R16 114T	7.5	7.0 - 9.0	3.6	51	1180	2601	267	10.5	804	31.7	10.4	13.1	358	2452	540	A A -
	LT 265/75 R16 10 S 123R	7.5	7.0 - 8.0	5.6	80	1550	3415	267	10.5	804	31.7	12.4	15.6	358	2452	- - -	-
	D 120	1400 3085															
	P 255/70 R16 109T	7.5	6.5 - 8.5	3.6	51	1030	2271	260	10.2	764	30.1	10.4	13.1	343	2330	540	A A -
	245/70 R16 XL 111T	7.0	6.5 - 8.0	3.5	50	1090	2403	248	9.8	750	29.5	10.4	13.1	337	2288	540	A A -
	P 245/75 R16 109T	7.0	6.5 - 8.0	3.6	51	1030	2271	248	9.8	774	30.5	10.4	13.1	347	2361	540	A A -
	LT 245/75 R16 10 S 120R	7.0	6.5 - 8.0	5.6	80	1380	3042	248	9.8	744	29.3	12.4	15.6	335	2269	- - -	-
	D 116	1260 2778															
	P 235/70 R16 104T	7.0	6.0 - 8.0	3.6	51	900	1984	240	9.4	736	29.0	10.4	13.1	332	2245	540	A A -
	LT 235/85 R16 10 S 120R	6.5	6.0 - 7.5	5.6	80	1380	3042	235	9.3	806	31.7	12.4	15.6	359	2458	- - -	-
	D 116	1260 2778															
	LT 225/75 R16 10 S 115R	6.0	6.0 - 7.0	5.6	80	1215	2680	223	8.8	744	29.3	12.4	15.6	335	2269	- - -	-
	D 112	1120 2470															
	215/65 R16 XL 102T	6.5	6.0 - 7.5	3.5	50	850	1874	221	8.7	686	27.0	10.4	13.1	312	2092	540	A A -
	215/70 R16 C 06 S 108R	6.5	5.5 - 7.0	3.9	55	1000	2205	221	8.7	708	27.9	12.7	16.0	321	2159	- - -	-
	D 106	950 2094															
	LT 215/85 R16 10 S 115R	6.0	5.5 - 7.0	5.6	80	1215	2680	216	8.5	772	30.4	12.4	15.6	346	2355	- - -	-
	D 112	1120 2470															
	205/60 R16 92T	6.0	5.5 - 7.5	3.6	51	630	1389	209	8.2	652	25.7	10.4	13.1	299	1989	540	A A -
	205/80 R16 XL 104T	5.5	5.0 - 7.0	3.5	50	900	1984	203	8.0	734	28.9	10.4	13.1	331	2239	540	A A -
	LT 205 R16 08 S 112R	6.0	5.0 - 7.5	4.6	65	1120	2469	208	8.2	736	29.0	12.4	15.6	333	2245	- - -	-
	D 110	1060 2337															
15"	235/75 R15 XL 109T	6.5	6.0 - 8.0	3.5	50	1030	2271	235	9.3	733	28.9	10.4	13.1	328	2236	540	A A -
	LT 235/75 R15 06 S 104R	6.5	6.0 - 7.0	3.5	50	900	1985	235	9.3	733	28.9	12.4	15.6	328	2236	- - -	-
	D 101	825 1820															
	LT 215/75 R15 08 S 106R	6.0	5.5 - 7.0	4.6	65	950	2095	216	8.5	703	27.7	12.4	15.6	316	2144	- - -	-
	D 103	875 1930															
	215 R15 XL 105T	6.0	5.5 - 7.0	3.5	50	925	2039	218	8.6	724	28.5	10.4	13.1	324	2208	540	A A -
	205/60 R15 91T	6.0	5.5 - 7.5	3.6	51	670	1477	209	8.2	627	24.7	10.4	13.1	286	1912	540	A A -
	205/65 R15 94T	6.0	5.5 - 7.5	3.6	51	670	1477	209	8.2	647	25.5	10.4	13.1	294	1973	540	A A -
	205/70 R15 96T	6.0	5.0 - 7.0	3.6	51	710	1565	209	8.2	669	26.3	10.4	13.1	303	2040	540	A A -
	33X12.5 R15 LT 06 108R	10.0	8.5 - 11.0	2.5	35	1000	2205	318	12.5	826	32.5	12.4	15.6	364	2519	- - -	-
	32X11.5 R15 LT 06 113R	9.0	8.0 - 10.0	3.5	50	1150	2535	290	11.4	801	31.5	12.4	15.6	354	2443	- - -	-
	31X10.5 R15 LT 06 109R	8.5	7.0 - 9.0	3.5	50	1030	2270	268	10.6	775	30.5	12.4	15.6	344	2364	- - -	-
	30X9.5 R15 LT 06 104R	7.5	6.5 - 8.5	3.5	50	900	1985	240	9.4	750	29.5	12.4	15.6	334	2288	- - -	-
14"	P 215/75 R14 98T	6.0	5.5 - 7.0	3.6	51	755	1664	216	8.5	678	26.7	10.4	13.1	304	2068	540	A A -
	175/70 R14 XL 88T	5.0	4.5 - 6.0	3.5	50	560	1235	177	7.0	602	23.7	10.4	13.1	274	1836	540	A A -
	27X8.5 R14 LT 08 101R	7.0	6.0 - 7.5	4.6	65	825	1819	218	8.6	674	26.5	12.7	16.0	302	2056	- - -	-