

KL71

Rim	Tire Size			Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	Rim Protector		
						bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				mm	mm
Black Sidewall																				
24"	38X14	R24	LT 08	118Q	11.0	9.0 - 11.5	3.4	50	1320	2910	354	13.9	959	37.8	17.2	21.7	441	2925	-	
22"	37X13.5	R22	LT 10	123Q	11.0	8.5 - 11.0	4.5	60	1550	3415	345	13.6	934	36.8	17.2	21.7	426	2849	-	
20"	38X15.5	R20	LT 08	125Q	12.0	11.0 - 13.0	3.5	50	1650	3635	362	14.3	959	37.8	17.2	21.7	430	2925	-	
	37X13.5	R20	LT 10	127Q	11.0	8.5 - 11.0	4.5	65	1750	3860	345	13.6	934	36.8	17.2	21.7	420	2849	-	
	35X12.5	R20	LT 10	121Q	10.0	8.5 - 11.0	4.5	65	1450	3195	318	12.5	883	34.8	16.2	20.4	400	2693	O	
	33X12.5	R20	LT 10	114Q	10.0	8.5 - 11.0	4.5	65	1180	2600	318	12.5	832	32.8	16.7	21.0	380	2538	O	
18"	35X12.5	R18	LT 08	118Q	10.0	8.5 - 11.0	3.5	50	1320	2910	318	12.5	883	34.8	17.2	21.7	395	2693	-	
	33X12.5	R18	LT 10	118Q	10.0	8.5 - 11.0	3.5	50	1320	2910	318	12.5	883	34.8	17.2	21.7	395	2693	-	
17"	LT315/70	R17	08	S 121Q	9.5	8.5 - 10.0	3.5	50	1450	3195	323	12.7	880	34.6	14.8	18.6	391	2684	O	
			D 118																	
	LT265/70	R17	10	S 121Q	8.0	7.0 - 8.5	5.5	80	1450	3195	272	10.7	810	31.9	14.8	18.6	363	2471	O	
			D 118																	
	35X12.5	R17	LT 10	124Q	10.0	8.0 - 11.0	4.5	65	1600	3525	318	12.5	883	34.8	16.7	21.0	392	2693	O	
16"	LT315/75	R16	10	S 127Q	8.5	8.0 - 10.0	4.5	65	1750	3860	307	12.1	883	34.8	16.7	21.0	389	2693	O	
			D 124																	
	LT305/70	R16	10	S 124Q	9.0	8.0 - 9.5	4.5	65	1600	3525	311	12.2	840	33.1	14.8	18.6	372	2562	O	
			D 121																	
	LT285/75	R16	10	S 126Q	8.0	7.0 - 9.0	5.5	80	1700	3750	286	11.3	840	33.1	15.7	19.8	372	2562	O	
			D 123																	
	LT265/75	R16	08	S 119Q	7.5	7.0 - 9.0	4.5	65	1360	3000	267	10.5	810	31.9	14.8	18.6	361	2471	O	
			D 116																	
	LT265/75	R16	10	S 123Q	7.5	7.0 - 9.0	5.5	80	1550	3415	267	10.5	810	31.9	14.8	18.6	361	2471	O	
			D 120																	
	LT245/75	R16	10	S 120Q	7.0	6.5 - 8.0	5.5	80	1380	3042	248	9.8	780	30.7	14.8	18.6	349	2379	O	
			D 116																	
LT235/85	R16	10	S 120Q	6.5	6.0 - 7.5	5.5	80	1380	3042	235	9.3	812	32.0	14.8	18.6	361	2477	O		
		D 116																		
LT225/75	R16	10	S 115Q	6.0	6.0 - 7.0	6.5	94	1215	2680	223	8.8	744	29.3	14.3	18.0	335	2269	O		
		D 112																		
	205/80	R16	XL	104Q	5.5	5.0 - 6.5	3.5	50	900	1985	203	8.0	741	29.2	14.3	18.0	334	2260	O	
15"	LT235/75	R15	06	S 104Q	6.5	6.0 - 7.0	3.5	50	900	1985	235	9.3	739	29.1	14.3	18.0	330	2254	O	
			D 101																	
	LT215/75	R15	08	S 106Q	6.0	5.0 - 7.0	4.5	65	950	2095	216	8.5	709	27.9	13.8	17.4	318	2162	O	
			D 103																	
		195	R15	XL	100Q	5.5	5.0 - 6.0	3.5	50	800	1765	198	7.8	702	27.6	13.8	17.4	316	2141	O
		35X12.5	R15	LT 06	113Q	10.0	8.5 - 11.0	2.5	35	1160	2555	318	12.5	883	34.8	15.7	19.8	386	2693	O
		33X12.5	R15	LT 06	108Q	10.0	8.5 - 11.0	2.5	35	1000	2205	318	12.5	821	32.3	14.8	18.6	362	2504	O
		32X11.5	R15	LT 06	113Q	9.0	8.0 - 10.0	3.5	50	1150	2535	290	11.4	807	31.8	15.7	19.8	357	2461	O
	31X10.5	R15	LT 06	109Q	8.5	7.0 - 9.0	3.5	50	1030	2270	268	10.6	776	30.6	14.8	18.6	345	2367	O	
	30X9.5	R15	LT 06	104Q	7.5	6.5 - 8.5	3.5	50	900	1985	240	9.4	756	29.8	14.8	18.6	337	2306	O	
14"	27X8.5	R14	LT 06	95Q	7.0	6.0 - 7.5	3.5	50	690	1520	218	8.6	680	26.8	14.3	18.0	304	2074	O	

XL : Extra Load