




Size	LI/SI	PR	Rim	S/W (mm)	O/W (mm)	load Index		Max Pressure (Kpa/Psi)	Sidewall			
						(kg)	(Lbs)					
31x10.50R15LT	109Q	6PR	8 1/2J	268	775	1030	2270	350/50	BSW			POR
32X11.50R15LT	113Q	6PR	9 J	290	801	1150	2535	350/50	BSW			POR
33X12.50R15LT	108Q	6PR	10J	318	826	1000	2205	250/35	BSW			POR
33X12.50R17LT	120Q	10PR	10 J	318	826	1400	3085	450/65	BSW			POR
LT215/75R15	100/97Q	6PR	6 J	216	703	800/730	1765/1610	350/50	BSW			POR
LT235/75R15	104/101Q	6PR	6 1/2J	235	733	900/825	1985/1820	350/50	BSW			POR
LT215/85R16	115/112Q	10PR	6 J	216	772	1215/1120	2680/2470	550/80	BSW			POR
LT225/75R16	115/112N	10PR	6 J	223	744	1215/1120	2680/2470	550/80	BSW			POR
LT235/85R16	120/116Q	10PR	6 1/2J	235	806	1380/1260	3042/2778	550/80	BSW			POR
LT245/75R16	120/116N	10PR	7 J	248	774	1380/1260	3042/2778	550/80	BSW			POR
LT305/70R16	124/121P	10PR	9 J	311	834	1600/1450	3525/3195	450/65	BSW			-
LT315/75R16	127/124Q	10PR	8 1/2J	313	878	1750/1600	3860/3525	450/65	BSW			-