




Size	LI/SI	PR	Rim	S/W (mm)	O/W (mm)	load Index		Max Pressure (Kpa/Psi)	Sidewall			
						(kg)	(Lbs)					
LT235/75R15	104/101Q	6PR	6 1/2J	235	733	900/825	1985/1820	350/50	WSW			POR
LT235/70R16	110/107Q	8PR	7J	240	736	1060/975	2335/2150	450/65	WSW			POR
LT235/85R16	120/116Q	10PR	6 1/2J	235	806	1380/1260	3042/2778	550/80	WSW			POR
LT245/70R16	118/115Q	10PR	7J	248	750	1320/1215	2910/2680	550/80	WSW			POR
LT265/75R16	119/116Q	8PR	7 1/2J	267	804	1360/1250	3000/2755	450/65	WSW			POR
LT265/75R16	123/120Q	10PR	7 1/2J	267	804	1500/1400	3415/3085	550/80	WSW			-
LT285/75R16	116/113Q	6PR	8J	286	834	1250/1150	2755/2535	350/50	WSW			POR
LT285/75R16	126/123Q	10PR	8J	286	834	1700/1550	3750/3415	550/80	WSW			-
LT265/65R17	120/117Q	10PR	8J	272	782	1400/1285	3085/2835	550/80	WSW			POR
LT265/70R17	121/118Q	10PR	8J	272	804	1450/1320	3195/2910	550/80	WSW			POR
LT285/70R17	121/118Q	8PR	8 1/2J	292	832	1450/1320	3195/2910	450/65	WSW			POR
31X10.50R15LT	109Q	6PR	8 1/2J	268	775	1030	2270	350/50	WSW			POR
35X12.50R15LT	113Q	6PR	10J	318	877	1150	2535	250/35	WSW			POR
35X12.50R17LT	121Q	10PR	10J	318	877	1450	3195	450/65	WSW			POR
33X12.50R18LT	118Q	10PR	10J	318	826	1320	2910	450/65	WSW			POR
35X12.50R18LT	118Q	8PR	10J	318	877	1320	2910	350/50	WSW			POR
33X12.50R20LT	114Q	10PR	10J	318	826	1180	2600	450/65	WSW			POR
35X12.50R20LT	121Q	10PR	10J	318	877	1450	3195	450/65	WSW			POR
33X12.50R22LT	109Q	10PR	10J	318	832	1030	2270	450/65	BSW			POR