

Size	LI/SI	PR	Rim	S/W (mm)	O/W (mm)	load Index		Max Pressure (Kpa/Psi)	Sidewall			
						(kg)	(Lbs)					
145R12C	86/84Q	8PR	4.00B	145	537	530/500	1168/1102	450/65	BSW	YES	YES	YES
155R12LT/C	83/81S	6PR	4.50B	157	553	487/462	1074/1019	350/51	BSW	YES	YES	YES
155R12LT/C	88/86S	8PR	4.50B	157	553	560/530	1235/1168	450/65	BSW	YES	YES	YES
155/70R12LT	104/102R	12PR	4.50B	157	523	900/850	1984/1874	650	BSW	YES	YES	YES
5.00R12LT	83/81Q	8PR	3.50B	143	568	487/462	1074/1019	450/65	BSW	YES	YES	YES
5.50R12LT	92/90Q	10PR	3.50B	160	595	630/600	1389/1323	560/81	BSW	YES	YES	YES
5.50R13LT	88/84Q 88/86Q	8PR	4.00B	160	620	560/500	1235/1102	460/67	BSW	YES	YES	YES
145R13C		8PR	4.00B	147	566	560/530	1235/1168	450/65	BSW	YES	YES	YES
155R13LT/C	90/88Q	8PR	4.50B	157	578	600/560	1323/1235	450/65	BSW	YES	YES	YES
165R13LT	94/93R	8PR	4.50B	165	594	670/650	1477/1433	450/65	BSW	YES	YES	YES
165/70R13LT	88/86R	6PR	5.00B	170	562	560/530	1235/1168	375	BSW	YES	YES	YES
175R13LT	97/95R	8PR	5.00B	177	610	730/690	1609/1521	450/65	BSW	YES	YES	YES
165R14LT	91/90R	6PR	4 1/2J	165	620	615/600	1356/1323	350/51	BSW	YES	YES	YES
175R14LT	99/97R	8PR	5J	178	634	775/730	1709/1609	450/65	BSW	YES	YES	YES
175/70R14LT	95/93S	6PR	5J	177	602	690/650	1521/1433	375/54	BSW	YES	YES	YES
175/75R14LT	94/91R	8PR	5J	177	618	670/615	1477/1356	450/65	BSW	YES	YES	YES
165/70R13	79T	--	5.00B	170	562	437	964	300/44	BSW	-	-	-
165/70R14	81T	--	5J	170	588	462	1019	300/44	BSW	-	-	-