

# KR26

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG		Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"					
<b>Black Sidewall</b>																		
<b>17"</b>	<b>235/55 R17 99H</b>	7.5	6.5 - 8.5	3.0	44	775	1709	245	9.6	690	27.2	7.5	9.4	317	2105	520	A B	-
	<b>225/50 R17 94H</b>	7.0	6.0 - 8.0	3.0	44	670	1477	233	9.2	658	25.9	7.5	9.4	304	2007	520	A B	-
	<b>225/55 R17 97H</b>	7.0	6.0 - 8.0	3.0	44	730	1609	233	9.2	680	26.8	7.5	9.4	313	2074	520	A B	-
	<b>225/65 R17 102H</b>	6.5	6.0 - 8.0	3.0	44	850	1874	228	9.0	724	28.5	7.5	9.4	330	2208	520	A B	-
	<b>215/55 R17 94H</b>	7.0	6.0 - 7.5	3.0	44	670	1477	226	8.9	668	26.3	7.5	9.4	308	2037	520	A B	-
<b>16"</b>	<b>225/55 R16 95H</b>	7.0	6.0 - 8.0	3.0	44	690	1521	233	9.2	654	25.7	7.5	9.4	300	1995	520	A B	-
	<b>225/60 R16 98H</b>	6.5	6.0 - 8.0	3.0	44	750	1653	228	9.0	676	26.6	7.5	9.4	308	2062	520	A B	-
	<b>225/65 R16 100H</b>	6.5	6.0 - 8.0	3.0	44	800	1764	228	9.0	698	27.5	7.5	9.4	317	2129	520	A B	-
	<b>215/55 R16 93H</b>	7.0	6.0 - 7.5	3.0	44	650	1433	226	8.9	642	25.3	7.5	9.4	295	1958	520	A B	-
	<b>215/60 R16 95H</b>	6.5	6.0 - 7.5	3.0	44	690	1521	221	8.7	664	26.1	7.5	9.4	304	2025	520	A B	-
	<b>215/65 R16 98H</b>	6.5	6.0 - 7.5	3.0	44	750	1653	221	8.7	686	27.0	7.5	9.4	312	2092	520	A B	-
	<b>205/55 R16 91H</b>	6.5	5.5 - 7.5	3.0	44	615	1356	214	8.4	632	24.9	7.5	9.4	291	1928	520	A B	-
	<b>205/60 R16 92H</b>	6.0	5.5 - 7.5	3.0	44	630	1389	209	8.2	652	25.7	7.5	9.4	299	1989	520	A B	-
	<b>205/65 R16 95H</b>	6.0	5.5 - 7.5	3.0	44	690	1521	209	8.2	672	26.5	7.5	9.4	307	2050	520	A B	-
	<b>195/60 R16 89H</b>	6.0	5.5 - 7.0	3.0	44	580	1279	201	7.9	640	25.2	7.5	9.4	294	1952	520	A B	-
<b>15"</b>	<b>225/70 R15 100T</b>	6.5	6.0 - 7.0	3.0	44	800	1764	228	9.0	697	27.4	7.5	9.7	314	2126	520	A B	-
	<b>215/65 R15 96H</b>	6.5	6.0 - 7.5	3.0	44	710	1565	221	8.7	661	26.0	7.5	9.4	300	2016	520	A B	-
	<b>215/70 R15 98T</b>	6.5	5.5 - 7.0	3.0	44	750	1653	221	8.7	683	26.9	7.5	9.4	308	2083	520	A B	-
	<b>205/60 R15 91H</b>	6.0	5.5 - 7.5	3.0	44	615	1356	209	8.2	627	24.7	7.5	9.4	286	1912	520	A B	-
	<b>205/65 R15 94H</b>	6.0	5.5 - 7.5	3.0	44	670	1477	209	8.2	647	25.5	7.5	9.4	294	1973	520	A B	-
	<b>205/70 R15 96T</b>	6.0	5.0 - 7.0	3.0	44	710	1565	209	8.2	669	26.3	7.5	9.4	303	2040	520	A B	-
	<b>205/75 R15 97T</b>	5.5	5.0 - 7.0	3.0	44	730	1609	203	8.0	689	27.1	7.5	9.4	311	2101	520	A B	-
	<b>195/55 R15 85H</b>	6.0	5.0 - 7.0	3.0	44	515	1135	201	7.9	595	23.4	7.5	9.4	274	1815	520	A B	-
	<b>195/60 R15 88H</b>	6.0	5.5 - 7.0	3.0	44	560	1235	201	7.9	615	24.2	7.5	9.4	282	1876	520	A B	-
	<b>195/65 R15 91H</b>	6.0	5.5 - 7.0	3.0	44	615	1356	201	7.9	635	25.0	7.5	9.4	290	1937	520	A B	-
	<b>185/60 R15 84H</b>	5.5	5.0 - 6.5	3.0	44	500	1102	189	7.4	603	23.7	7.5	9.4	277	1839	520	A B	-
	<b>185/65 R15 88H</b>	5.5	5.0 - 6.5	3.0	44	560	1235	189	7.4	621	24.4	7.5	9.4	284	1894	520	A B	-
	<b>175/50 R15 75H</b>	5.5	5.0 - 6.0	3.0	44	387	853	182	7.2	557	21.9	*	*	259	1699	520	A B	-
	<b>175/65 R15 84H</b>	5.0	5.0 - 6.0	3.0	44	500	1102	177	7.0	609	24.0	7.5	9.4	279	1857	520	A B	-
<b>14"</b>	<b>195/60 R14 86H</b>	6.0	5.5 - 7.0	3.0	44	530	1168	201	7.9	590	23.2	7.5	9.4	269	1800	460	A B	-
	<b>195/70 R14 91H</b>	6.0	5.0 - 6.5	3.0	44	615	1356	201	7.9	630	24.8	7.5	9.4	285	1922	460	A B	-
	<b>185/60 R14 82H</b>	5.5	5.0 - 6.5	3.0	44	475	1047	189	7.4	578	22.8	7.5	9.4	265	1763	460	A B	-
	<b>185/65 R14 86H</b>	5.5	5.0 - 6.5	3.0	44	530	1168	189	7.4	596	23.5	7.5	9.4	272	1818	460	A B	-
	<b>185/70 R14 88T</b>	5.5	4.5 - 6.0	3.0	44	560	1235	189	7.4	616	24.3	7.5	9.4	279	1879	460	A B	-
	<b>175/65 R14 82H</b>	5.0	5.0 - 6.0	3.0	44	475	1047	177	7.0	584	23.0	7.5	9.4	267	1781	460	A B	-
	<b>175/70 R14 84T</b>	5.0	4.5 - 6.0	3.0	44	500	1102	177	7.0	602	23.7	7.5	9.4	274	1836	460	A B	-
	<b>165/60 R14 75H</b>	5.0	4.5 - 6.0	3.0	44	387	853	170	6.7	554	21.8	7.5	9.4	255	1690	460	A B	-
	<b>165/70 R14 81T</b>	5.0	4.0 - 5.5	3.0	44	462	1019	170	6.7	588	23.1	7.5	9.4	268	1793	460	A B	-
	<b>155/65 R14 75H</b>	4.5	4.5 - 5.5	3.0	44	387	853	157	6.2	558	22.0	7.0	8.8	257	1702	460	A B	-



# KR26

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				
<b>Black Sidewall</b>																	
<b>13"</b>	<b>175/60 R13 77H</b>	5.0	5.0 - 6.0	3.0	44	412	908	177	7.0	540	21.3	7.5	9.4	247	1647	460	A B -
	<b>175/70 R13 82H</b>	5.0	4.5 - 6.0	3.0	44	475	1047	177	7.0	576	22.7	7.5	9.4	261	1757	460	A B -
	<b>165/65 R13 77H</b>	5.0	4.5 - 6.0	3.0	44	412	908	170	6.7	544	21.4	7.5	9.4	248	1659	460	A B -
	<b>165/70 R13 79T</b>	5.0	4.0 - 5.5	3.0	44	437	853	170	6.7	562	22.1	7.5	9.4	256	1714	460	A B -
	<b>155/65 R13 73H</b>	4.5	4.5 - 5.5	3.0	44	365	805	157	6.2	532	20.9	7.0	8.8	244	1623	460	A B -
	<b>155/70 R13 75H</b>	4.5	4.0 - 5.0	3.0	44	387	853	157	6.2	548	21.6	7.5	9.4	250	1671	460	A B -
	<b>155/80 R13 79T</b>	4.5	4.0 - 5.0	3.0	44	437	963	157	6.2	578	22.8	7.0	8.8	262	1763	460	A B -
	<b>145/80 R13 75T</b>	4.0	3.5 - 5.0	3.0	44	387	853	145	5.7	562	22.1	7.0	8.8	256	1714	460	A B -
<b>White Sidewall</b>																	
<b>13"</b>	<b>165/80 R13 83T</b>	4.5	4.0 - 5.5	3.0	44	487	1074	165	6.5	594	23.4	7.5	9.4	568	1812	460	A B -
<b>Outlined White Letter</b>																	
<b>12"</b>	<b>165/70 R12 77H</b>	4.5	4.0 - 5.0	3.0	44	365	805	157	6.2	523	20.6	7.0	8.8	237	1595	-	- - -
	<b>155/70 R12 73H</b>	5.0	4.0 - 5.5	3.0	44	412	908	170	6.7	537	21.1	7.0	8.8	243	1638	-	- - -