

TA31

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				
Black Sidewall																	
20"	245/50 R20 102V	7.5	6.5 - 8.5	3.5	51	850	1874	246	9.7	756	29.8	7.9	10.0	351	2306	500	A A O
19"	275/40 R19 XL 105W	9.5	9.0 - 10.5	3.4	50	925	2039	278	10.9	703	27.7	8.0	10.1	327	2144	500	A A O
	245/45 R19 XL 102W	8.0	7.5 - 9.0	3.4	50	850	1874	243	9.6	703	27.7	8.0	10.1	327	2144	500	A A O
18"	245/40 R18 XL 97V	8.5	8.0 - 9.5	3.4	50	730	1609	248	9.8	653	25.7	8.0	10.1	305	1992	500	A A O
	245/45 R18 XL 100V	8.0	7.5 - 9.0	3.4	50	800	1764	243	9.6	677	26.7	8.0	10.1	314	2065	500	A A O
	245/50 R18 XL 104V	7.5	7.0 - 8.5	3.4	50	900	1984	253	10.0	703	27.7	8.0	10.1	324	2144	500	A A O
	235/45 R18 94V	7.5	7.5 - 9.0	3.0	44	670	1477	230	9.1	669	26.3	8.2	10.3	311	2040	500	A A O
	235/50 R18 XL 101V	7.5	6.5 - 8.5	3.4	50	825	1819	245	9.6	693	27.3	8.0	10.1	321	2114	500	A A O
	225/40 R18 88V	8.0	7.5 - 9.0	3.0	44	565	1246	230	9.1	637	25.1	8.2	10.3	299	1943	500	A A O
	225/45 R18 91V	7.5	7.0 - 8.5	3.5	51	615	1356	225	8.9	660	26.0	8.0	10.1	313	2010	500	A A O
	225/45 R18 XL 95V	7.5	7.0 - 8.5	3.4	50	690	1521	225	8.9	659	25.9	8.0	10.1	307	2010	500	A A O
	215/40 R18 XL 89V	7.5	7.0 - 8.5	3.4	50	580	1279	218	8.6	629	24.8	8.0	10.1	296	1918	500	A A O
	215/45 R18 XL 93V	7.0	7.0 - 8.0	3.4	50	650	1433	213	8.4	651	25.6	8.0	10.1	304	1986	500	A A O
17"	245/45 R17 XL 99V	8.0	7.5 - 9.0	3.4	50	775	1709	243	9.6	652	25.7	8.0	10.1	302	1989	500	A A O
	235/55 R17 XL 103V	7.5	6.5 - 8.5	3.4	50	875	1929	245	9.6	690	27.2	8.0	10.1	317	2105	500	A A O
	235/65 R17 104H	7.5	7.0 - 8.5	3.5	51	900	1984	251	9.9	736	28.9	7.9	10.0	332	2243	500	A A -
	225/45 R17 91H	7.5	7.0 - 8.5	3.5	51	615	1356	224	8.8	632	24.9	7.7	9.7	292	1985	500	A A O
	225/45 R17 91W	7.0	7.0 - 8.5	3.5	51	615	1356	220	8.7	634	25.0	8.0	10.1	298	1928	500	A A O
	225/45 R17 XL 94V	7.5	7.0 - 8.5	3.4	50	670	1477	225	8.9	634	25.0	8.0	10.1	295	1934	500	A A O
	225/50 R17 XL 98V	7.0	6.0 - 8.0	3.4	50	750	1653	233	9.2	658	25.9	8.0	10.1	304	2007	500	A A O
	225/55 R17 97V	7.0	6.0 - 8.0	3.0	44	730	1609	233	9.2	680	26.8	8.2	10.3	313	2074	500	A A O
	225/60 R17 99H	6.5	6.0 - 8.0	3.0	44	775	1709	228	9.0	702	27.6	8.0	10.1	321	2141	500	A A O
	215/45 R17 XL 91V	7.0	7.0 - 8.0	3.4	50	615	1356	213	8.4	626	24.6	8.0	10.1	292	1909	500	A A -
	215/50 R17 XL 95V	7.0	6.0 - 7.5	3.4	50	690	1521	226	8.9	648	25.5	8.0	10.1	300	1976	500	A A O
	215/55 R17 94V	7.0	6.0 - 7.5	3.0	44	670	1477	226	8.9	668	26.3	8.2	10.3	308	2037	500	A A O
	205/50 R17 XL 93V	6.5	5.5 - 7.5	3.4	50	650	1433	214	8.4	638	25.1	8.0	10.1	296	1946	500	A A -
205/55 R17 XL 95V	6.5	5.5 - 7.5	3.4	50	690	1521	214	8.4	658	25.9	8.0	10.1	304	2007	500	A A O	
16"	235/55 R16 98H	7.5	6.5 - 8.5	3.5	51	750	1653	245	9.6	664	26.1	8.0	10.1	304	2025	500	A A O
	235/55 R16 98V	7.5	6.5 - 8.5	3.5	51	750	1653	245	9.6	664	26.1	8.0	10.1	304	2025	500	A A O
	235/60 R16 100H	7.0	6.5 - 8.5	3.0	44	800	1764	240	9.4	688	27.1	8.0	10.1	313	2098	500	A A O
	225/55 R16 XL 99H	7.0	6.0 - 8.0	3.4	50	775	1709	233	9.2	654	25.7	8.0	10.1	300	1995	500	A A -
	225/60 R16 98H	6.5	6.0 - 8.0	3.0	44	750	1653	228	9.0	676	26.6	8.0	10.1	308	2062	500	A A O
	225/65 R16 100T	6.5	6.0 - 8.0	3.0	44	800	1764	228	9.0	698	27.5	8.0	10.1	317	2129	500	A A -
	215/45 R16 XL 90V	7.0	7.0 - 8.0	3.4	50	600	1323	213	8.4	600	23.6	8.0	10.1	279	1830	500	A A -
	215/55 R16 XL 97H	7.0	6.0 - 7.5	3.4	50	730	1609	226	8.9	642	25.3	8.0	10.1	295	1958	500	A A O
	215/60 R16 95H	6.5	6.0 - 7.5	3.0	44	690	1521	221	8.7	664	26.1	8.2	10.3	304	2025	500	A A O
	215/65 R16 98H	6.5	6.0 - 7.5	3.0	44	750	1653	221	8.7	686	27.0	8.0	10.1	312	2092	500	A A -
	205/55 R16 91H	6.5	5.5 - 7.5	3.5	51	615	1356	214	8.4	632	24.9	8.0	10.1	291	1928	500	A A -
	205/60 R16 92H	6.0	5.5 - 7.5	3.0	44	630	1389	209	8.2	652	25.7	8.2	10.3	299	1989	500	A A O
	205/65 R16 95H	6.0	5.5 - 7.5	3.0	44	690	1521	209	8.2	672	26.5	8.2	10.3	307	2050	500	A A -
	205/65 R16 95V	6.0	5.5 - 7.5	3.0	44	690	1521	214	8.4	668	26.3	8.0	10.1	302	2041	500	A A -
	195/50 R16 84H	6.0	5.5 - 7.0	3.5	51	500	1102	201	7.9	602	23.7	8.0	10.1	279	1836	500	A A -
185/40 R16 73H	6.5	6.5 - 7.5	3.5	51	365	805	188	7.4	554	21.8	8.0	10.1	261	1690	500	A A -	

XL : Extra Load



TA31

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				
Black Sidewall																	
15"	215/65 R15 96H	6.5	6.0 - 7.5	3.0	44	710	1565	221	8.7	661	26.0	8.0	10.1	300	2016	500	A A -
	205/60 R15 91H	6.0	5.5 - 7.5	3.0	44	615	1356	209	8.2	627	24.7	8.0	10.1	286	1912	500	A A -
	205/65 R15 94H	6.0	5.5 - 7.5	3.0	44	670	1477	209	8.2	647	25.5	8.2	10.3	294	1973	500	A A -
	195/55 R15 85H	6.0	5.5 - 7.0	3.0	44	515	1135	201	7.9	595	23.4	8.2	10.3	274	1815	500	A A -
	195/60 R15 88H	6.0	5.5 - 7.0	3.0	44	560	1235	201	7.9	615	24.2	8.0	10.1	282	1876	500	A A -
	195/65 R15 91T	6.0	5.5 - 7.0	3.5	51	615	1356	201	7.9	635	25.0	8.2	10.3	290	1937	500	A A -
	195/65 R15 91H	6.0	5.5 - 7.0	3.0	44	615	1356	201	7.9	635	25.0	8.2	10.3	290	1937	500	A A -
	185/55 R15 82H	6.0	5.5 - 7.0	3.0	44	475	1047	194	7.6	585	23.0	8.0	10.1	270	1784	500	A A -
	P185/60 R15 84H	6.0	5.0 - 6.5	3.0	44	500	1102	191	7.5	602	23.7	8.0	10.1	277	1836	500	A A -
	P185/65 R15 86T	5.5	5.0 - 6.5	3.0	44	530	1168	189	7.4	620	24.4	7.9	10.0	290	299	500	A A -
	185/65 R15 88H	5.5	5.0 - 6.5	3.0	44	560	1235	189	7.4	621	24.4	8.0	10.1	284	1894	500	A A -
	175/50 R15 75H	5.5	5.0 - 6.0	3.0	44	387	853	182	7.2	557	21.9	8.2	10.3	259	1699	500	A A -
165/60 R15 77H	5.0	4.5 - 6.0	3.0	44	412	908	170	6.7	579	22.8	8.0	10.1	268	1766	500	A A -	
14"	195/60 R14 86H	6.0	5.5 - 7.0	3.0	44	530	1168	201	7.9	590	23.2	8.0	10.1	269	1800	500	A A -
	195/70 R14 91H	6.0	5.0 - 6.5	3.0	44	615	1356	201	7.9	630	24.8	8.0	10.1	285	1922	500	A A -
	185/65 R14 86H	5.5	5.0 - 6.5	3.0	44	530	1168	189	7.4	596	23.5	8.2	10.3	272	1818	500	A A -
	165/60 R14 75H	5.0	4.5 - 6.0	3.0	44	387	853	170	6.7	554	21.8	8.2	10.3	255	1690	500	A A -
	165/65 R14 79T	5.0	4.5 - 6.0	3.0	44	437	963	170	6.7	566	22.3	7.1	8.9	262	1779	500	A A -
	155/70 R14 77H	4.5	4.0 - 5.0	3.0	44	412	908	157	6.2	574	22.6	8.0	10.1	263	1751	500	A A -

XL : Extra Load