

# TA71

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG		Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"					
<b>Black Sidewall</b>																		
19"	275/40 ZR19 XL 105W	9.5	9.0 - 11.0	3.4	50	925	2039	278	10.9	703	27.7	9.2	11.6	327	2144	500	A A	O
	255/40 ZR19 XL 100W	9.0	8.5 - 10.0	3.4	50	800	1764	266	10.5	688	27.1	9.2	11.6	321	2098	500	AA A	O
	* 255/45 R19 100V	8.5	8.0 - 9.5	3.5	51	800	1764	265	10.4	723	28.5	9.2	11.6	335	2205	600	A A	*
	255/45 ZR19 XL 104W	8.5	8.0 - 9.5	3.4	50	900	1984	255	10.0	713	28.1	9.2	11.6	331	2175	500	A A	O
	245/40 ZR19 XL 98W	8.5	8.0 - 9.5	3.4	50	750	1653	254	10.0	680	26.8	9.2	11.6	318	2074	500	AA A	O
	245/45 ZR19 XL 102W	8.0	7.5 - 9.0	3.4	50	850	1874	249	9.8	704	27.7	9.2	11.6	328	2147	500	AA A	O
18"	255/45 ZR18 99W	8.5	8.0 - 9.5	3.5	51	775	1709	260	10.2	688	27.1	9.2	11.6	319	2098	500	AA A	O
	245/40 ZR18 XL 97W	8.5	8.0 - 9.5	3.4	50	730	1609	254	10.0	654	25.7	9.2	11.6	305	1995	500	AA A	O
	245/45 ZR18 XL 100W	8.0	7.5 - 9.0	3.4	50	800	1764	248	9.8	678	26.7	9.2	11.6	315	2068	500	AA A	O
	245/50 R18 XL 104V	7.5	7.0 - 8.5	3.4	50	900	1984	259	10.2	704	27.7	9.2	11.6	325	2147	600	A A	O
	235/40 ZR18 XL 95W	8.5	8.0 - 9.5	3.4	50	690	1521	245	9.6	646	25.4	9.2	11.6	302	1970	500	AA A	O
	235/45 R18 XL 98V	8.0	7.5 - 9.0	3.4	50	750	1653	244	9.6	670	26.4	9.2	11.6	312	2044	600	A A	O
	235/50 ZR18 97W	7.5	6.5 - 8.5	3.5	51	730	1609	255	10.0	694	27.3	9.2	11.6	321	2117	500	AA A	O
	235/55 R18 100V	7.5	6.5 - 8.5	3.5	51	800	1764	251	9.9	716	28.2	9.2	11.6	330	2184	600	A A	O
	225/40 R18 XL 92V	8.0	7.5 - 9.0	3.4	50	630	1389	234	9.2	638	25.1	9.2	11.6	299	1946	600	A A	O
	225/45 ZR18 XL 95W	7.5	7.0 - 8.5	3.4	50	690	1521	232	9.1	660	26.0	9.2	11.6	308	2013	500	AA A	O
	225/50 ZR18 95W	7.0	6.0 - 8.0	3.5	51	690	1521	243	9.6	684	26.9	9.2	11.6	317	2086	500	AA A	O
	225/60 R18 100V	6.5	6.0 - 8.0	3.5	51	800	1764	240	9.4	728	28.7	9.2	11.6	334	2220	600	A A	O
17"	255/40 ZR17 94W	9.0	8.5 - 10.0	3.5	51	670	1477	266	10.5	637	25.1	9.2	11.6	296	1943	500	AA A	O
	245/40 ZR17 91W	8.5	8.0 - 9.5	3.5	51	615	1356	253	10.0	629	24.8	9.2	11.6	293	1918	500	AA A	O
	245/45 ZR17 XL 99W	8.0	7.5 - 9.0	3.4	50	775	1709	248	9.8	653	25.7	9.2	11.6	302	1992	500	AA A	O
	245/50 R17 99V	7.5	7.0 - 8.5	3.5	51	775	1709	261	10.3	679	26.7	9.2	11.6	312	2071	600	A A	O
	235/45 ZR17 XL 97W	8.0	7.5 - 9.0	3.4	50	730	1609	245	9.6	645	25.4	9.2	11.6	299	1967	500	AA A	O
	235/50 R17 96V	7.5	6.5 - 8.5	3.5	51	710	1565	254	10.0	669	26.3	9.2	11.6	308	2040	600	A A	O
	235/55 ZR17 XL 103W	7.5	6.5 - 8.5	3.4	50	875	1929	255	10.0	691	27.2	9.2	11.6	317	2108	500	AA A	O
	225/45 ZR17 91W	7.5	7.0 - 8.5	3.5	51	615	1356	229	9.0	635	25.0	9.2	11.6	295	1937	500	AA A	O
	225/50 ZR17 XL 98W	7.0	6.0 - 8.0	3.4	50	750	1653	237	9.3	659	25.9	9.2	11.6	305	2010	500	AA A	O
	225/55 R17 XL 101V	7.0	6.0 - 8.0	3.4	50	825	1819	245	9.6	681	26.8	9.2	11.6	313	2077	600	A A	O
	215/50 R17 XL 95V	7.0	6.0 - 7.5	3.4	50	690	1521	234	9.2	649	25.6	9.2	11.6	301	1979	600	A A	O
	215/55 R17 94V	7.0	6.0 - 7.5	3.5	51	670	1477	234	9.2	669	26.3	9.2	11.6	308	2040	600	A A	O
205/50 R17 XL 93V	6.5	5.5 - 7.5	3.4	50	650	1433	220	8.7	639	25.2	9.2	11.6	297	1949	600	A A	O	
16"	225/55 R16 95V	7.0	6.0 - 8.0	3.5	51	690	1521	243	9.6	655	25.8	9.2	11.6	300	1998	600	A A	O
	225/60 R16 98V	6.5	6.0 - 8.0	3.5	51	750	1653	236	9.3	677	26.7	9.2	11.6	309	2065	600	A A	O
	215/55 R16 XL 97V	7.0	6.0 - 7.5	3.4	50	730	1609	234	9.2	643	25.3	9.2	11.6	295	1961	600	A A	O
	215/60 R16 95V	6.5	6.0 - 7.5	3.5	51	690	1521	227	8.9	665	26.2	9.2	11.6	304	2028	600	A A	O
	205/55 R16 91V	6.5	5.5 - 7.5	3.5	51	615	1356	222	8.7	633	24.9	9.2	11.6	292	1931	600	A A	O
	205/60 R16 XL 96V	6.0	5.5 - 7.5	3.4	50	710	1565	216	8.5	653	25.7	9.2	11.6	299	1992	600	A A	O
	205/65 R16 95V	6.0	5.5 - 7.5	3.5	51	690	1521	215	8.5	673	26.5	9.2	11.6	307	2053	600	A A	O
15"	205/65 R15 94V	6.0	5.5 - 7.5	3.5	51	670	1477	215	8.5	648	25.5	9.2	11.6	295	1976	600	A A	O
	195/60 R15 88V	6.0	5.5 - 7.0	3.5	51	560	1235	202	8.0	616	24.3	9.2	11.6	282	1879	600	A A	O
	195/65 R15 91V	6.0	5.5 - 7.0	3.5	51	615	1356	208	8.2	636	25.0	9.2	11.6	290	1940	600	A A	O

XL : Extra Load

\* Available at the 3rd Quarter of 2017